Note: This datasheet may be out of date

 $\underline{ \text{Please download the latest datasheet of LFD21859MDP1A049 from the official website of Murata Manufacturing} \\$

Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=LFD21859MDP1A049

LFD21859MDP1A049












Appearance & Shape







Adiplexer branching low and high band.

- 1. Low insertion loss.
- 2. Small size, low-profiled and light weight.
- 3. Absolutely no adjustment required.
- 4. Reflow solderable.



Packaging Information

Packaging	Specifications	Minimum Order Quantity
-	180mm Embossed Tape	4000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date

 $\underline{ \text{Please download the latest datasheet of LFD21859MDP1A049 from the official website of Murata Manufacturing} \\$

1.05mm

Thickness(max.)

 $\underline{\text{Co., Ltd.}} \\ \text{https://www.murata.com/en-us/products/productdetail?partno=LFD21859MDP1A049} \\$

LFD21859MDP1A049



Applications	CDMA	
Center Frequency{P1}(f1)	1920.00MHz	
Frequency Range{P1}(f1)	1850.00MHz to 1990.00MHz	
Center Frequency{P2}(f2)	859.00MHz	
Frequency Range{P2}(f2)	824.00MHz to 894.00MHz	
Insertion Loss I)(P1-P3 in f1)	0.45dB max. (at 25°C)	
Insertion Loss II)(P1-P3 in f1)	0.55dB max. (-40 to +85°C)	
Insertion Loss I)(P2-P3 in f2)	0.40dB max. (at 25°C)	
Insertion Loss II)(P2-P3 in f2)	0.50dB max. (-40 to +85°C)	
Attenuation{P1-P3}(in f2)	19.0dB min.	
Attenuation{P2-P3}(in f1)	20.0dB min.	
VSWR{P1}(in f1)	1.70 max.	
VSWR{P2}(in f2)	1.70 max.	
VSWR{P3}(in f1,f2)	1.70 max.	
Power Capacity	3W	
Operating Temperature Range	-40℃ to 85℃	
L x W (size)	2.00x1.25mm	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/


Last updated :2019/04/23


Note: This datasheet may be out of date

 $\underline{ \text{Please download the latest datasheet of LFD21859MDP1A049 from the official website of Murata Manufacturing} \\$ Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=LFD21859MDP1A049

LFD21859MDP1A049









Attenuation(P2-P3), VSWR(P3)







Insertion Loss(P2-P3), VSWR(P2)

Attenuation(P1-P3), VSWR(P3)

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/04/23