Note: This datasheet may be out of date

 $\underline{ \text{Please download the latest datasheet of LFD21920MDP1A048 from the official website of Murata Manufacturing} \\$

 $\underline{\text{Co., Ltd.}} \\ \text{https://www.murata.com/en-us/products/productdetail?partno=LFD21920MDP1A048} \\$

LFD21920MDP1A048












Appearance & Shape







Adiplexer branching low and high band.

- 1. Low insertion loss.
- 2. Small size, low-profiled and light weight.
- 3. Absolutely no adjustment required.
- 4. Reflow solderable.



Packaging Information

Packaging	Specifications	Minimum Order Quantity
-	180mm Embossed Tape	4000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/04/23



Note: This datasheet may be out of date

 $\underline{ \text{Please download the latest datasheet of LFD21920MDP1A048 from the official website of Murata Manufacturing} \\$

1.05mm

Thickness(max.)

 $\underline{\text{Co., Ltd.}} \\ \text{https://www.murata.com/en-us/products/productdetail?partno=LFD21920MDP1A048} \\$

LFD21920MDP1A048



Applications	GSM	
Center Frequency{P1}(f1)	1795.00MHz	
Frequency Range{P1}(f1)	1710.00MHz to 1880.00MHz	
Center Frequency{P2}(f2)	920.00MHz	
Frequency Range{P2}(f2)	880.00MHz to 960.00MHz	
Insertion Loss I)(P1-P3 in f1)	0.55dB max. (at 25°C)	
Insertion Loss II)(P1-P3 in f1)	0.65dB max. (-40 to +85°C)	
Insertion Loss I)(P2-P3 in f2)	0.50dB max. (at 25°C)	
Insertion Loss II)(P2-P3 in f2)	0.60dB max. (-40 to +85°C)	
Attenuation{P1-P3}(in f2)	20.0dB min.	
Attenuation{P2-P3}(in f1)	16.0dB min.	
VSWR{P1}(in f1)	1.80 max.	
VSWR{P2}(in f2)	1.80 max.	
VSWR{P3}(in f1,f2)	1.80 max.	
Power Capacity	3W	
Operating Temperature Range	-40℃ to 85℃	
L x W (size)	2.00x1.25mm	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





URL: https://www.murata.com/

Last updated :2019/04/23

LFD21920MDP1A048









Attenuation(P2-P3), VSWR(P3)

Attenuation(P1-P3), VSWR(P3)





Insertion Loss(P2-P3), VSWR(P2)

Insertion Loss(P1-P3), VSWR(P1)

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/04/23