



LJ5 - DC24V - S - H - A

Relay Type: _____

Coil Voltage:- 3 ~ 24VDC _____

Type of Sealing: S; Plastic Sealed Type _____

Coil Power:- H:- 0.45W, D:- 0.2W _____

Contact Form: A:1 Form A _____

Features	Dimension L * W * H (mm)	18.4 * 10.2 * 15.3				
	Terminal Type	PCB				
	Weight	6 gm Approximately				
Contact Data	Contact Form	1A				
	Contact Material	Ag Alloy				
	Contact Capacity	5A @250VAC / 5A @30VDC				
	Contact Resistance	100 mΩ @ 1A, 6 VDC				
	Coil Voltage (DC)	3 ~ 24VDC				
Coil Data	Coil Power Consumption	0.45W, 0.2W				
	Coil Specification	Coil Voltage	Coil Resistance (Ω) ±10%	Pull in Voltage (VDC)	Drop Out Voltage (VDC)	
			0.45W	0.2W		
		5 VDC	55	125	75%	10%
		12 VDC	320	720	75%	10%
24 VDC	1280	2880	75%	10%		
General Data	Dielectric Strength	1000 VAC (Between Open Contacts)				
		2500 VAC (Between Coil & Contacts)				
	Insulation Resistance	100 MΩ 500 VDC				
	Electrical Life	1 x 10 ⁵				
	Mechanical Life	1 x 10 ⁷				
Operating Temperature	-40 °C ~ + 70°C					
Mounting Diagram						
Application	Television, Stereo, Microwave, Air Conditioner, Refrigerator, Iron, Electrical Boiler, Satellite Receiver, etc.					