


1.5A Very L.D.O Voltage Regulator

LM27150/27151/27152

FEATURES

- High Current Capability 1.5A
- Low Dropout Voltage 350mV
- Low Ground Current
- Accurate 1% Guaranteed Initial Tolerance
- Extremely Fast Transient Response
- Reverse-Battery and "Load Dump" Protection
- Zero-Current Shutdown Mode(5-Pin Version)
- Error Flag Signals Output out-of-Regulation (5-Pin Version)
- Also Characterized For Smaller Loads With Industry -Leading Performance specifications
- Fixed Voltage and Adjustable Versions
- Moisture Sensitivity Level 3



APPLICATION

- Battery Powered Equipment
- High-Efficiency " Green" Computer System
- Automotive Electronics
- High-Efficiency Linear Power Supplies
- High-Efficiency Post-Regulator For Switching Supply

DESCRIPTION

The LM27150, LM27151 and LM27152 are high current, high accuracy, and low-dropout voltage regulators. Using process with a PNP pass element, these regulators feature 350mV (full load) dropout voltages and very low ground current. These devices also find applications in lower current, low dropout-critical systems, where their tiny dropout voltage and ground current values are important attributes.

The LM27150, LM27151 and LM27152 are fully protected against over current faults, reversed input polarity, reversed lead insertion, over temperature operation, and positive and negative transient voltage spikes. LM27151 features logic level enable control and an error flag which signals whenever the output falls out of regulation. On the LM27151 and LM27152, the ENABLE pin may be tied to V_{in} if it is not required for ON/OFF control.

ORDERING INFORMATION

Device	Package
LM27150T-X.X	TO-220 3L / 5L
LM27151T-X.X	
LM27152T	
LM27150R-X.X	TO-263 3L / 5L
LM27151R-X.X	
LM27152R	
LM27150RS-X.X	TO-252 3L / 5L
LM27151RS-X.X	
LM27152RS	

X.X = Output Voltage = 1.5, 1.8, 2.5, 3.0, 3.3, 5.0, 12

Absolute Maximum Ratings

CHARACTERISTIC	SYMBOL	MIN.	MAX.	UNIT
Input Supply Voltage	V_{IN}	- 20	+ 30	V
Lead Temperature(Soldering, 5 sec)	T_{SOL}	-	260	°C
Storage Temperature Range	T_{STG}	- 65	+ 150	°C

1.5A Very L.D.O Voltage Regulator

LM27150/27151/27152

Recommended Operating Ratings

CHARACTERISTIC	SYMBOL	MIN.	MAX.	UNIT
Operating Input Voltage	V_{IN}	-	+ 26	V
Junction Temperature	T_J	- 40	+ 125	°C

Ordering Information


V_{OUT}	Package	Order No.	Description	Supplied As	Status
1.5 V	TO-220 3L	LM27150T-1.5	1.5A, Fixed	Tube	Contact us
	TO-220 5L	LM27151T-1.5	1.5A, Fixed, Enable	Tube	Contact us
	TO-263 3L	LM27150R-1.5	1.5A, Fixed	Reel	Contact us
	TO-263 5L	LM27151R-1.5	1.5A, Fixed, Enable	Reel	Contact us
	TO-252 3L	LM27150RS-1.5	1.5A, Fixed	Reel	Contact us
	TO-252 5L	LM27151RS-1.5	1.5A, Fixed, Enable	Reel	Contact us
1.8 V	TO-220 3L	LM27150T-1.8	1.5A, Fixed	Tube	Contact us
	TO-220 5L	LM27151T-1.8	1.5A, Fixed, Enable	Tube	Contact us
	TO-263 3L	LM27150R-1.8	1.5A, Fixed	Reel	Contact us
	TO-263 5L	LM27151R-1.8	1.5A, Fixed, Enable	Reel	Contact us
	TO-252 3L	LM27150RS-1.8	1.5A, Fixed	Reel	Contact us
	TO-252 5L	LM27151RS-1.8	1.5A, Fixed, Enable	Reel	Contact us
2.5 V	TO-220 3L	LM27150T-2.5	1.5A, Fixed	Tube	Contact us
	TO-220 5L	LM27151T-2.5	1.5A, Fixed, Enable	Tube	Contact us
	TO-263 3L	LM27150R-2.5	1.5A, Fixed	Reel	Contact us
	TO-263 5L	LM27151R-2.5	1.5A, Fixed, Enable	Reel	Contact us
	TO-252 3L	LM27150RS-2.5	1.5A, Fixed	Reel	Contact us
	TO-252 5L	LM27151RS-2.5	1.5A, Fixed, Enable	Reel	Contact us
3.0 V	TO-220 3L	LM27150T-3.0	1.5A, Fixed	Tube	Contact us
	TO-220 5L	LM27151T-3.0	1.5A, Fixed, Enable	Tube	Contact us
	TO-263 3L	LM27150R-3.0	1.5A, Fixed	Reel	Contact us
	TO-263 5L	LM27151R-3.0	1.5A, Fixed, Enable	Reel	Contact us
	TO-252 3L	LM27150RS-3.0	1.5A, Fixed	Reel	Contact us
	TO-252 5L	LM27151RS-3.0	1.5A, Fixed, Enable	Reel	Contact us
3.3 V	TO-220 3L	LM27150T-3.3	1.5A, Fixed	Tube	Contact us
	TO-220 5L	LM27151T-3.3	1.5A, Fixed, Enable	Tube	Contact us
	TO-263 3L	LM27150R-3.3	1.5A, Fixed	Reel	Contact us
	TO-263 5L	LM27151R-3.3	1.5A, Fixed, Enable	Reel	Contact us
	TO-252 3L	LM27150RS-3.3	1.5A, Fixed	Reel	Contact us
	TO-252 5L	LM27151RS-3.3	1.5A, Fixed, Enable	Reel	Contact us

1.5A Very L.D.O Voltage Regulator


LM27150/27151/27152

Ordering Information


V _{OUT}	Package	Order No.	Description	Supplied As	Status
5.0 V	TO-220 3L	LM27150T-5.0	1.5A, Fixed	Tube	Contact us
	TO-220 5L	LM27151T-5.0	1.5A, Fixed, Enable	Tube	Contact us
	TO-263 3L	LM27150R-5.0	1.5A, Fixed	Reel	Contact us
	TO-263 5L	LM27151R-5.0	1.5A, Fixed, Enable	Reel	Contact us
	TO-252 3L	LM27150RS-5.0	1.5A, Fixed	Reel	Contact us
	TO-252 5L	LM27151RS-5.0	1.5A, Fixed, Enable	Reel	Contact us
12 V	TO-220 3L	LM27150T-12	1.5A, Fixed	Tube	Contact us
	TO-220 5L	LM27151T-12	1.5A, Fixed, Enable	Tube	Contact us
	TO-263 3L	LM27150R-12	1.5A, Fixed	Reel	Contact us
	TO-263 5L	LM27151R-12	1.5A, Fixed, Enable	Reel	Contact us
	TO-252 3L	LM27150RS-12	1.5A, Fixed	Reel	Contact us
	TO-252 5L	LM27151RS-12	1.5A, Fixed, Enable	Reel	Contact us
ADJ	TO-220 5L	LM27152T	1.5A, Adjustable, Enable	Tube	Contact us
	TO-263 5L	LM27152R	1.5A, Adjustable, Enable	Reel	Contact us
	TO-252 5L	LM27152RS	1.5A, Adjustable, Enable	Reel	Contact us




PIN CONFIGURATION




TO-263 3L




TO-263 5L




TO-252 3L



TO-252 5L



TO-220 3L




TO-220 5L

PIN DESCRIPTION


Pin No.	TO-220 / TO-263 / TO-252 3L (for LM27150)		TO-220 / TO-263 / TO-252 5L (for LM27151/2)	
	Name	Function	Name	Function
1	V _{IN}	Input Supply	EN	Chip Enable
2	GND	Ground	V _{IN}	Input Supply
3	V _{OUT}	Output Voltage	GND	Ground
4	-	-	V _{OUT}	Output Voltage
5	-	-	FLG / ADJ	Error Flag Output or Output Adjust

TYPICAL APPLICATION

- Typical Fixed Output Application



- Typical Adjustable Output Application



$$V_{OUT} = V_{REF} \times [1 + (R1/R2)] *$$

* For best results, the total series resistance should be small enough to pass the minimum regulator load current.

1.5A Very L.D.O Voltage Regulator

LM27150/27151/27152

ELECTRICAL CHARACTERISTICS

$I_{OUT} = 100\text{mA}$, $T_J = 25^\circ\text{C}$, unless otherwise specified. **Bold** values are guaranteed across the operating temperature range. Adjustable versions are programmed to 5.0V.

Symbol	Parameter	Condition	Min	Typ	Max	Units
V_{OUT}	Output Voltage	$I_O = 10\text{mA}$	-1		1	%
		$10\text{mA} \leq I_O \leq I_{FL}$, $(V_{OUT} + 1\text{V}) \leq V_{IN} \leq 26\text{V}$	-2		2	
ΔV_{LINE}	Line Regulation	$I_O = 10\text{mA}$, $(V_{OUT} + 1\text{V}) \leq V_{IN} \leq 26\text{V}$		0.06	0.5	%
ΔV_{LOAD}	Load Regulation	$V_{IN} = V_{OUT} + 5\text{V}$, $10\text{mA} \leq I_{OUT} \leq I_{FULLLOAD}$ (Note 1)		0.2	1	%
$\Delta V_O / \Delta T$	Output Voltage Temp. Coefficient	Output Voltage (Note 2), Temp. Coefficient		20	100	ppm/ $^\circ\text{C}$
V_{DO}	Dropout Voltage	$\Delta V_{OUT} = -1\%$, (Note 1.3)				mV
		$I_O = 100\text{mA}$		100	200	
		$I_O = 750\text{mA}$ $I_O = 1.5\text{A}$		250 350	600	
I_{GND}	Ground Current	$I_O = 750\text{mA}$, $V_{IN} = V_{OUT} + 1\text{V}$ (Note 1.4) $I_O = 1.5\text{A}$		8 22	20	mA
I_{GNDDO}	Ground Pin Current at Dropout	$V_{IN} = 0.5\text{V}$ less than specified V_{OUT} , $I_{OUT} = 10\text{mA}$ (Note 5)		2		mA
I_{LIMIT}	Current Limit	LM27150, $V_{OUT} = 0\text{V}$ (Note 1)		2.1	3.5	A
e_n	Output Noise Voltage (10Hz to 100kHz)	$C_L = 10\mu\text{F}$ $C_L = 33\mu\text{F}$ $I_L = 100\text{mA}$		400		μVRMS
				260		

Flag Output (Error Comparator) LM27151

$I_{FLG(LEAK)}$	Output Leakage Current	$V_{OH} = 26\text{V}$		0.01	1.00 2.00	μA
$V_{FLG(DO)}$	Output Low Voltage	Device set for 5V. $V_{IN} = 4.5\text{V}$ $I_{OL} = 250\mu\text{A}$ (Note 5)		220	300 400	mV
V_{FLG}	Upper Threshold Voltage	Device set for 5V (Note 5)	40 25	60		mV
	Lower Threshold Voltage	Device set for 5V (Note 5)		75	95 140	mV
	Hysteresis	Device set for 5V (Note 5)		15		mV

1.5A Very L.D.O Voltage Regulator

LM27150/27151/27152

Reference LM27152

V _{REF}	Reference Voltage		1.228 1.215	1.24	1.252 1.265	V
		(Note 6)	1.203		1.277	V
I _{ADJ}	Adjust Pin Bias Current			40	80 120	nA
	Reference Voltage Temp. Coefficient	(Note 2)		20		ppm/°C
	Adjust Pin Bias Current Temp. Coefficient			0.1		nA/°C

Enable Input LM27151 / LM27152

V _{EN}	Enable Input Voltage	Logic Low (Off) Logic High (On)	2.4		0.8	V
I _{EN}	Enable Pin Input Current	V _{EN} =26V		100	600 750	μA
		V _{EN} =0.8V			2.5 5	μA
	Regulator Output Current Shutdown	(Note 7)		10	500	μA

Note 1. Employ pulse-testing procedures to minimize temperature rise

Note 2. Output Voltage temperature coefficient is defined as the worst case voltage change divided by the total temperature range.

Note 3. Dropout Voltage is defined as the input-to-output differential when the Output Voltage drops to 99% of its nominal value with V+1V applied to V_{OUTIN}. For Output Voltages below 2.3V the Dropout Voltage is the input-to-output voltage differential with the minimum input voltage being 2.3V. The minimum input operation voltage is 2.3V.

Note 4. GND pin current is the regulator quiescent current. The total current drawn from the source is a sum of the load current plus the GND pin current.

Note 5. For specified V_{OUT} ≥2.5V.

Note 6. V ≤ V_{REFOUT} ≤ (V_{IN}-1V), 2.3V ≤ V_{IN} ≤ 26V, 10mA ≤ I ≤ 1.5A, T_{LJ} < T_J MAX.


Note 7. V_{EN} ≤ 0.8V and V_{IN} ≤ 26V, V=0

Note 8. When used in dual supply systems, where the regulator load is returned to a negative supply, the output voltage must be diode-clamped to ground.


1.5A Very L.D.O Voltage Regulator

LM27150/27151/27152


TYPICAL OPERATING CHARACTERISTICS




LM27150 Dropout Voltage vs. Output Current




LM27150 Dropout Voltage vs. Temperature




LM27150-5.0 Dropout Characteristics




LM27150 Ground Current vs. Supply Voltage




LM27150 Ground Current vs. Temperature




LM27150 Ground Current vs. Temperature



LM27150-3.3 Output Voltage vs. Temperature



LM27150-3.3 Short Circuit Current vs. Temperature



LM27150 Ground Current vs. Input Voltage

APPLICATION INFORMATION

The LM27150 are high performance low-dropout voltage regulators suitable for all moderate to high current voltage regulator applications. Their 350mV dropout voltage at full load makes them especially valuable in battery powered systems and as high efficiency noise filters in "post-regulator" applications. Unlike older NPN-pass transistor designs, dropout performance of the PNP output of these devices is limited merely by the low V_{CE} saturation voltage.

The LM27150 family of regulators is fully protected from damage due to fault conditions. Current Limiting is provided. This limiting is linear; output current under overload conditions is constant. Thermal shutdown disables the device when the die temperature exceeds the 125°C maximum safe operating temperature. Transient protection allows device survival even when the input voltage spikes between -20V and +30V. When the input voltage exceeds about 28V, the over voltage sensor temporarily disables the regulator.




Figure 1. Linear regulators require only two capacitors for operation.

Thermal Design

Linear regulators are simple to use. The most complicated design parameters to consider are thermal characteristics. Thermal design requires the following application-specific parameters:

- Maximum ambient temperature, T_A
- Output Current, I_{OUT}
- Output Voltage, V_{OUT}
- Input Voltage, V_{IN}

First, we calculate the power dissipation of the regulator from these numbers and the device parameters from this datasheet.

$$P_D = I_{OUT}(1.01V_{IN} - V_{OUT})$$

Where the ground current is approximated by 1% of I_{OUT} . Then the heat sink thermal resistance is determined with this formula:

$$\theta_{SA} = \frac{T_{JMAX} - T_A}{P_D} - (\theta_{JC} + \theta_{CS})$$

Where $T_{JMAX} \leq 125^\circ\text{C}$ and θ_{CS} is between 0 and 2°C/W.

Capacitor Requirements

For stability and minimum output noise, a capacitor on the regulator output is necessary. The value of this capacitor is dependent upon the output current; lower currents allow smaller capacitors. LM27150 regulators are stable with the 10uF minimum capacitor values at full load. Where the regulator is powered from a source with a high AC impedance, a 0.1uF capacitor connected between input and GND is recommended. This capacitor should have good characteristics to above 250kHz.

Minimum Load Current

The LM27150 regulators are specified between finite loads. If the output is too small, leakage currents is too small, leakage currents dominate and the output voltage rises. The 5mA minimum load current swamps any expected leakage current across the operating temperature range.


Adjustable Regulator Design

The adjustable regulator versions, LM27152 allows programming the output voltage anywhere between 1.25V and the 25V maximum operating rating of the family.

Two resistors are used. Resistors can be quite large, up to 1MΩ, because of the very high input impedance and low bias current of the sense comparator: The resistor values are calculated by:

$$R1=R2\left(\frac{V_{OUT}}{V_{REF}} - 1\right)$$

Where V_{OUT} is desired output voltage, Figure 2 shows component definition. Applications with widely varying load currents may scale the resistors to draw the minimum load current required for proper operation.



$$V_{OUT} = 1.240 \times [1 + (R1/R2)]$$

Figure 2. Adjustable Regulator with Resistors

Error Flag

LM27151 versions feature and Error Flag, which looks at the output voltage and signals an error condition when this voltage drops 5% below its expected value. The error flag is an open-collector output that pulls low under fault conditions. It may sink 10mA. Low output voltage signifies a number of possible problems, including an over-current fault (the device is in current limit) and low input voltage. The flag output is inoperative during over temperature shutdown conditions.

Enable input

LM27151 and LM27152 versions feature an enable (EN) input that allows ON/OFF control of the device. Special design allows "zero" current drain when the device is disabled—only microamperes of leakage current flows. The EN input has TTL/CMOS compatible thresholds for simple interfacing with logic, or may be directly tied to $\leq 30V$. Enabling the regulator requires approximately 20 μA of current.