

LM2902

LINEAR INTEGRATED CIRCUIT

QUADRUPLE OPERATIONAL AMPLIFIERS

■ DESCRIPTION

UTC LM2902 consist of four independent, high-gain, frequency-compensated operational amplifiers which are designed to operate from a single power supply over a wide range of voltage. Operation from split supplies is also possible so long as the difference between the two supplies is 3V ~ 30V. The low supply current drain is independent of the magnitude of the supply voltage.


The device can easily be implemented in single supply voltage system, including transducer amplifiers, DC gain blocks, and all of conventional OP Amp circuits.

■ FEATURES



- * Wide Supply Voltage Range. (Single Supply: 3~30V)
- * Low Supply Current Drain Independent of Supply Voltage: 0.8 mA Typ
- * Large DC voltage gain: 100dB
- * Input Common-Mode Voltage Range Includes Ground.
- * Low Input Bias and Offset Parameters
- * Differential Input Voltage Range Equal to Maximum Rated Supply Voltage: 32V
- * Open-Loop Differential Voltage Amplification: 100 V/mV Typ.
- * Internal Frequency Compensation for Unity Gain

■ ORDERING INFORMATION


Ordering Number		Package	Packing
Lead Free	Halogen-Free		
LM2902L-D14-T	LM2902G-D14-T	DIP-14	Tube
LM2902L-S14-R	LM2902G-S14-R	SOP-14	Tape Reel
LM2902L-P14-R	LM2902G-P14-R	TSSOP-14	Tape Reel

LM2902G-D14-T 	(1)Packing Type (2)Package Type (3)Green Package	(1) T: Tube, R: Tape Reel (2) DIP: DIP-14, S14: SOP-14, P14: TSSOP-14 (3) G: Halogen Free and Lead Free, L: Lead Free
--	--	---

■ MARKING

DIP-14	SOP-14 / TSSOP-14
 <div style="margin-top: 10px;"> Date Code L: Lead Free G: Halogen Free Lot Code </div>	 <div style="margin-top: 10px;"> Date Code L: Lead Free G: Halogen Free Lot Code </div>

■ PIN CONFIGURATION



■ ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage (Note 1)	V _{CC}	32	V
Differential Input voltage (Note 2)	V _{I(DIFF)}	± 32	V
Input Voltage	V _{IN}	-0.3 ~ +32	V
Output Short Circuit (one amplifier) to Ground (T _A ≤ 25°C, V _{CC} ≤ 15V) (Note 3)		Continuous	
Operation Temperature	T _{OPR}	-40 ~ +125	°C
Storage Temperature	T _{STG}	-65 ~ +150	°C

Notes: 1. All voltage values (except differential voltages and V_{CC} specified for the measurement of I_{IN(OS)}) are with respect to the network GND.

2. Differential voltages are at IN+ with respect to IN-.

3. Short circuits from outputs to V_{CC} can cause excessive heating and eventual destruction.

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	SOP-14	86	°C/W
	DIP-14	80	°C/W
	TSSOP-14	113	°C/W

■ ELECTRICAL CHARACTERISTICS (V_{CC}=5V, unless otherwise specified, V_{CC}=30V for testing only.)


PARAMETER	SYMBOL	TEST CONDITIONS*	MIN	TYP	MAX	UNIT
Input Offset Voltage	V _{I(OFF)}	V _{CC} =5V to 30V, V _{IC} =V _{ICR(min)} , V _{OUT} =1.4V	T _A =25°C		3	mV
			T _A =-40~+125°C		7	mV
Input Offset Current	I _{I(OFF)}	V _{OUT} =1.4V	T _A =25°C	2	30	nA
			T _A =-40~+125°C		100	nA
Input Bias Current	I _{I(BIAS)}	V _{OUT} =1.4V	T _A =25°C	-20	-150	nA
			T _A =-40~+125°C		-300	nA
Input Common-mode Voltage Range	V _{I(CM)}	V _{CC} =5V to 30V	T _A =25°C	0	V _{CC} -1.5	V
			T _A =-40~+125°C	0	V _{CC} -2	V
Output Voltage Level	V _{OH}	R _L =2kΩ	T _A =25°C	V _{CC} -1.5		V
		V _{CC} =30V, R _L =2kΩ	T _A =-40~+125°C	26		V
		V _{CC} =30V, R _L ≥10kΩ		27	28	V
Low	V _{OL}	R _L ≤ 10kΩ	T _A =-40~+125°C	5	20	mV
Large Signal Current Gain	G _V	V _{CC} =15V, V _{OUT} =1V ~ 11V R _L ≥2kΩ	T _A =25°C	50	100	V/mV
			T _A =-40~+125°C	25		V/mV
Common-mode Rejection Ratio	CMRR	V _{IC} =V _{ICR(min)}	T _A =25°C	70	80	dB
Supply Voltage Rejection Ratio ($\Delta V_{CC}/\Delta V_{IO}$)	PSRR		T _A =25°C	65	100	dB
Crosstalk Attenuation	V _{O1} /V _{O2}	f = 1kHz ~ 20 kHz	T _A =25°C		120	dB
Output Current	I _{OUT}	V _{CC} =15V, V _{ID} =1V, V _{OUT} =0	T _A =25°C	-20	-30	mA
			T _A =-40~+125°C	-10		mA
		V _{CC} =15V, V _{ID} =-1V, V _{OUT} =15V	T _A =25°C	10	20	mA
			T _A =-40~+125°C	5		mA
		V _{ID} =-1V, V _{OUT} =200mV	T _A =25°C	12	30	μA
Short-circuit Output Current	I _{OS}	V _{CC} =5V, V _{OUT} =0, GND at -5V	T _A =25°C		± 40	mA
Supply Current (four amplifiers)	I _{CC}	V _{OUT} =2.5V, R _L =∞	T _A =-40~+125°C		0.7	mA
		V _{CC} =30V, V _{OUT} =0.5V _{CC} , R _L =∞			1.4	3

Note: All characteristics are measured under open-loop conditions with zero common-mode input voltage.







LM2902

LINEAR INTEGRATED CIRCUIT





■ SCHEMATIC DIAGRAM (One Section Only)



■ TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.