


3-TERMINAL POSITIVE VOLTAGE REGULATOR

LM7806

TO-220

Plastic Package



The Voltages Available allow these Regulators to be used in Logic Systems, Instrumentation, Hi-Fi Audio Circuits and other Solid State Electronic Equipment

ABSOLUTE MAXIMUM RATINGS ($T_a=25^\circ\text{C}$)

DESCRIPTION	SYMBOL	VALUE	UNIT
Input Voltage	V_{IN}	35	V
		40	
Power Dissipation	P_D	15	W
Operating Temperature	T_{amb}	- 20 to +80	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	- 55 to +150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS ($T_a=25^\circ\text{C}$ unless specified otherwise)

$V_{IN}=15\text{V}$, $I_O=100\text{mA}$, $T_a=25^\circ\text{C}$

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Output Voltage	V_O	$I_O=5\text{mA} \sim 1.5\text{A}$	5.76		6.24	V
		$V_{IN}=8.5 \sim 21\text{V}$, $P_D 15\text{W}$				
Line Regulation	R_{EGV}	$V_{IN}=8.5 \sim 25\text{V}$			60	mV
Load Regulation	R_{EGL}	$I_O=5\text{mA} \sim 1\text{A}$			60	mV
Quiescent Current	I_Q				8.0	mA
Quiescent Current Change	I_Q	$V_{IN}=8.5 \sim 25\text{V}$			1.0	mA
		$I_O=5\text{mA} \sim 1\text{A}$			0.5	mA
Input Voltage	V_{IN}		8.5		25	V
Ripple Rejection Ratio	R_R	$V_{IN}=9.0 \sim 19\text{V}$, $f=120\text{Hz}$	58			dB
Max Output Current	I_{OM}	$T_J=25^\circ\text{C}$		2.2		A
Output Voltage Drift	V/T	$I_O=5\text{mA}$, $T_J=0 \sim 125^\circ\text{C}$		- 0.3		mV/ $^\circ\text{C}$
Output Noise Voltage	V_{NO}	$f=10\text{Hz} \sim 100\text{KHz}$		10		μV
Short Circuit Current Limit	I_{SC}	$T_J=25^\circ\text{C}$		2.0		A

LM7806Rev041004E

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of
Continental Device India Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.
Telephone + 91-11-2579 6150, 5141 1112 Fax + 91-11-2579 5290, 5141 1119
email@cdil.com www.cdilsemi.com