


**Low Current Positive Voltage Regulator**

# LM78LXXN3



**Description**


The LM78LXXN3 series of positive regulators are available in the SOT-23 package and with 5V, 6V, 8V, 9V, 10V, 12V, 15V, 18V and 24V fixed output voltages, making it useful in a wide range of applications. These regulators can provide local on-card regulation, eliminating the distribution problems associated with single point regulation. Each type employs internal current limiting, thermal shut-down and safe operating area protection, making it essentially indestructible. If adequate heat sinking is provided, they can deliver over 100mA output current. Although designed primarily as fixed voltage regulators, these devices can be used with external components to obtain adjustable voltages and currents. LM78LXXN3 is characterized for operation from 0°C to 125°C.

**Features:**

- Internal Short-Circuit Current Limiting
- Internal Thermal Overload Protection
- No External Components Required
- Pb-free lead plating and halogen-free package

**Ordering Information**

Device	Output Voltage Tolerance	Package	Shipping
LM78LXXN3-A-T1-G	±3%	SOT-23	3000 pcs / Tape & Reel
LM78LXXN3-B-T1-G	±5%	(Pb-free lead plating and halogen-free package)	





**Absolute Maximum Ratings**

Parameter	Ratings	Unit
Input Voltage	LM78L05 ~ 10	30
	LM78L12 ~18	35
	LM78L24	40
Output Current	200	mA
Operating Junction Temperature Range	-40 ~ +125	°C
Storage Temperature Range	-65 ~ +150	°C
Power Dissipation	240 (Note)	mW

Note : When tested in free air condition, without heat sinking.

**Electrical Characteristics**

**LM78L05** ( $V_{in}=10V$ ,  $I_o=80mA$ ,  $T_j=25^{\circ}C$ ,  $C_{in}=0.33\mu F$ ,  $C_{out}=0.1\mu F$ , unless otherwise noted) (Note 1)

Symbol	Parameter	Min	Typ	Max	Conditions	Units
Vo	Output Voltage	4.85	5	5.15	$V_{in}=10V$ , $I_o=80mA$ , $T_j=25^{\circ}C$ $7V \leq V_{in} \leq 20V$ , $1mA \leq I_o \leq 80mA$	V
		4.75	-	5.25	$V_{in}=10V$ , $1mA \leq I_o \leq 140mA$ (Note 2)	
$\Delta V_o$	Line Regulation	-	32	150	$7V \leq V_{in} \leq 20V$	mV
		-	26	100	$8V \leq V_{in} \leq 20V$	
$\Delta V_o$	Load Regulation	-	15	60	$1mA \leq I_o \leq 200mA$	mV
		-	8	30	$1mA \leq I_o \leq 80mA$	
IQ	Quiescent Current	-	2.6	6	$T_j=25^{\circ}C$ , $V_{in}=10V$ , $I_o=80mA$	mA
$\Delta IQ$	Quiescent Current Change	-	-	1.5	$8V \leq V_{in} \leq 20V$	mA
		-	-	0.1	$1mA \leq I_o \leq 80mA$	
Vn	Output Noise Voltage	-	42	-	$10Hz \leq f \leq 100KHz$	$\mu V$
$\Delta V_{in} / \Delta V_{out}$	Ripple Rejection	41	49	-	$8V \leq V_{in} \leq 18V$ , $f=120Hz$	dB
$\Delta V_o / \Delta T_j$	Temperature Stability	-	-0.65	-	$I_o=5mA$ , $0^{\circ}C \leq T_j \leq 125^{\circ}C$	mV/°C
VD	Dropout Voltage	-	1.7	-	$I_o=80mA$	V

**LM78L06** ( $V_{in}=12V$ ,  $I_o=80mA$ ,  $T_j=25^{\circ}C$ ,  $C_{in}=0.33\mu F$ ,  $C_{out}=0.1\mu F$ , unless otherwise noted) (Note 1)

Symbol	Parameter	Min	Typ	Max	Conditions	Units
Vo	Output Voltage	5.82	6	6.18	$V_{in}=12V$ , $I_o=80mA$ , $T_j=25^{\circ}C$ $8V \leq V_{in} \leq 20V$ , $1mA \leq I_o \leq 80mA$	V
		5.70	-	6.30	$V_{in}=11V$ , $1mA \leq I_o \leq 140mA$ (Note 2)	
$\Delta V_o$	Line Regulation	-	35	175	$8V \leq V_{in} \leq 20V$	mV
		-	29	125	$9V \leq V_{in} \leq 20V$	
$\Delta V_o$	Load Regulation	-	16	80	$1mA \leq I_o \leq 200mA$	mV
		-	9	40	$1mA \leq I_o \leq 80mA$	
IQ	Quiescent Current	-	2.7	6	$T_j=25^{\circ}C$ , $V_{in}=12V$ , $I_o=80mA$	mA
$\Delta IQ$	Quiescent Current Change	-	-	1.5	$9V \leq V_{in} \leq 20V$	mA
		-	-	0.1	$1mA \leq I_o \leq 80mA$	
Vn	Output Noise Voltage	-	46	-	$10Hz \leq f \leq 100KHz$	$\mu V$
$\Delta V_{in} / \Delta V_{out}$	Ripple Rejection	40	48	-	$9V \leq V_{in} \leq 19V$ , $f=120Hz$	dB
$\Delta V_o / \Delta T_j$	Temperature Stability	-	0.75	-	$I_o=5mA$ , $0^{\circ}C \leq T_j \leq 125^{\circ}C$	mV/°C
VD	Dropout Voltage	-	1.7	-	$I_o=80mA$	V



**LM78L08** ( $V_{in}=14V$ ,  $I_o=80mA$ ,  $T_j=25^{\circ}C$ ,  $C_{in}=0.33\mu F$ ,  $C_{out}=0.1\mu F$ , unless otherwise noted) (Note 1)

Symbol	Parameter	Min	Typ	Max	Conditions	Units
Vo	Output Voltage	7.76	8	8.24	$V_{in}=14V$ , $I_o=80mA$ , $T_j=25^{\circ}C$ $10.5V \leq V_{in} \leq 23V$ , $1mA \leq I_o \leq 80mA$	V
		7.60	-	8.40	$V_{in}=14V$ , $1mA \leq I_o \leq 140mA$ (Note 2)	
$\Delta V_o$	Line Regulation	-	42	175	$10.5V \leq V_{in} \leq 23V$	mV
		-	36	125	$11V \leq V_{in} \leq 23V$	
$\Delta V_o$	Load Regulation	-	18	80	$1mA \leq I_o \leq 200mA$	mV
		-	10	40	$1mA \leq I_o \leq 80mA$	
IQ	Quiescent Current	-	2.8	6	$T_j=25^{\circ}C$ , $V_{in}=14V$ , $I_o=80mA$	mA
$\Delta IQ$	Quiescent Current Change	-	-	1.5	$11V \leq V_{in} \leq 23V$	mA
		-	-	0.1	$1mA \leq I_o \leq 80mA$	
Vn	Output Noise Voltage	-	54	-	$10Hz \leq f \leq 100KHz$	$\mu V$
$\Delta V_{in} / \Delta V_{out}$	Ripple Rejection	37	46	-	$11V \leq V_{in} \leq 21V$ , $f=120Hz$	dB
$\Delta V_o / \Delta T_j$	Temperature Stability	-	0.75	-	$I_o=5mA$ , $0^{\circ}C \leq T_j \leq 125^{\circ}C$	mV/ $^{\circ}C$
VD	Dropout Voltage	-	1.7	-	$I_o=80mA$	V

**LM78L09** ( $V_{in}=16V$ ,  $I_o=80mA$ ,  $T_j=25^{\circ}C$ ,  $C_{in}=0.33\mu F$ ,  $C_{out}=0.1\mu F$ , unless otherwise noted) (Note 1)

Symbol	Parameter	Min	Typ	Max	Conditions	Units
Vo	Output Voltage	8.73	9	9.27	$V_{in}=16V$ , $I_o=80mA$ , $T_j=25^{\circ}C$ $12V \leq V_{in} \leq 24V$ , $1mA \leq I_o \leq 80mA$	V
		8.55	-	9.45	$V_{in}=12V$ , $1mA \leq I_o \leq 140mA$ (Note 2)	
$\Delta V_o$	Line Regulation	-	45	175	$12V \leq V_{in} \leq 24V$	mV
		-	40	125	$13V \leq V_{in} \leq 24V$	
$\Delta V_o$	Load Regulation	-	19	90	$1mA \leq I_o \leq 200mA$	mV
		-	11	40	$1mA \leq I_o \leq 80mA$	
IQ	Quiescent Current	-	2.9	6	$T_j=25^{\circ}C$ , $V_{in}=16V$ , $I_o=80mA$	mA
$\Delta IQ$	Quiescent Current Change	-	-	1.5	$13V \leq V_{in} \leq 24V$	mA
		-	-	0.1	$1mA \leq I_o \leq 80mA$	
Vn	Output Noise Voltage	-	58	-	$10Hz \leq f \leq 100KHz$	$\mu V$
$\Delta V_{in} / \Delta V_{out}$	Ripple Rejection	38	45	-	$15V \leq V_{in} \leq 25V$ , $f=120Hz$	dB
$\Delta V_o / \Delta T_j$	Temperature Stability	-	0.75	-	$I_o=5mA$ , $0^{\circ}C \leq T_j \leq 125^{\circ}C$	mV/ $^{\circ}C$
VD	Dropout Voltage	-	1.7	-	$I_o=80mA$	V



**LM78L10** ( $V_{in}=17V, I_o=80mA, T_j=25^{\circ}C, C_{in}=0.33\mu F, C_{out}=0.1\mu F$ , unless otherwise noted) (Note 1)

Symbol	Parameter	Min	Typ	Max	Conditions	Units
Vo	Output Voltage	9.70	10	10.30	$V_{in}=17V, I_o=80mA, T_j=25^{\circ}C$ $13V \leq V_{in} \leq 25V, 1mA \leq I_o \leq 80mA$	V
		9.50	-	10.50	$V_{in}=17V, 1mA \leq I_o \leq 140mA$ (Note 2)	
$\Delta V_o$	Line Regulation	-	51	175	$13V \leq V_{in} \leq 25V$	mV
		-	42	125	$14V \leq V_{in} \leq 25V$	
$\Delta V_o$	Load Regulation	-	20	90	$1mA \leq I_o \leq 200mA$	mV
		-	11	40	$1mA \leq I_o \leq 80mA$	
IQ	Quiescent Current	-	3	6	$T_j=25^{\circ}C, V_{in}=17V, I_o=80mA$	mA
$\Delta IQ$	Quiescent Current Change	-	-	1.5	$14V \leq V_{in} \leq 25V$	mA
		-	-	0.1	$1mA \leq I_o \leq 80mA$	
Vn	Output Noise Voltage	-	62	-	$10Hz \leq f \leq 100KHz$	$\mu V$
$\Delta V_{in} / \Delta V_{out}$	Ripple Rejection	37	44	-	$15V \leq V_{in} \leq 25V, f=120Hz$	dB
$\Delta V_o / \Delta T_j$	Temperature Stability	-	0.75	-	$I_o=5mA, 0^{\circ}C \leq T_j \leq 125^{\circ}C$	$mV/^{\circ}C$
VD	Dropout Voltage	-	1.7	-	$I_o=80mA$	V

**LM78L12** ( $V_{in}=19V, I_o=80mA, T_j=25^{\circ}C, C_{in}=0.33\mu F, C_{out}=0.1\mu F$ , unless otherwise noted) (Note 1)

Symbol	Parameter	Min	Typ	Max	Conditions	Units
Vo	Output Voltage	11.64	12	12.36	$V_{in}=19V, I_o=80mA, T_j=25^{\circ}C$ $14V \leq V_{in} \leq 27V, 1mA \leq I_o \leq 80mA$	V
		11.40	-	12.60	$V_{in}=19V, 1mA \leq I_o \leq 140mA$ (Note 2)	
$\Delta V_o$	Line Regulation	-	55	250	$14V \leq V_{in} \leq 27V$	mV
		-	49	200	$16V \leq V_{in} \leq 27V$	
$\Delta V_o$	Load Regulation	-	22	100	$1mA \leq I_o \leq 200mA$	mV
		-	13	50	$1mA \leq I_o \leq 80mA$	
IQ	Quiescent Current	-	3.1	6.5	$T_j=25^{\circ}C, V_{in}=19V, I_o=80mA$	mA
$\Delta IQ$	Quiescent Current Change	-	-	1.5	$16V \leq V_{in} \leq 27V$	mA
		-	-	0.1	$1mA \leq I_o \leq 80mA$	
Vn	Output Noise Voltage	-	70	-	$10Hz \leq f \leq 100KHz$	$\mu V$
$\Delta V_{in} / \Delta V_{out}$	Ripple Rejection	37	42	-	$15V \leq V_{in} \leq 25V, f=120Hz$	dB
$\Delta V_o / \Delta T_j$	Temperature Stability	-	-1.0	-	$I_o=5mA, 0^{\circ}C \leq T_j \leq 125^{\circ}C$	$mV/^{\circ}C$
VD	Dropout Voltage	-	1.7	-	$I_o=80mA$	V



**LM78L15** ( $V_{in}=23V$ ,  $I_o=80mA$ ,  $T_j=25^{\circ}C$ ,  $C_{in}=0.33\mu F$ ,  $C_{out}=0.1\mu F$ , unless otherwise noted) (Note 1)

Symbol	Parameter	Min	Typ	Max	Conditions	Units
Vo	Output Voltage	14.55	15	15.45	$V_{in}=23V$ , $I_o=80mA$ , $T_j=25^{\circ}C$ $17.5V \leq V_{in} \leq 30V$ , $1mA \leq I_o \leq 80mA$	V
		14.25	-	15.75	$V_{in}=23V$ , $1mA \leq I_o \leq 140mA$ (Note 2)	
$\Delta V_o$	Line Regulation	-	25	150	$17.5V \leq V_{in} \leq 30V$	mV
		-	15	75	$19V \leq V_{in} \leq 30V$	
$\Delta V_o$	Load Regulation	-	20	150	$1mA \leq I_o \leq 200mA$	mV
		-	25	150	$1mA \leq I_o \leq 80mA$	
IQ	Quiescent Current	-	2.2	6.5	$T_j=25^{\circ}C$ , $V_{in}=23V$ , $I_o=80mA$	mA
$\Delta IQ$	Quiescent Current Change	-	-	1.5	$19V \leq V_{in} \leq 30V$	mA
		-	-	0.1	$1mA \leq I_o \leq 80mA$	
Vn	Output Noise Voltage	-	90	-	$10Hz \leq f \leq 100KHz$	$\mu V$
$\Delta V_{in} / \Delta V_{out}$	Ripple Rejection	34	63	-	$18.5V \leq V_{in} \leq 28.5V$ , $f=120Hz$	dB
$\Delta V_o / \Delta T_j$	Temperature Stability	-	-1.3	-	$I_o=5mA$ , $0^{\circ}C \leq T_j \leq 125^{\circ}C$	$mV/^{\circ}C$
VD	Dropout Voltage	-	1.7	-	$I_o=80mA$	V

**LM78L18** ( $V_{in}=26V$ ,  $I_o=80mA$ ,  $T_j=25^{\circ}C$ ,  $C_{in}=0.33\mu F$ ,  $C_{out}=0.1\mu F$ , unless otherwise noted) (Note 1)


Symbol	Parameter	Min	Typ	Max	Conditions	Units
Vo	Output Voltage	17.46	18	18.54	$V_{in}=26V$ , $I_o=80mA$ , $T_j=25^{\circ}C$ $21V \leq V_{in} \leq 33V$ , $1mA \leq I_o \leq 80mA$	V
		17.10	-	18.90	$V_{in}=26V$ , $1mA \leq I_o \leq 140mA$ (Note 2)	
$\Delta V_o$	Line Regulation	-	70	360	$20.5V \leq V_{in} \leq 33V$	mV
		-	64	300	$22V \leq V_{in} \leq 33V$	
$\Delta V_o$	Load Regulation	-	27	180	$1mA \leq I_o \leq 200mA$	mV
		-	19	90	$1mA \leq I_o \leq 80mA$	
IQ	Quiescent Current	-	3.5	6.5	$T_j=25^{\circ}C$ , $V_{in}=26V$ , $I_o=80mA$	mA
$\Delta IQ$	Quiescent Current Change	-	-	1.5	$21V \leq V_{in} \leq 33V$	mA
		-	-	0.1	$1mA \leq I_o \leq 80mA$	
Vn	Output Noise Voltage	-	89	-	$10Hz \leq f \leq 100KHz$	$\mu V$
$\Delta V_{in} / \Delta V_{out}$	Ripple Rejection	32	36	-	$21.5V \leq V_{in} \leq 31.5V$ , $f=120Hz$	dB
$\Delta V_o / \Delta T_j$	Temperature Stability	-	-1.8	-	$I_o=5mA$ , $0^{\circ}C \leq T_j \leq 125^{\circ}C$	$mV/^{\circ}C$
VD	Dropout Voltage	-	1.7	-	$I_o=80mA$	V

**LM78L24** ( $V_{in}=32V, I_o=80mA, T_j=25^{\circ}C, C_{in}=0.33\mu F, C_{out}=0.1\mu F$ , unless otherwise noted) (Note 1)

Symbol	Parameter	Min	Typ	Max	Conditions	Units
Vo	Output Voltage	23.28	24	24.72	$V_{in}=32V, I_o=80mA, T_j=25^{\circ}C$ $27V \leq V_{in} \leq 38V, 1mA \leq I_o \leq 80mA$	V
		22.80	24	25.20	$V_{in}=32V, 1mA \leq I_o \leq 140mA$ (Note 2)	
$\Delta V_o$	Line Regulation	-	95	480	$26.5V \leq V_{in} \leq 39V$	mV
		-	78	400	$29V \leq V_{in} \leq 39V$	
$\Delta V_o$	Load Regulation	-	41	240	$1mA \leq I_o \leq 200mA$	mV
		-	28	120	$1mA \leq I_o \leq 80mA$	
IQ	Quiescent Current	-	3.6	6.5	$T_j=25^{\circ}C, V_{in}=32V, I_o=80mA$	mA
$\Delta IQ$	Quiescent Current Change	-	-	1.5	$28V \leq V_{in} \leq 39V$	mA
		-	-	0.1	$1mA \leq I_o \leq 80mA$	
Vn	Output Noise Voltage	-	97	-	$10Hz \leq f \leq 100KHz$	$\mu V$
$\Delta V_{in} / \Delta V_{out}$	Ripple Rejection	30	33	-	$27.5V \leq V_{in} \leq 37.5V, f=120Hz$	dB
$\Delta V_o / \Delta T_j$	Temperature Stability	-	-2.0	-	$I_o=5mA, 0^{\circ}C \leq T_j \leq 125^{\circ}C$	$mV/^{\circ}C$
VD	Dropout Voltage	-	1.7	-	$I_o=80mA$	V


- Note : 1. The maximum steady state usable output current is dependent on input voltage, heat sinking, lead length of the package and copper of PCB. The data above represent pulse test conditions with junction temperatures specified at the initial of test.  
 2. Power dissipation < 0.24W

**Typical Application**




A common ground is required between the input and the output voltages. The input voltage must remain typically 2.0V above the output voltage even during the low point on the input ripple voltage.  
 Note : C1 and C2 are required if regulator is located far from power supply filter and load, or oscillation may induced on the loop.





**Schematic Diagram**



### Block Diagram





**Typical Characteristics**







**Typical Characteristics(Cont.)**



**SOT-23 Reel Dimension**




**SOT-23 Carrier Tape Dimension**



**Recommended wave soldering condition**

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds


**Recommended temperature profile for IR reflow**



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (T <sub>smax</sub> to T <sub>p</sub> )	3°C/second max.	3°C/second max.
Preheat		
-Temperature Min(T <sub>s min</sub> )	100°C	150°C
-Temperature Max(T <sub>s max</sub> )	150°C	200°C
-Time(t <sub>s min</sub> to t <sub>s max</sub> )	60-120 seconds	60-180 seconds
Time maintained above:		
-Temperature (T <sub>L</sub> )	183°C	217°C
- Time (t <sub>L</sub> )	60-150 seconds	60-150 seconds
Peak Temperature(T <sub>p</sub> )	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

**SOT-23 Dimension**



**Marking:**

Vout:	5V→05
	6V→06
	8V→08
	9V→09
	10V→10
	12V→12
	15V→15
	18V→18
	24V→24

3-Lead SOT-23 Plastic Surface Mounted Package  
 CYStek Package Code: N3

Style : Pin 1.GND 2.Vout 3.Vin

DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.1102	0.1204	2.80	3.04	J	0.0032	0.0079	0.08	0.20
B	0.0472	0.0551	1.20	1.40	K	0.0118	0.0266	0.30	0.67
C	0.0335	0.0512	0.89	1.30	L	0.0335	0.0453	0.85	1.15
D	0.0118	0.0197	0.30	0.50	S	0.0830	0.1004	2.10	2.55
G	0.0669	0.0910	1.70	2.30	V	0.0098	0.0256	0.25	0.65
H	0.0000	0.0040	0.00	0.10	L1	0.0118	0.0197	0.30	0.50

**Notes :** 1.Controlling dimension : millimeters.  
 2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.  
 3.If there is any question with packing specification or packing method, please contact your local CYStek sales office.

**Material :**

- Lead : Tin plated.
- Mold Compound : Epoxy resin family, flammability solid burning class:UL94V-0.

**Important Notice:**

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.