

## Ultra Low Power Low Dropout Middle Current Voltage Regulators

### ■ General Description

The LN6218 series are precise, low power consumption, high voltage; positive voltage regulators manufactured using CMOS and laser trimming technologies. The series provides large currents with a significantly small dropout voltage. The LN6218 consists of a current limiter circuit, a driver transistor, a precision reference voltage and an error correction circuit. The series is compatible with low ESR ceramic capacitors. The current limiter's feedback circuit also operates as a short protect for the output current limiter and the output pin. Output voltage can be set internally by laser trimming technologies. It is selectable in 100mV increments within a range of 1.2V to 5.0V. SOT-89-3, SOT-23-3L packages are available.

### ■ Package


- SOT-89-3
- SOT-23-3L

### ■ Ordering Information

#### LN6218P ①②③④⑤

Designator	Symbol	Description	Designator	Symbol	Description
① ②	Integer	Output Voltage: e.g. ①=3, ②=0 $\Rightarrow$ 3.0V	④	P	SOT-89-3
③			⑤	R	Embossed Tape: standard Feed
	2	Accuracy: within $\pm 2\%$		L	Embossed Tape: reverse Feed
④		Package			
	M	SOT-23-3			


### ■ Pin Configuration



Pin number		Pin Name	Function
SOT-23-3L	SOT-89-3L		
3	2	VIN	Power Supply
1	1	VSS	Ground
2	3	VOUT	Output Pin

## ■ Marking Rule

- SOT-89 -3 and SOT-23L



① Represents product series

Symbol	Product Series	
6	LN6218P◆◆◆◆◆	

② Represents the type of regulator


Voltage(V)	0.1~3.0	3.1~5.0
±2%	E	F

③ Represents the Output Voltage

Symbol	Output Voltage (V)		Symbol	Output Voltage (V)	
0	-	3.1	-	F	1.6 4.6 -
1	-	3.2	-	H	1.7 4.7 -
2	-	3.3	-	K	1.8 4.8 -
3	-	3.4	-	L	1.9 4.9 -
4	-	3.5	-	M	2 5.0 -
5	-	3.6	-	N	2.1 - -
6	-	3.7	-	P	2.2 - -
7	-	3.8	-	R	2.3 - -
8	-	3.9	-	S	2.4 - -
9	-	4	-	T	2.5 - -
A	-	4.1	-	U	2.6 - -
B	1.2	4.2	-	V	2.7 - -
C	1.3	4.3	-	X	2.8 - -
D	1.4	4.4	-	Y	2.9 - -
E	1.5	4.5	-	Z	3 - -

④ and “\*” Represents the assembly lot no.

## ■ Function Block Diagram




## ■ Absolute Maximum Ratings

Parameter	Symbol	Maximum Rating		Unit
Input Voltage	V <sub>IN</sub>	V <sub>SS</sub> -0.3~V <sub>SS</sub> +6		V
Output Current	V <sub>OUT</sub>	V <sub>SS</sub> -0.3~V <sub>IN</sub> +0.3		
Power Dissipation	P <sub>D</sub>	SOT-23-3L	250	mW
		SOT-89-3	500	
Operating Ambient Temperature	T <sub>opr</sub>	-40~+85		°C
Storage Temperature	T <sub>stg</sub>	-40~+125		
ESD(HBM)		4000		V

**Caution:** The absolute maximum ratings are rated values exceeding which the product could suffer physical damage. These values must therefore not be exceeded under any conditions.

## ■ Typical Application Circuit



## ■ Application Conditions

Input capacitor (CIN): 1.0 $\mu$ F or more

Output capacitor (CL): 0.1  $\mu$ F or more (tantalum capacitor)


**Caution A general series regulator may oscillate, depending on the external components selected. Check that no oscillation occurs with the application using the above capacitor.**

## ■ Electrical Characteristics


Item	Symbol	Condition	Min	Typ	Max	Unit
Output Voltage	$V_{OUT(E)1}$	$V_{IN} = V_{OUT(S)} + 1.0 \text{ V}$ , $I_{OUT} = 1 \text{ mA}$ , $\pm 2\%$	$V_{OUT(S)} \times 0.98$	$V_{OUT(S)}$	$V_{OUT(S)} \times 1.02$	V
Output Current	$I_{OUT}$	$V_{IN} \geq V_{OUT(S)} + 1.0 \text{ V}$	250 * <sup>5</sup>	—	—	mA
Dropout Voltage	$V_{drop}$	$I_{OUT} = 50 \text{ mA}$	$1.5 \text{ V} \leq V_{OUT(S)} \leq 2.5 \text{ V}$	—	0.20	0.28
			$2.6 \text{ V} \leq V_{OUT(S)} \leq 3.3 \text{ V}$	—	0.16	0.24
			$3.4 \text{ V} \leq V_{OUT(S)} \leq 5.0 \text{ V}$	—	0.12	0.20
Line Regulations	$\frac{\Delta V_{OUT1}}{\Delta V_{IN} \bullet V_{OUT}}$	$V_{OUT(S)} + 0.5 \text{ V} \leq V_{IN} \leq 5.5 \text{ V}$ $I_{OUT} = 1 \text{ mA}$	—	0.05	0.2	%/V
Input Voltage	$\Delta V_{OUT2}$	$V_{IN} = V_{OUT(S)} + 1.0 \text{ V}$ $1.0 \text{ mA} \leq I_{OUT} \leq 50 \text{ mA}$	—	20	40	mV
Output Voltage Temperature Characteristics	$\frac{\Delta V_{OUT}}{\Delta T_a \bullet V_{OUT}}$	$V_{IN} = V_{OUT(S)} + 1.0 \text{ V}$ , $I_{OUT} = 10 \text{ mA}$ $-40^\circ\text{C} \leq T_a \leq 85^\circ\text{C}$	—	$\pm 100$	—	ppm/ $^\circ\text{C}$
Supply Current	$I_{SS1}$	$V_{IN} = V_{OUT(S)} + 1.0 \text{ V}$	—	1	2	$\mu\text{A}$
Input Voltage	$V_{IN}$	—	1.8	—	6	V
Ripple-Rejection	$ RR $	$V_{IN} = V_{OUT(S)} + 1.0 \text{ V}$ , $f = 1.0 \text{ kHz}$ $V_{rip} = 0.5 \text{ Vrms}$ , $I_{OUT} = 10 \text{ mA}$	—	25	—	dB
Short current	$I_{short}$	$V_{IN} = V_{OUT(S)} + 1.5 \text{ V}$ ,	—	30	—	mA
Current Limiter	$I_{lim}$	$V_{IN} = V_{OUT(S)} + 1.5 \text{ V}$ ,	—	380	—	mA

## ■ Typical Performance Characteristics (3.0V output)


### 1. Output Voltage vs. Output Current




### 2. Output Voltage vs. Input Voltage




### 3. Dropout Voltage vs. Output Current




### 4. Dropout Voltage vs. Output Voltage



### 5. Output Voltage vs. Ambient Temperature




### 6. Ripple Rejection Rate




### 7. Transient Response

#### Input Transient Response




#### Load Transient Response




## ■ Packaging Information

- SOT-89-3



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.400	1.600	0.055	0.063
b	0.320	0.520	0.013	0.197
b1	0.400	0.580	0.016	0.023
c	0.350	0.440	0.014	0.017
D	4.400	4.600	0.173	0.181
D1	1.550 REF		0.061 REF	
E	2.300	2.600	0.091	0.102
E1	3.940	4.250	0.155	0.167
e	1.500 TYP		0.060 TYP	
e1	3.000 TYP		0.118 TYP	
L	0.900	1.200	0.035	0.047

● SOT-23-3L



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950(BSC)		0.037(BSC)	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°