



Relay Type: LP12 - DC12V
 Terminal Type: Nil Solder, P Plug In
 Coil Voltage:- DC: 6 ~ 220V
 AC: 6 ~ 380V

Features	Dimension L * W * H (mm)	58.8 * 33 * 28			
	Terminal Type	Solder/Plug in			
	Weight	80 gm Approximately			
Contact Data	Contact Form/Resistance	2C		100mΩ	
	Contact Material	Ag Alloy			
	Contact Capacity	10A @ 250VAC /28VDC			
Coil Data	Coil Voltage (DC) & (AC)	6 ~ 220 VDC 6 ~ 380 VAC			
	Coil Power Consumption	DC: 2.0W; AC 3.5VA			
	Coil Specification	Coil Voltage	Coil Resistance (Ω) ±10%	Pull in Voltage (VDC)	Drop Out Voltage (VDC)
		12 VDC	160	75%	10%
		24 VDC	500	75%	10%
240 VAC		10000	80%	30%	
General Data	Dielectric Strength	1200 VAC @ 50 Hz / Min (Between Open Contacts)			
		1500 VAC @ 50 Hz / Min (Between Coil & Contacts)			
	Insulation Resistance	500MΩ			
	Electrical Life	1 x 10 ⁵			
	Mechanical Life	1 x 10 ⁷			
Operating Temperature	- 25 °C ~ + 55°C				
Mounting Diagram					
Application	Vending Machine, Control Equipment, Cooking Appliances etc.				