

LP3970

Power Management Unit for Advanced Application Processors

General Description

The LP3970 is a multi-function, programmable Power Management Unit, designed especially for advanced application processors. The LP3970 has been optimized for low power handheld applications. PMU provides 11 low dropout, low noise linear regulators, two DC/DC magnetic buck regulators, a back-up battery charger and 4 GPO's. A high speed serial interface is included to program individual regulator output voltages as well on/off control.

Key Specifications

Buck regulators

- Programmable V_{OUT} from 0.8 to 3.5 V
- Up to 95% Efficiency
- 600 mA output current
- +3% output voltage accuracy

LDO's

- Programmable V_{OUT} of 1.5-3.3 V
- +3% output voltage accuracy
- 100/150/300 mA output current
- 100 mV (typ) Dropout


Features

- Compatible with advanced applications processors
- Additional buck regulator for powering high current peripheral devices
- 11 LDOs for powering Internal processor functions and I/O's
- Backup battery charger for Lithium and Lithium-Manganese coin cell batteries
- Automatic switching to backup battery
- High speed serial interface for independent control of device functions and settings
- Precision internal reference
- Thermal overload protection
- Current overload protection
- 48-lead 7x7x0.8 mm LLP package
- Software Programmable Low Noise LDO's

Applications

- PDA phones
- Smart phones
- Personal Media Players
- Digital Cameras

Simplified Application Circuit



20137101

Notes

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.

For the most current product information visit us at www.national.com.

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT AND GENERAL COUNSEL OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

BANNED SUBSTANCE COMPLIANCE

National Semiconductor certifies that the products and packing materials meet the provisions of the Customer Products Stewardship Specification (CSP-9-111C2) and the Banned Substances and Materials of Interest Specification (CSP-9-111S2) and contain no "Banned Substances" as defined in CSP-9-111S2.



National Semiconductor
Americas Customer
Support Center
Email: new.feedback@nsc.com
Tel: 1-800-272-9959

www.national.com

National Semiconductor
Europe Customer Support Center
Fax: +49 (0) 180-530 85 86
Email: europe.support@nsc.com
Deutsch Tel: +49 (0) 69 9508 6208
English Tel: +44 (0) 870 24 0 2171
Français Tel: +33 (0) 1 41 91 8790

National Semiconductor
Asia Pacific Customer
Support Center
Email: ap.support@nsc.com

National Semiconductor
Japan Customer Support Center
Fax: 81-3-5639-7507
Email: jpn.feedback@nsc.com
Tel: 81-3-5639-7560