


LQH2HPN101MGR#

“#” indicates a package specification code.



< List of part numbers with package codes >
LQH2HPN101MGRL

Shape



Notes

When rated current is applied to the products, inductance will be within ±30% of initial inductance value range.
Keep the temperature (ambient temperature plus self-generation of heat) under 105°C.
When rated current is applied to the products, the temperature rise caused by self-generated heat shall be limited to 20°C.

References

Packaging code	Specifications	Minimum quantity
L	φ180mm Embossed taping	3000






Mass (Typ.)	
1 piece	0.019g

Specifications

Inductance	100μH ±20%
Inductance test frequency	1MHz
Rated current (I _{sat}) (Based on Inductance change)	210mA
Rated current (I _{temp}) (Based on Temperature rise)	150mA(Ambient temp.85°C)
Max. of DC resistance	7.08Ω
Avg. of DC resistance	5.9Ω ±20%
Self resonance frequency (min.)	5MHz
Operating temperature range (Self-temperature rise is included)	-40°C to 105°C
Operating temperature range (Self-temperature rise is not included)	-40°C to 85°C
Class of magnetic shield	Magnetic Resin
Series	LQH2HPN_GR

Attention

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2.This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



⚠ Attention

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
 - 2.This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.