
muRata Inductor Data Sheet

LQH3NPN330MMR# "#" indicates a package specification code.



< List of part numbers with package codes > LQH3NPN330MMRE, LQH3NPN330MMRF





# Notes

When rated current is applied to the products, inductance will be within ±30% of nominal inductance value.

When rated current is applied to the products, the temperature rise caused by self-generated heat shall be limited to 40 °C max. Keep the temperature (ambient temperature plus self-generation of heat) under 125°C.



Packaging code	Specifications	Minimum quantity
F	φ330mm Embossed taping	8000
E	φ180mm_Embossed taping	2000

Mass (Typ.)	
1 piece	0.051g

## Specifications

Inductance	33μH ±20%
Inductance test frequency	1MHz
Rated current (Isat) (Based on Inductance change)	380mA
Rated current (Itemp) (Based on Temperature rise)	600mA
Max. of DC resistance	0.948Ω
Avg. of DC resistance	0.790Ω±20%
Self resonance frequency (min.)	15MHz
Operating temperature range (Self-temperature rise is included)	-40°C to 125°C
Operating temperature range (Self-temperature rise is not included)	-40°C to 85°C
Class of magnetic shield	Magnetic Resin
Series	LQH3NPN_MR

1 of 2

## 🔔 Attention


1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



# Chart of characteristic data (The charts below may show another part number which shares its characteristics.)



#### 2 of 2

#### 🔔 Attention

0

0

LQH3NPN330MMR

200

400

Current[mA]

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

1000

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

600

800