
muRata Inductor Data Sheet

LQM18PN2R2MGH#

"#" indicates a package specification code.

< List of part numbers with package codes > LQM18PN2R2MGHD , LQM18PN2R2MGHB





Notes

When rated current is applied to the products, inductance will be within $\pm 30\%$ of initial inductance value.

When rated current is applied to the products, the temperature rise caused by self-generated heat shall be limited to 40 °C max. Keep the temperature (ambient temperature plus self-generation of heat) under 125 °C.



Relefences

1	Packaging code	Specifications	Minimum quantity
	D	φ180mm Paper taping	4000
	В	Packing in bulk	1000

Mass (Typ.)	
1 piece	0.006g

Specifications

Inductance	2.2µH ±20%
Inductance test frequency	1MHz
Rated current (Isat) (Based on Inductance change)	0.25A(Max) / 0.35A(Typ.)
Rated current (Itemp) (Based on Temperature rise)	1.05A(Max) / 1.15A(Typ.)
Max. of DC resistance	0.25Ω
Avg. of DC resistance	0.2Ω (typ.)
Self resonance frequency (min.)	70MHz
Operating temperature range	-40°C to 85°C
Class of magnetic shield	Ferrite Core
Series	LQM18PN_GH

1 of 2

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued


without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Chart of characteristic data (The charts below may show another part number which shares its characteristics.)



2 of 2

🔔 Attention

0

0

LQM18PN2R2MGH

400

800

Current[mA]

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2000

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

1200

1600