

# SCHOTTKY BARRIER DIODE

● **Applications**

Low current rectification and high speed switching

● **Features**


- Extremely small surface mounting type. (SC-79/SOD523)
- Extremely Fast Switching Speed
- Extremely Low Forward Voltage 0.6 V (max) @ IF = 200mA
- Low Reverse Current

● **Construction**

Silicon epitaxial planar

- We declare that the material of product compliance with RoHS requirements.

## LRB520S-30T1G



### DEVICE MARKING AND ORDERING INFORMATION

Device	Marking	Shipping
LRB520S-30T1G	5J	3000/Tape&Reel
LRB520S-30T3G	5J	10000/Tape&Reel

### MAXIMUM RATINGS (T<sub>A</sub> = 25°C)

Parameter	Symbol	Limits	Unit
DC reverse voltage	V <sub>R</sub>	30	V
Mean rectifying current	I <sub>o</sub>	200	mA
Peak forward surge current	I <sub>FSM</sub>	1	A
Junction temperature	T <sub>j</sub>	125	°C
Storage temperature	T <sub>stg</sub>	-40~+125	°C

### ELECTRICAL CHARACTERISTICS(T<sub>A</sub> = 25°C)

Parameter	Symbol	Min.	Typ	Max.	Unit	Conditions
Forward voltage	V <sub>F</sub>	-	-	0.60	V	I <sub>F</sub> =200mA
Reverse current	I <sub>R</sub>	-	-	1.0	μA	V <sub>R</sub> =10V

LRB520S-30T1G

Electrical characteristic curves (Ta=25°C)




Fig. 1 Forward characteristics




Fig. 2 Reverse characteristics





Fig. 3 Capacitance between terminals characteristics







Fig. 4 Derating curve (mounting on glass epoxy PCBs)




Ct DISPERSION MAP




IFSM DISERSION MAP




IFSM-CYCLE CHARACTERISTICS




IFSM-t CHARACTERISTICS



Rth-t CHARACTERISTICS





Io-Pf CHARACTERISTICS




VR-Pr CHARACTERISTICS

LRB520S-30T1G

SC-79/SOD-523



**RECOMMENDED  
SOLDERING FOOTPRINT\***



NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

DIM	MILLIMETERS		
	MIN	NOM	MAX
A	0.50	0.60	0.70
b	0.25	0.30	0.35
c	0.07	0.14	0.20
D	1.10	1.20	1.30
E	0.70	0.80	0.90
H <sub>E</sub>	1.50	1.60	1.70
L	0.30 REF		
L2	0.15	0.20	0.25