


Dual Series Schottky Barrier Diodes

●Applications

General purpose detection
High speed switching

●Features

1. Small surface mounting type.
2. Low V_F and low I_R
3. High reliability
4. We declare that the material of product compliance with RoHS requirements.




ORDERING INFORMATION

| Device | Marking | Shipping |
|------------|---------|-------------------|
| LRB715WT1G | 3D | 3000/Tape & Reel |
| LRB715WT3G | 3D | 10000/Tape & Reel |

●Absolute maximum ratings (Ta=25°C)





| Parameter | Symbol | Limits | Unit |
|-----------------------------|-----------|----------|------|
| Peak reverse voltage | V_{RM} | 40 | V |
| DC reverse voltage | V_R | 40 | V |
| Mean rectifying current | I_o | 30 | mA |
| Peak forward surge current* | I_{FSM} | 200 | mA |
| Junction temperature | T_j | 125 | °C |
| Storage temperature | T_{stg} | -40~+125 | °C |

* 60 Hz for 1 

●Electrical characteristics (Ta=25°C)




| Parameter | Symbol | Min. | Typ. | Max. | Unit | Conditions |
|-------------------------------|--------|------|------|------|---------|------------------|
| Forward voltage | V_F | - | - | 0.37 | V | $I_F=1mA$ |
| Reverse current | I_R | - | - | 1 | μA | $V_R=10V$ |
| Capacitance between terminals | C_T | - | 2.0 | - | pF | $V_R=1V, f=1MHz$ |

Note) ESD sensitive product handling required.

Electrical characteristic curves (Ta=25°C)

Fig. 1 Forward characteristics

Fig. 2 Reverse characteristics

Fig. 3 Capacitance between terminals characteristics

Fig. 4 Reverse recovery time characteristics

LRB715WT1G

SC-89



NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETERS
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. 463C-01 OBSOLETE, NEW STANDARD 463C-02.

| DIM | MILLIMETERS | | | INCHES | | |
|-----|-------------|------|------|-----------|-------|-------|
| | MIN | NOM | MAX | MIN | NOM | MAX |
| A | 1.50 | 1.60 | 1.70 | 0.059 | 0.063 | 0.067 |
| B | 0.75 | 0.85 | 0.95 | 0.030 | 0.034 | 0.040 |
| C | 0.60 | 0.70 | 0.80 | 0.024 | 0.028 | 0.031 |
| D | 0.23 | 0.28 | 0.33 | 0.009 | 0.011 | 0.013 |
| G | 0.50 BSC | | | 0.020 BSC | | |
| H | 0.53 REF | | | 0.021 REF | | |
| J | 0.10 | 0.15 | 0.20 | 0.004 | 0.006 | 0.008 |
| K | 0.30 | 0.40 | 0.50 | 0.012 | 0.016 | 0.020 |
| L | 1.10 REF | | | 0.043 REF | | |
| M | --- | --- | 10 ° | --- | --- | 10 ° |
| N | --- | --- | 10 ° | --- | --- | 10 ° |
| S | 1.50 | 1.60 | 1.70 | 0.059 | 0.063 | 0.067 |

