

Linear Systems Log Conformance Monolithic Dual NPN

The LS318 is a monolithic pair of NPN transistors mounted in a single P-DIP package. The monolithic dual chip design reduces parasitics and is ideal for use in logging applications. See LS358 for PNP.

The 8 Pin P-DIP provides ease of manufacturing, and the symmetrical pinout prevents improper orientation.

(See Packaging Information).

LS318 Features:

- Tight matching
- Low Output Capacitance

FEATURES

LOG CONFORMANCE $\Delta r_e = 1\Omega$ TYP.

ABSOLUTE MAXIMUM RATINGS¹
@ 25°C (unless otherwise noted)

Maximum Temperatures

Storage Temperature -65°C to +200°C
Operating Junction Temperature -55°C to +150°C

Maximum Power Dissipation

Continuous Power Dissipation (One side) 250mW
Continuous Power Dissipation (Both sides) 500mW
Linear Derating factor (One side) 2.3mW/°C
Linear Derating factor (Both sides) 4.3mW/°C

Maximum Currents

Collector Current 10mA

MATCHING CHARACTERISTICS @ 25°C (unless otherwise stated)

SYMBOL	CHARACTERISTIC	MIN	TYP	MAX	UNITS	CONDITIONS
$ V_{BE1} - V_{BE2} $	Base Emitter Voltage Differential	--	0.4	1	mV	$I_C = 10\mu A, V_{CE} = 5V$
$\Delta (V_{BE1} - V_{BE2}) / \Delta T$	Base Emitter Voltage Differential Change with Temperature	--	1	5	$\mu V/^\circ C$	$I_C = 10\mu A, V_{CE} = 5V$ $T_A = -55^\circ C$ to $+125^\circ C$
$ I_{B1} - I_{B2} $	Base Current Differential	--	--	10	nA	$I_C = 10\mu A, V_{CE} = 5V$
$ \Delta (I_{B1} - I_{B2}) / ^\circ C$	Base Current Differential Change with Temperature	--	--	0.5	$nA/^\circ C$	$I_C = 10\mu A, V_{CE} = 5V$ $T_A = -55^\circ C$ to $+125^\circ C$
h_{FE1} / h_{FE2}	DC Current Gain Differential	--	5	--	%	$I_C = 10\mu A, V_{CE} = 5V$

ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)

SYMBOL	CHARACTERISTICS	MIN.	TYP.	MAX.	UNITS	CONDITIONS
Δr_e	Log Conformance	--	--	1.5	Ω	$I_C = 10-100-1000\mu A, V_{CE} = 5V$
BV_{CBO}	Collector to Base Voltage	25	--	--	V	$I_C = 10\mu A, I_E = 0$
BV_{CEO}	Collector to Emitter Voltage	25	--	--	V	$I_C = 10\mu A, I_B = 0$
BV_{EBO}	Emitter-Base Breakdown Voltage	6.2	--	--	V	$I_E = 10\mu A, I_C = 0^2$
BV_{CCO}	Collector to Collector Voltage	45	--	--	V	$I_C = 10\mu A, I_E = 0$
h_{FE}	DC Current Gain	150	--	600		$I_C = 10\mu A, V_{CE} = 5V$
		150	--	600		$I_C = 100\mu A, V_{CE} = 5V$
		150	--	--		$I_C = 1mA, V_{CE} = 5V$
$V_{CE(SAT)}$	Collector Saturation Voltage	--	--	0.25	V	$I_C = 1mA, I_B = 0.1mA$
I_{EBO}	Emitter Cutoff Current	--	--	0.2	nA	$I_C = 0, V_{EB} = 3V$
I_{CBO}	Collector Cutoff Current	--	--	0.2	nA	$I_E = 0, V_{CB} = 20V$
C_{OBO}	Output Capacitance	--	--	2	pF	$I_E = 0, V_{CB} = 3V$
C_{C1C2}	Collector to Collector Capacitance	--	--	2	pF	$V_{CC} = 0V$
I_{C1C2}	Collector to Collector Leakage Current	--	--	0.5	nA	$V_{CC} = \pm 45V$
f_T	Current Gain Bandwidth Product	200	--	--	MHz	$I_C = 1mA, V_{CE} = 5V$
NF	Narrow Band Noise Figure	--	--	3	dB	$I_C = 100\mu A, V_{CE} = 5V, BW=200Hz, R_G = 10K\Omega, f = 1KHz$

Notes:

1. Absolute Maximum ratings are limiting values above which serviceability may be impaired
2. The reverse base-to-emitter voltage must never exceed 6.2 volts; the reverse base-to-emitter current must never exceed 10 μA .

Available Packages:

LS318 in P-DIP
LS318 available as bare die

Please contact Micross for full package and die dimensions:

Email: chipcomponents@micross.com
Web: www.micross.com/distribution.aspx

P-DIP (Top View)

