

Linear Systems PNP Transistor

The LS3550SA is a PNP transistor mounted in a TO-92 package.

The TO-92 provides ease of manufacturing.

(See Packaging Information).

LS3550SA Features:

- Low Output Capacitance

FEATURES	
3 LEAD TO-92 PACKAGE	
ABSOLUTE MAXIMUM RATINGS ¹ @ 25°C (unless otherwise noted)	
Maximum Temperatures	
Storage Temperature	-65°C to +150°C
Operating Junction Temperature	-55°C to +150°C
Maximum Power Dissipation	
Continuous Power Dissipation	TBD
Maximum Currents	
Collector Current	10mA
Maximum Voltages	
Collector to Collector Voltage	80V


ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)

SYMBOL	CHARACTERISTICS	MIN.	TYP.	MAX.	UNITS	CONDITIONS
V_{CB0}	Collector to Base Voltage	-45	--	--	V	$I_C = 10\mu A, I_E = 0$
V_{CE0}	Collector to Emitter Voltage	-45	--	--	V	$I_C = 10\mu A, I_B = 0$
V_{EBO}	Emitter-Base Breakdown Voltage	-6.2	--	--	V	$I_E = 10\mu A, I_C = 0^2$
V_{CC0}	Collector to Collector Voltage	-80	--	--	V	$I_C = 10\mu A, I_E = 0$
h_{FE}	DC Current Gain	150	--	--		$I_C = -1mA, V_{CE} = -5V$
		120	--	--		$I_C = -10mA, V_{CE} = -5V$
		100	--	--		$I_C = -100mA, V_{CE} = -5V$
$V_{CE(SAT)}$	Collector Saturation Voltage	--	--	-0.25	V	$I_C = -100mA, I_B = -10mA$
I_{EBO}	Emitter Cutoff Current	--	--	-0.2	nA	$I_E = 0, V_{CB} = -3V$
I_{CBO}	Collector Cutoff Current	--	--	-0.2	nA	$I_E = 0, V_{CB} = -30V$
C_{OBO}	Output Capacitance	--	--	2	pF	$I_E = 0, V_{CB} = -10V$
f_T	Current Gain Bandwidth Product(Current)	--	--	600	MHz	$I_C = -1mA, V_{CE} = -5V$
NF	Narrow Band Noise Figure	--	--	3	dB	$I_C = -100\mu A, V_{CE} = -5V, BW=200Hz, R_G= 10\Omega, f = 1KHz$

- Notes:
- Absolute Maximum ratings are limiting values above which serviceability may be impaired
 - The reverse base-to-emitter voltage must never exceed 6.2 volts; the reverse base-to-emitter current must never exceed 10µA.



TO-92 (Bottom View)



Available Packages:

LS3550SA in TO-92
LS3550SA available as bare die

Please contact Micross for full package and die dimensions:

Email: chipcomponents@micross.com
Web: www.micross.com/distribution.aspx