




LS37 thru LS3B/SK37AFL thru SK310AFL

Surface Mount Schottky Rectifier
Reverse Voltage 70~100V Forward Current 3A

Features

- Schottky barrier diodes
- Low forward voltage drop
- Low leakage current
- Moisture sensitivity: level 1, per J-STD-020
- Solder dip 260 °C, 10 s
- Low profile, typical thickness 1.0mm
- AEC-Q101 qualified



eSGB (SMAF)

Typical Applications

For use in low voltage,high frequency inverters,free wheeling, and polarity protection application

Maximum Ratings (TA = 25 °C unless otherwise noted)						
Parameter	Symbol	LS37	LS38	LS39	LS3B	Unit
Maximum repetitive peak reverse voltage	VRRM	70	80	90	100	V
Maximum RMS voltage	VRMS	49	56	63	70	V
Maximum DC blocking voltage	VDC	70	70	70	70	V
Maximum average forward rectified current at TL (See Fig.1)	IF(AV)	3.0				A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load	IFSM	100				A
Operating junction and storage temperature range	TJ, TSTG	- 55 to + 150				°C

Electrical Characteristics (TA = 25 °C unless otherwise noted)							
Parameter	Test Conditions	Symbol	LS37	LS38	LS39	LS3B	Unit
Instantaneous forward voltage	IF=3A, TA=25°C	VF	Max:0.80				Volts
	IF=3A, TA=125°C		Typ:0.60				
Maximum DC reverse current at rated DC blocking voltage	TA=25°C	IR	500				uA
	TA=125°C		100				mA
Typical junction capacitance	4.0 V, 1 MHz	C _J	234				pF
Typical thermal resistance	junction to lead	R _{θJL} ¹⁾	20				°C/W

Note1:Thermal resistance from junction to lead,mounted on PCB with 8.0x8.0mm copper pads



LS37 thru LS3B/SK37AFL thru SK310AFL

Surface Mount Schottky Rectifier
Reverse Voltage 70~100V Forward Current 3A

Ratings and Characteristics Curves

(TA = 25°C unless otherwise noted)




Figure 1. Forward Current Derating Curve




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current




Figure 3. Typical Reverse Characteristics




Figure 4. Typical Junction Capacitance




Figure 5. Typical Instantaneous Forward Characteristics




LS37 thru LS3B/SK37AFL thru SK310AFL



Surface Mount Schottky Rectifier
Reverse Voltage 70~100V Forward Current 3A

Package Outline Dimensions


in inches (millimeters)



DIM	Unit: mm		Unit: inch	
	MIN	MAX	MIN	MAX
A	0.92	1.08	0.036	0.043
A1	0	0.1	0.000	0.004
B	1.25	1.45	0.049	0.057
C	0.1	0.25	0.004	0.010
D	2.6	2.8	0.102	0.110
E	4.1	4.3	0.161	0.169
L	0.7	1.1	0.028	0.043
HE	4.8	5.2	0.189	0.205



Soldering footprint




Packing Information

Packing quantities:

10,000 pcs/Reel, 12mm Tape, 13" Reel

Tape & Reel Specification





LS37 thru LS3B/SK37AFL thru SK310AFL

Surface Mount Schottky Rectifier
Reverse Voltage 70~100V Forward Current 3A

Disclaimers

These materials are intended as a reference to assist our customers in the selection of the Suzhou Good-Ark product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Suzhou Good-Ark Electronics Co., Ltd. or a third party.

Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.

All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Suzhou Good-Ark Electronics Co., Ltd. without notice due to product improvements or other reasons. It is therefore recommended that customers contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized Suzhou Good-Ark Electronics Co., Ltd. for the latest product information before purchasing a product listed herein. The information described here may contain technical inaccuracies or typographical errors. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors. Please also pay attention to information published by Suzhou Good-Ark Electronics Co., Ltd. by various means, including our website home page.

(<http://www.goodark.com>)

When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, Please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.

The prior written approval of Suzhou Good-Ark Electronics Co., Ltd. is necessary to reprint or reproduce in whole or in part these materials.

Please contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized distributor for further details on these materials or the products contained herein.