

**Samsung Secret**

Panel Information

Customer : Konka**DATE : 20. Mar. 2012****SAMSUNG TFT-LCD****MODEL : LSC400HL03*****(TFT Panel + Driver Kit)***

The Information Described in this Specification is Preliminary and can be changed without prior notice

LCD Business**Samsung Electronics Co . , LTD.**

MODEL

LSC400HL03

Doc. No

06-000-G-20120320

Page

1 / 27

Contents

Revision History	(3)
General Description	(4)
General Information	(4)
1. Absolute Maximum Ratings	(5)
2. Optical Characteristics	(6)
3. Electrical Characteristics	(9)
3.1 TFT LCD Module	
3.2 Back Light Unit	
3.3 Converter Input & Specification	
4. Input Terminal Pin Assignment	(12)
4.1 Input Signal & Power	
4.2 Converter Input Pin Configuration	
4.3 Converter Input Power Sequence	
4.4 LVDS Interface	
4.5 Input Signals, Basic Display Colors and Gray Scale of Each Color	
5. Interface Timing	(18)
5.1 Timing Parameters (DE only mode)	
5.2 LVDS Input data Characteristics	
5.3 3D mode Sequence	
5.4 Timing Diagrams of interface Signal (DE only mode)	
5.5 Power ON/OFF Sequence	
6. Outline Dimension	(22)
7. Packing	(24)
8. Marking & Others	(25)
9. General Precaution	(26)
9.1 Handling	
9.2 Storage	
9.3 Operation	
9.4 Operation Condition Guide	
9.5 Others	

Samsung Secret**Revision History**

Date	Rev. No	Page	Summary
Mar. 20. 2012	000	All	First issue

MODEL

LSC400HL03

Doc. No

06-000-G-20120320

Page

3 / 27

General Description

Samsung Secret

Description

LSC400HL03 is a color active matrix liquid crystal display (LCD) that uses amorphous silicon TFT (Thin Film Transistor) as switching components. This model is composed of a TFT LCD panel, a driver circuit, and an assembly KIT of source PBA. The model has a resolution of a 1920 x 1080 and can display up to 1.07 Billion colors with wide viewing angle of 89° or higher degree in all directions. This panel is designed applications by providing an excellent performance function of the Flat Panel Display such as Home-alone Multimedia TFT-LCD TV and High Definition TV.

Features

- RoHS compliance (Pb-free)
- High contrast ratio & aperture ratio with wide color gamut
- SPVA (Super Patterned Vertical Align) mode
- Wide viewing angle ($\pm 178^\circ$)
- High speed response
- FHD resolution (16:9)
- DE (Data Enable) mode
- 2ch LVDS (Low Voltage Differential Signaling) interface (2pixel/clock)

General Information

Items	Specification	Unit	Note
Outline Size	902.6(H) × 517.1(V) × 1.80(D)	mm	
Pixel Pitch	0.46 (H) x 0.46(V)	mm	
Active Display Area	885.6 (H) X 498.15(V)	mm	
Surface Treatment	Anti-Glare		
Display Colors	1.07 Billion (10bit)	colors	
Number of Pixels	1920 x 1080	pixel	16:9
Pixel Arrangement	RGB vertical stripe		
Display Mode	Normally Black		

Samsung Secret

1. Absolute Maximum Ratings

If the condition exceeds maximum ratings, it can cause malfunction or unrecoverable damage on the device.

Item	Symbol	Min.	Max.	Unit	Note
Power Supply Voltage	V_{DD}	10.8	13.2	V	(1)
Storage temperature	T_{STG}	5	40	°C	(2), (4)
Operating temperature	T_{OPR}	0	50	°C	(2), (5)
Storage humidity	H_{STG}	35	75	%RH	(2), (4)
Operating humidity	H_{STG}	20	90	%RG	(2), (5)
Endurance on static electricity			150	V	(3)

Note (1) $T_a = 25 \pm 2$ °C

(2) Temperature and the range of relative humidity are shown in the figure below.

a. 90 % RH Max. ($T_a \leq 39$ °C)

b. Relative Humidity is 90% or less. ($T_a > 39$ °C)

c. No condensation

(3) Keep the static electricity under 150V in process the polarizer is attached on glass

(4) The storage condition with glass

(5) The operating condition with assembly





Fig. Temperature and Relative humidity range

2. Optical Characteristics

Samsung Secret

The optical characteristics should be measured in a dark room or the space surrounded by similar setting.

Measuring equipment : TOPCON RD-80S, TOPCON SR-3, ELDIM EZ-Contrast

(Ta = 25 ± 2°C, VDD=12V, fv= 60Hz, f_{DCLK} = 148.5MHz, **Light source : D65 standard**)

Item	Symbol	Condition	Min.	Typ.	Max.	Unit	Note	
Contrast Ratio (Center of screen)	C/R		3000	4000	-		(1) SR-3	
Response Time *	G-to-G	Tg	-	8	15	msec	(2) RD-80S	
Luminance of White (Center of screen)	Y _L		TBD	TBD	-	cd/m ²	(3) SR-3	
Color Chromaticity (CIE 1931)	Red	Rx	Normal q _{L,R} = 0 q _{U,D} = 0 Viewing Angle	TBD	+0.03		(4) SR-3	
		Ry		TBD				
	Green	Gx		TBD				
		Gy		TBD				
	Blue	Bx		TBD				
		By		TBD				
	White	Wx		TBD				
		Wy		TBD				
Color Gamut	-		-	TBD	-	%	(4) SR-3	
Color Temperature	-		-	TBD	-	K		
Viewing Angle	Hor.	q _L	C/R≥10	75	89	-	Degree	(5) EZ-Contrast
		q _R		75	89	-		
	Ver.	q _U		75	89	-		
		q _D		75	89	-		

- The characteristics of light source (D65 , The general light source)

- Color Temperature : 6487K
- Wx, Wy : 0.313, 0.329
- Luminance of white : 7217 cd/m²

- Response time is measured using general backlight not D65 standard.

- 3D crosstalk is managed by response time on 2D mode.

MODEL

LSC400HL03

Doc. No

06-000-G-20120320

Page

6 / 27


Samsung Secret

- Test Equipment Setup


The measurement should be executed in a stable, windless and dark room between 40min and 60min after operating the panel at the given temperature for stabilization of the D65 standard light. This should be measured in the center of screen.

Environment condition : $T_a = 25 \pm 2 \text{ }^\circ\text{C}$

Photo detector	Field
SR-3	2° /1°
RD-80S	1°



- Definition of test point



Note (1) Definition of Contrast Ratio (C/R)


: Ratio of gray max (Gmax) & gray min (Gmin) at the center point ⑤ of the panel

$$C/R = \frac{G_{\max}}{G_{\min}}$$

Gmax : Luminance with all pixels white

Gmin : Luminance with all pixels black

Note (2) Definition of Response time : Sum of Tr, Tf




Note (3) Definition of Luminance of White : Luminance of white at center point ⑤

Note (4) Definition of Color Chromaticity (CIE 1931)

Color coordinate of Red, Green, Blue & White at center point ⑤

Note (5) Definition of Viewing Angle

: Viewing angle range (C/R ≥ 10)

3. Electrical Characteristics

3.1 TFT LCD Module

The connector for display data & timing signal should be connected.

$T_a = 25^\circ\text{C} \pm 2^\circ\text{C}$

Item	Symbol	Min.	Typ.	Max.	Unit	Note
Voltage of Power Supply	V_{DD}	10.8	12.0	13.2	V	(1)
Current of Power Supply	(a) Black	-	TBD	TBD	mA	(2),(3)
	(b) White	-	TBD	TBD	mA	
	(c) N-PTN	-	TBD	TBD	mA	
Vsync Frequency	f_V	48	60	62.5	Hz	
Hsync Frequency	f_H	60	67.5	70	kHz	
Main Frequency	f_{DCLK}	130	148.5	152.5	MHz	
Rush Current	I_{RUSH}	-	-	4	A	(4)

Note (1) The ripple voltage should be controlled under 10% of V_{DD} .

(2) $f_V=60\text{Hz}$, $f_{DCLK} = 148.5\text{MHz}$, $V_{DD} = 12.0\text{V}$, DC Current.

(3) Power dissipation check pattern (LCD panel only)


a) Black Pattern




b) White Pattern



c) N-PTN



(4) Measurement Conditions



Rush Current I_{RUSH} can be measured when T_{RUSH} is $470 \mu\text{s}$.

4. Input Terminal Pin Assignment

Samsung Secret

4.1 Input Signal & Power

Pin	Description	Pin	Description
1	NC	26	3D EN
2	NC	27	NC
3	NC	28	Rx2[0]N
4	NC	29	Rx2[0]P
5	3D_Sync_O	30	Rx2[1]N
6	GND *note (2)	31	Rx2[1]P
7	GND	32	Rx2[2]N
8	NC	33	Rx2[2]P
9	NC	34	GND
10	NC	35	Rx2CLKN
11	GND	36	Rx2CLKP
12	Rx1[0]N	37	GND
13	Rx1[0]P	38	Rx2[3]N
14	Rx1[1]N	39	Rx2[3]P
15	Rx1[1]P	40	Rx2[4]N *note (1)
16	Rx1[2]N	41	Rx2[4]P *note (1)
17	Rx1[2]P	42	NC
18	GND	43	NC
19	Rx1CLKN	44	GND
20	Rx1CLKP	45	GND
21	GND	46	GND
22	Rx1[3]N	47	NC
23	Rx1[3]P	48	VCC
24	Rx1[4]N *note (1)	49	VCC
25	Rx1[4]P *note (1)	50	VCC
		51	VCC


Note : No connection, Pins are used only for SEC.

Note(1) If 8bit of LVDS signal input from SET,

Keep [4]channel **level '0'**




Note(2) 3D format is set with interleave function only .



Samsung Secret

Note4) Pin number starts from Right side



- All GND pins should be connected together and also be connected to the LCD's metal chassis.
- All power input pins should be connected together.
- All NC pins should be separated from other signal or power.

4.2 LVDS Interface

Samsung Secret

- LVDS Receiver : T-con (merged)
- Data Format (JEIDA only)

	LVDS pin	JEIDA -DATA
TxOUT/RxIN0	TxIN/RxOUT0	R4
	TxIN/RxOUT1	R5
	TxIN/RxOUT2	R6
	TxIN/RxOUT3	R7
	TxIN/RxOUT4	R8
	TxIN/RxOUT6	R9
	TxIN/RxOUT7	G4
TxOUT/RxIN1	TxIN/RxOUT8	G5
	TxIN/RxOUT9	G6
	TxIN/RxOUT12	G7
	TxIN/RxOUT13	G8
	TxIN/RxOUT14	G9
	TxIN/RxOUT15	B4
	TxIN/RxOUT18	B5
TxOUT/RxIN2	TxIN/RxOUT19	B6
	TxIN/RxOUT20	B7
	TxIN/RxOUT21	B8
	TxIN/RxOUT22	B9
	TxIN/RxOUT24	HSYNC
	TxIN/RxOUT25	VSYNC
	TxIN/RxOUT26	DEN
TxOUT/RxIN3	TxIN/RxOUT27	R2
	TxIN/RxOUT5	R3
	TxIN/RxOUT10	G2
	TxIN/RxOUT11	G3
	TxIN/RxOUT16	B2
	TxIN/RxOUT17	B3
	TxIN/RxOUT23	RESERVED
TxOUT/RxIN4	TxIN/RxOUT28	R0
	TxIN/RxOUT29	R1
	TxIN/RxOUT30	G0
	TxIN/RxOUT31	G1
	TxIN/RxOUT32	B0
	TxIN/RxOUT33	B1
	TxIN/RxOUT34	RESERVED

Samsung Secret

4.3 Input Signals, Basic Display Colors and Gray Scale of Each Color

COLOR	DISPLAY (10bit)	DATA SIGNAL																													GRAY SCALE LEVEL					
		RED										GREEN										BLUE														
		R0	R1	R2	R3	R4	R5	R6	R7	R8	R9	G0	G1	G2	G3	G4	G5	G6	G7	G8	G9	B0	B1	B2	B3	B4	B5	B6	B7	B8		B9				
BASIC COLOR	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	-
	BLUE	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	-
	GREEN	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	-	
	CYAN	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	-	
	RED	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	-	
	MAGENTA	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	-	
	YELLOW	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	-	
	WHITE	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	-	
GRAY SCALE OF RED	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R0			
	DARK ↑	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1			
		0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R2			
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	R3~R1020		
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:		
	LIGHT ↓	1	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1021			
		0	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1022			
	RED	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1023		
GRAY SCALE OF GREEN	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G0		
	DARK ↑	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G1		
		0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G2		
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	G3~G1020		
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:		
	LIGHT ↓	0	0	0	0	0	0	0	0	0	0	1	0	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	G1021			
		0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	G1022			
	GREEN	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	G1023			
GRAY SCALE OF BLUE	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	B0			
	DARK ↑	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	B1			
		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	B2			
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	B3~B1020		
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:		
	LIGHT ↓	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	1	1	1	1	1	1	1	1	B1021			
		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	B1022			
	BLUE	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	B1023			

Note) Definition of Gray :

Rn : Red Gray, Gn : Green Gray, Bn : Blue Gray (n = Gray level)

Input Signal : 0 = Low level voltage, 1 = High level voltage

Samsung Secret

5. Interface Timing

5.1 Timing Parameters (DE mode)

SIGNAL	ITEM	SYMBOL	MIN.	TYP.	MAX.	Unit	NOTE
Clock	Frequency	$1/T_C$	130	148.5	152.5	MHz	-
Hsync		F_H	60	67.5	70	KHz	-
Vsync		F_V	48	60	62.5	Hz	-
Vertical Display Term	Active Display Period	T_{VD}	-	1080	-	Lines	-
	Vertical Total	T_V	1110	1125	1400	Lines	-
Horizontal Display Term	Active Display Period	T_{HD}	-	1920	-	Clocks	-
	Horizontal Total	T_H	2092	2200	2348	clocks	-

Note) For DE only mode,

Product doesn't have to receive the signal of H-sync and V-sync from input device.

(1) Test Point : TTL control signal and CLK at input terminal of LVDS Tx of the system

(2) Internal VDD = 3.3V

(3) Spread spectrum

- Modulation rate (max) : $\pm 1.5\%$



- Modulation Frequency : under 100KHz

Samsung Secret

5. 2 LVDS Input Data Characteristics

ITEM	SYMBOL	Min.	Typ.	Max.	UNIT	NOTE
Input common mode voltage	V_{CM}	0.3	-	1.8	V	
Differential Input Voltage	$ V_{ID} $	100	-	600	mV	
Input Data Position	t_{RSRM}	-	-	400	ps	
	t_{RSLM}	-400	-	-	ps	


Note) The Spread Spectrum should be 0% when the skew is measured.



Samsung Secret

5.3 3D mode Sequence

5.3.1 3D Sequence




Timing	Spec (ms)			Description
	Min.	Typ.	Max	
T7	≥ 42			Backlight should be on after 10 frame when 3D signal input from SET
T8	≥ 30			Backlight should be off after 7 frame when 3D signal change to 2D signal from SET

5.3.2 Level of 3D Control signal

Test Items	Test Condition		Spec	
			Min	Max
3D Enable Level	C-PBA Input Level (Change to 3D mode)	High	(2.7)	(3.3)
		Low	0.0	(0.4)

Samsung Secret


5.4 Timing diagrams of interface signal (DE mode)



5.5 Power ON/OFF Sequence

Samsung Secret

To prevent a latch-up or DC operation of the LCD Module, the power on/off sequence should be accorded with the settings described in the diagram below.



T1 : V_{DD} rising time from 10% to 90%

T2 : The time from V_{DD} to valid data at power ON.

T3 : The time from valid data off to V_{DD} off at power Off.


T4 : V_{DD} off time for Windows restart

T5 : The time from valid data to B/L enable at power ON.

T6 : The time from valid data off to B/L disable at power Off.

- The condition of supply voltage to enter in the module from the external system should have the same condition as the definition of VDD.
- Apply the voltage for the lamp within the range which the LCD operates. When the back light is turned on before the LCD is operated or when the LCD is turned off before the back light is turned off, the display may show the abnormal screen momentarily.
- While the VDD is off level, please keep the level of input signals low or keep a high impedance condition.
- The figure of T4 should be measured after the module has been fully discharged between the periods when the power is on and off.
- The interface signal must not keep the high impedance condition when the power is on.
- Interface signal should not be kept at high impedance when the power is on.
- In Case T5 is less than 1000msec and T6 is less than 100msec, Garbage Display can be seen. (It is not related to electrical function issue, Just for recommendation to prevent Garbage Display)

FILE NO.		A	B	C	D	E	F	G	H
NO	PART NAME	CODE NO	SPECIFICATION		QTY	WEIGHT	FINISH	MATERIAL	INCLUDED QTY OF MATERIAL
									REMARK




REV	DATE		DESCRIPTION		CHK'D BY		REASON		CHK'D BY	
	UNIT	mm	DRAWN BY	DES'N BY	APP'D BY	MODEL NAME		46" NNB 60Hz+		SHEET 1/1
	SCALE	1:1000	Y.K.HONG			PART/SHEET NAME		PCB CONTROL		
	TOLERANCE	LEVEL 2	12. 01. 04		SPEC. NO	CODE NO.				VER. 00
GENERAL TOLERANCE			LEVEL 1	LEVEL 2	LEVEL 3	SAMSUNG ELECTRONICS				
STEP	LEVEL 1	LEVEL 2	LEVEL 3							
0 < X <= 4	±0.05	±0.1	±0.2							
4 < X <= 16	±0.08	±0.15	±0.3							
16 < X <= 64	±0.12	±0.25	±0.5							
64 < X <= 256	±0.25	±0.4	±0.5							

Samsung Secret

7. PACKING

7.1 The order for products to be stacked on the pallet



7.2 Packing Specification

Item	Specification	Remark
Total Pallet Size	W×V×Height [mm]	TBD X TBD XTBD
Tray	TBD [Panel/Tray]	- . Panel : TBD kg (TBD kg/Panel, TBD ea/Tray)) - . Middle Sheet : TBD kg (TBD kg/ea, TBD ea/Tray) - . Panel Tray : TBD kg (EPS)
Pallet	TBD [Tray/Pallet]	- . Pallet TBD kg (wood pallet) - . TBD ea + TBD ea(Top tray)
Total Weight	TBD [kg]	- . Packing Box : TBD kg (Paper)

Samsung Secret

8. MARKING & OTHERS


A nameplate bearing followed by is affixed to a shipped product at the specified location on each product.

8.1 Cell Label

Source
D-IC




- (1) Part number : LSC400HL03
- (2) Revision : three letters
- (3) Lot number : X X X X XXX XX X



Samsung Secret

8.2 Box Label



9. General Precautions

9.1 Handling

- (a) When the panel kit and BLU kit are assembled, the panel kit and BLU kit should be attached to the set system firmly by combining each mounted holes. Be careful not to give the mechanical stress.
- (b) Be careful not to give any extra mechanical stress to the panel when designing the set, and BLU kit.
- (c) Be cautious not to give any strong mechanical shock and / or any forces to the panel kit. Applying the any forces to the panel may cause the abnormal operation or the damage to the panel kit and the back light unit kit.
- (d) Refrain from applying any forces to the source PBA and the drive IC in the process of the handling or installing to the set. If any forces are applied to the products, it may cause a damage or a malfunction in the panel kit.
- (e) Refrain from applying any forces which cause a constant shock to the back side of panel kit, the set design and BLU kit. If any forces are applied to the products, it may cause an abnormal display, a functional failure and etc.
- (f) Note that polarizer could be damaged easily.
Do not press or scratch the bare surface with the material which is harder than a HB pencil lead.
- (g) Wipe off water droplets or oil immediately. If you leave the droplets for a long time on the product, a staining or the discoloration may occur.
- (h) If the surface of the polarizer is dirty, clean it using the absorbent cotton or the soft cloth.
- (i) Desirable cleaners are water or IPA(Isopropyl Alcohol).
Do not use Ketone type materials(ex. Acetone), Ethyl alcohol, Toluene, Ethyl acid or Methyl chloride. These might cause the permanent damage to the polarizer due to chemical reaction.
- (j) If the liquid crystal material leaks from the panel, this should be kept away from the eyes or mouth. If this contacts to hands, legs ,or clothes, you must washed it away with soap thoroughly and see a doctor for the medical examination.
- (k) Protect the panel kit and BLU Kit out of the static electricity. Otherwise the circuit IC could be damaged.

* Reference : Process control standard of SEC

No.	Item	Control standard
1	Ionizer	All Equipment should be controlled under 150V.(Typ. 100V)
2	Carrying Roller	Carrying Roller should be controlled under 200V.
3	Equipment GND Resistance	All Equipment Ground Should be less than 1ohm.

- (l) Remove the stains with finger-stalls wearing soft gloves in order to keep the display clean in the process of the incoming inspection and the assembly process.
- (m) Do not pull or fold the source drive IC which connects to the source PBA and the panel or the gate drive IC.
- (n) Do not pull, fold or bend the source drive IC and the gate drive IC in any processes. If not, the source drive IC could be bent one time in the process of assembling the panel Kit and the BLU Kit.
- (o) Do not adjust the variable resistor located on the panel kit and BLU kit except when adjusting the flicker.
- (p) Do not touch the pins of the interface connector directly with bare hands.
- (q) Be cautious not to be peeled off the protection film.




Fig. GND SR-Open Pattern – Be sure to be contacted to the ground while peeling of the protection film

- Make sure to peel off slowly
(It is recommended to peel it off at the speed of more than 8sec. constantly.)
- The peeling direction is shown at the left fig.
- Instruct the ground worker to work with the adequate methods such as the antistatic wrist band.
- Make sure to be grounded the source PBA while peeling of the protection film.
- Ionized air should be blown over during the peeling
- The protection film should not be contacted to the source drive IC.
- If the adhesive stains remain on the polarizer after the protection film is peeled off, please remove stains with isopropyl-alcohol liquid.

Samsung Secret

9.2 Storage

ITEM	Unit	Min.		Max.			
Storage Temperature	(°C)	5		40			
Storage Humidity	(%rH)	35		75			
Storage life	6 months						
Storage Condition	(1) The storage room should provide good ventilation and temperature control. (2) Products should not be placed on the floor, but on the Pallet away from a wall. (3) Prevent products from direct sunlight, moisture nor water; Be cautious of a build up of condensation. (4) Avoid other hazardous environment while storing goods. (5) If products delivered or kept in conditions of the recommended temperature or humidity, we recommend you leave them at a circumstances which is shown in the following table.						
	After	1 month	2 month	3 month	4month	5 month	6month
	Baking	No backing		50°C 10% 24Hr	50°C 10% 48Hr		

9.3 Operation

- (a) Do not connect, disconnect the module in the "Power On" condition.
- (b) Power supply should always be turned on/off by the item 5.5 "Power on/off sequence"
- (c) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference shall be done by system manufacturers. Grounding and shielding methods may be important to minimize the interference.
- (d) The cable between the back-light connector and its inverter power supply shall be a minimized length and be connected directly. The longer cable between the back-light and the inverter/converter may cause lower luminance of CCFL/LED and may require higher startup voltage(Vs).

9.4 Operation Condition Guide

(a) The LCD product should be operated under normal conditions.

Normal condition is defined as below;

- Temperature : $20 \pm 15^{\circ}\text{C}$
- Humidity : $55 \pm 20\%$
- Display pattern : continually changing pattern (Not stationary)

(b) If the product will be used in extreme conditions such as high temperature, humidity, display patterns or operation time etc., It is strongly recommended to contact SEC for Application engineering advice. Otherwise, its reliability and function may not be guaranteed. Extreme conditions are commonly found at Airports, Transit Stations, Banks, Stock market, and Controlling systems.

9.5 Others

(a) The ultra-violet ray filter is necessary for the outdoor operation.

(b) Avoid the condensation of water which may result in the improper operation of product or the disconnection of electrode.

(c) Do not exceed the limit on the absolute maximum rating. (For example, the supply voltage variation, the input voltage variation, the variation in content of parts and environmental temperature, and so on) If not, the module may be damaged.

(d) If the module keeps displaying the same pattern for a long period of time, the image may be remained to the screen.
To avoid the image sticking, it is recommended to use a screen saver.

(e) This module has its circuitry of PCB's on the rear side and should be handled carefully in order for a force not to be applied.

(f) Please contact the SEC in advance when the same pattern is displayed for a long time.