



LED Backlight Diagram:



| Pin No. | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 |
|---------|-----|-----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|----|----|----|----|
| Symbol | VSS | VDD | BL | RS | /WR | /RD | DB0 | DB1 | DB2 | DB3 | DB4 | DB5 | DB6 | DB7 | /CS | /RST | NC | NC | NC | NC |

Notes:

- 5.7" Transmissive, Normally-White TFT-LCD Module
- Viewing Direction: 12:00
- LCD Controller: SSD1926
- LED Driver: CL6201x2
- Operation Temp.: -10°C~70°C
- Storage Temp.: -30°C~80°C

| DWN. | YDY | TITLE | LCM OUTLINE DIMENSION | | |
|-------|-----------|----------|-----------------------|------------|--------|
| CHK. | LYJ | PART NO. | LT057B-01A | | |
| APPD. | | DWG. NO. | LT057BW-01A-A | | |
| REV. | A | UNIT | mm | PROJECTION | |
| DATE | '08.10.06 | SCALE | NTS | SHEET | 1 OF 1 |