



ELECTRONICS

Product Information

Customer :Gen

SAMSUNG TFT-LCD
MODEL : LTA550HF02

The Information Described in this Specification is Preliminary and can be changed without prior notice

NOTE :

Table with 2 columns: APPROVED BY (with signatures) and DATE (5.March.2009)

LCD Business

Samsung Electronics Co . , LTD.

Table with 6 columns: MODEL, LTA550HF02, Doc. No, 06-002-G-090305, Page, 1 / 29

## Contents

General Description .....	(3)
General Information .....	(3)
1. Absolute Maximum Ratings .....	(4)
2. Optical Characteristics .....	(6)
3. Electrical Characteristics .....	(9)
3.1 TFT LCD Module	
3.2 Back Light Unit	
3.3 Inverter Input Condition & Specification	
4. Block Diagram .....	(12)
5. Input Terminal Pin Assignment .....	(13)
5.1 Input Signal & Power	
5.2 Inverter Input Pin Configuration	
5.3 Inverter Input Power Sequence	
5.4 LVDS Interface	
5.5 Input Signals, Basic Display Colors and Gray Scale of Each Color	
6. Interface Timing .....	(18)
6.1 Timing Parameters (DE only mode)	
6.2 Timing Diagrams of interface Signal (DE only mode)	
6.3 Power ON/OFF Sequence	
7. Outline Dimension .....	(21)
8. Packing .....	(23)
9. Marking & Others .....	(24)
10. General Precaution .....	(25)
10.1 Handling	
10.2 Storage	
10.3 Operation	
10.4 Operation Condition Guide	
10.5 Others	

<b>MODEL</b>	<b>LTA550HF02</b>	<b>Doc. No</b>	<b>06-002-G-090305</b>	<b>Page</b>	<b>2 / 29</b>
--------------	-------------------	----------------	------------------------	-------------	---------------

## \* Revision History

Date	Rev. No	Page	Summary
Feb 23,2009	000	all	First issued
March 2,2009	001	4,7	Luminance of White 450nit→ 500nit
March 3,2009	002	4	Display color 8bit→10bit(FRC)

**MODEL**

**LTA550HF02**

**Doc. No**

**06-002-G-090305**

**Page**

**3 / 29**

## General Description

### Description

**LTA550HF02** is a color active matrix liquid crystal display (LCD) that uses amorphous silicon TFT (Thin Film Transistor) as switching components. This model is composed of a TFT LCD panel, a driver circuit and a back light unit.

The resolution of a 55.0" is 1920 x 1080 and this model can display up to 16.7 Million colors with wide viewing angle of 90° or higher in all directions. This panel is intended to support applications to provide an excellent performance for Flat Panel Display such as Home-alone Multimedia TFT-LCD TV and High Definition TV.

### Features

- RoHS compliance (Pb-free)
- High contrast & aperture ratio
- SPVA (Super Patterned Vertical Align) mode
- Wide viewing angle ( $\pm 178^\circ$ )
- High speed response
- FHD resolution (16:9)
- Low Power consumption
- Direct Type 22CCFLs (Cold Cathode Fluorescent Lamp)
- DE (Data Enable) mode
- LVDS (Low Voltage Differential Signaling) interface

## General Information

Items	Specification	Unit	Note
Module Size	1267.6(H <sub>TYP</sub> ) x 744.4(V <sub>TYP</sub> )	mm	±1.0mm
	60.0(D <sub>MAX</sub> )		
Weight	17000(Max.)	g	
Pixel Pitch	0.6(H) x 0.6(W)	mm	
Active Display Area	1209.6(H) X 680.4(V)	mm	
Surface Treatment	10bit(FRC)-1.06B	-	
Display Colors	8bit – 16.7M	Colors	
Number of Pixels	1920 x 1080	Pixel	
Pixel Arrangement	RGB vertical stripe	-	
Display Mode	Normally Black	-	
Luminance of White	<b>500</b> (Typ.)	cd/m <sup>2</sup>	

<b>MODEL</b>	<b>LTA550HF02</b>	<b>Doc. No</b>	<b>06-002-G-090305</b>	<b>Page</b>	<b>4 / 29</b>
--------------	-------------------	----------------	------------------------	-------------	---------------

## 1. Absolute Maximum Ratings

If the condition exceeds maximum ratings, it can cause malfunction or unrecoverable damage to the device.

Item	Symbol	Min.	Max.	Unit	Note	
Power Supply Voltage	$V_{DD}$	$V_{DD} - 1.2$	$V_{DD} + 1.2$	V	(1)	
Storage temperature	$T_{STG}$	-20	60	°C	(2)	
Glass surface temperature (Operation)	Center	$T_{OPR}$	0	50	°C	(2),(5)
	T. Uniformity	$\Delta T$	-	10	°C	
Shock ( non - operating )	$S_{nop}$	-	30	G	(3)	
Vibration ( non - operating )	$V_{nop}$	-	1.5	G	(4)	

Note (1)  $T_a = 25 \pm 2 \text{ }^\circ\text{C}$

(2) Temperature and relative humidity range are shown in the figure below.

a. 90 % RH Max. ( $T_a \leq 39 \text{ }^\circ\text{C}$ )

b. Relative Humidity is 90% or less. ( $T_a > 39 \text{ }^\circ\text{C}$ )

c. No condensation

(3) 11ms, sine wave, one time for  $\pm X, \pm Y, \pm Z$  axis

(4) 10-300 Hz, Sweep rate 10min, 30min for X,Y,Z axis





Fig. Temperature and Relative humidity range

(5) Definition of test point



$\Delta T$  should be less than  $10\text{ }^{\circ}\text{C}$  ( $\Delta T = |T_{\text{OPR}} - T_{\text{MAX}}|$ )

$T_{\text{OPR}}$  : Temperature of the center of the glass surface (Test point 5)

$T_1 \sim T_4$  : Temperature of each edge of the glass surface

$T_{\text{MAX}}$  : The highest temperature of the glass surface

## 2. Optical Characteristics

The optical characteristics should be measured in a dark room or equivalent.

Measuring equipment : TOPCON RD-80S, TOPCON SR-3 ,ELDIM EZ-Contrast

(Ta = 25 ± 2°C, VDD=12.0V, fv=120Hz, f<sub>DCLK</sub>=297MHz, Max. Dimming =3.3V)

Item	Symbol	Condition	Min.	Typ.	Max.	Unit	Note	
Contrast Ratio (Center of screen)	C/R	Normal $\theta_{L,R}=0$ $\theta_{U,D}=0$  Viewing Angle	4000	<b>5,000</b>	-		(1) SR-3	
Response Time	G-to-G		Tg	-	6	9	msec	(3) RD-80S
	Rising		Tr	-	10	13		
	Falling		Tf	-	6	10		
Luminance of White (Center of screen)	Y <sub>L</sub>			450	<b>500</b>	-	cd/m <sup>2</sup>	(4) SR-3
Color Chromaticity (CIE 1931)	Red		Rx	TYP. -0.03	0.650	TYP. +0.03		(5),(6) SR-3
			Ry		0.330			
	Green		Gx		0.285			
			Gy		0.635			
	Blue		Bx		0.150			
		By	0.057					
	White	Wx	0.280					
		Wy	0.290					
Color Gamut	-	-	72	-	%	(5) SR-3		
Color Temperature	-	-	10,000	-	K			
Viewing Angle	Hor.	$\theta_L$	-	90	-	Degree	(6) EZ-Contrast	
		$\theta_R$	-	90	-			
	Ver.	$\theta_U$	-	90	-			
		$\theta_D$	-	90	-			
Brightness Uniformity - Test(Equipment Setup)	B <sub>uni</sub>		-	-	25	%	(2) SR-3	

The measurement should be executed in a stable, windless and dark room between 40min and 60min after lighting the back light at the given temperature for stabilization of the back light. This should be measured in the center of screen.

. Max. Dimming = 3.3V

. Environment condition : Ta = 25 ± 2 °C

MODEL

LTA550HF02


Doc. No

06-002-G-090305


Page

7 / 29

Photo detector	Field
SR-3	1°
RD-80S	2°



- Definition of test point



Note (1) Definition of Contrast Ratio (C/R)

: Ratio of gray max (Gmax) & gray min (Gmin) at the center point ⑤ of the panel

$$C/R = \frac{G \max}{G \min}$$

Gmax : Luminance with all pixels white

Gmin : Luminance with all pixels black




Note (2) Definition of 9 points brightness uniformity (Test pattern : Full White)

$$B_{uni} = 100 * \frac{(B_{max} - B_{min})}{B_{max}}$$

Bmax : Maximum brightness

Bmin : Minimum brightness

Note (3) Definition of Response time : Sum of Tr, Tf



※ G-to-G : Average response time between Gray to Gray (Scale)


Note (4) Definition of Luminance of White : Luminance of white at center point ⑤

Note (5) Definition of Color Chromaticity (CIE 1931)

Color coordinate of Red, Green, Blue & White at center point ⑤

Note (6) Definition of Viewing Angle

: Viewing angle range (C/R ≥ 10)



### 3. Electrical Characteristics

#### 3.1 TFT LCD Module

The connector for display data & timing signal should be connected.

$T_a = 25^{\circ}\text{C} \pm 2^{\circ}\text{C}$

Item	Symbol	Min.	Typ.	Max.	Unit	Note
Voltage of Power Supply	$V_{DD}$	10.8	12	13.2	V	(1)
Current of Power Supply	(a) Black	-	1800	2000	mA	(2),(3)
	(b) White	-	1800	2000	mA	
	(c) H-Stripe	-	3200	3500	mA	
Vsync Frequency	$f_V$	90	120	125	Hz	
Hsync Frequency	$f_H$	100	135	140	kHz	
Main Frequency	$F_{dclk}$	240	297	310	MHz	
Rush Current	$I_{RUSH}$		-	7	A	(4)

Note (1) The ripple voltage should be controlled under 10% of  $V_{DD}$ .

(2)  $f_V=120\text{Hz}$ ,  $f_{DCLK}=297\text{MHz}$ ,  $V_{DD}=12.0\text{V}$ , DC Current.

(3) Power dissipation check pattern (LCD Module only)


a) Black Pattern




b) White Pattern



c) H-Stripe



(4) Measurement Conditions




Rush Current  $I_{RUSH}$  can be measured when  $T_{RUSH}$  is  $470 \mu\text{s}$ .

MODEL	LTA550HF02	Doc. No	06-002-G-090305	Page	10 / 29
-------	------------	---------	-----------------	------	---------

### 3.2 Back Light Unit

The back light unit contains 22 direct-lighting type CCFLs ( Cold Cathode Fluorescent Lamp ). The characteristics of lamps are shown in the following tables.

$T_a = 25 \pm 2^\circ\text{C}$



Item	Symbol	Min.	Typ.	Max.	Unit	Note
Operating Life Time	Hr	50,000	-	-	Hour	(1)

Note (1) It is defined as the time to take until the brightness reduces to 50% of its original value.

[Operating condition :  $T_a = 25 \pm 2^\circ\text{C}$ ,  $I_L = \text{TBD}$  , For single lamp only. ]

### 3.3 Inverter Input Condition & Specification

Items	Symbol	Conditions	Specifications			Unit	Note
			Min.	Typ.	Max.		
Input Voltage	V <sub>in</sub>	-	22	24	26	V	Ta=25±2 °C
Input Current	I <sub>RUSH</sub>	V <sub>in</sub> = 24V V <sub>dim</sub> = 3.3V	-	10.8	-	A	(1)
			-	9.6	-		(2)
Lamp Current	I <sub>o</sub>	V <sub>in</sub> = 24V V <sub>dim</sub> = 3.3V	7.0	7.5	8.0	mArms	(2)
Frequency	F <sub>LAMP</sub>	V <sub>in</sub> = 24V	42	44	46	kHz	-
Backlight On/Off	ON	V <sub>in</sub> = 24V	2.4	-	5.5	V	(3)
	OFF	V <sub>in</sub> = 24V	0	-	0.8		
Dimming Control	V <sub>DIM</sub>	Max Lum	3.3	-	-	V	(4)
		Min. Lum	-	-	0		

Note) Power Consumption is measured when 500[cd/m<sup>2</sup>] of luminance which is the typical luminance.


Lamp Current is measured at the point before Lamp.

- (1) Max Value of the Power Consumption is measured during initial turn-on time\* of the backlight.
- (2) Max Value of the Power Consumption is measured after 120 min warm-up.
- (3) Inverter pin NO.12 is for backlight On/Off.
- (4) Inverter pin NO.13 is for dimming control.

\* Initial turn-on time : From 0sec to 60min after turn-on

<b>MODEL</b>	<b>LTA550HF02</b>	<b>Doc. No</b>	<b>06-002-G-090305</b>	<b>Page</b>	<b>12 / 29</b>
--------------	-------------------	----------------	------------------------	-------------	----------------

#### 4. Block Diagram



MODEL	LTA550HF02	Doc. No	06-002-G-090305	Page	13 / 29
-------	------------	---------	-----------------	------	---------

## 5. Input Terminal Pin Assignment

### 5.1. Input Signal & Power

Connector : FI-RE41S-HF (JAE)

Pin	Symbol	Description	Pin	Symbol	Description
1	12V	DC power supply	26	Rx3[A]P	3 <sup>rd</sup> , 7 <sup>th</sup> LVDS Signal +
2	12V	DC power supply	27	Rx3[B]N	3 <sup>rd</sup> , 7 <sup>th</sup> LVDS Signal -
3	12V	DC power supply	28	Rx3[B]P	3 <sup>rd</sup> , 7 <sup>th</sup> LVDS Signal +
4	12V	DC power supply	29	Rx3[C]N	3 <sup>rd</sup> , 7 <sup>th</sup> LVDS Signal -
5	12V	DC power supply	30	Rx3[C]P	3 <sup>rd</sup> , 7 <sup>th</sup> LVDS Signal +
6	<b>NC</b>	<b>NOTE</b>	31	GND	Ground
7	GND	Ground	32	Rx3CLK-	3 <sup>rd</sup> , 7 <sup>th</sup> LVDS Clock -
8	GND	Ground	33	Rx3CLK+	3 <sup>rd</sup> , 7 <sup>th</sup> LVDS Clock +
9	GND	Ground	34	GND	Ground
10	Rx1[A]N	1 <sup>st</sup> , 5 <sup>th</sup> LVDS Signal -	35	Rx3[D]N	3 <sup>rd</sup> , 7 <sup>th</sup> LVDS Signal -
11	Rx1[A]P	1 <sup>st</sup> , 5 <sup>th</sup> LVDS Signal +	36	Rx3[D]P	3 <sup>rd</sup> , 7 <sup>th</sup> LVDS Signal +
12	Rx1[B]N	1 <sup>st</sup> , 5 <sup>th</sup> LVDS Signal -	37	Rx3[E]N	3 <sup>rd</sup> , 7 <sup>th</sup> LVDS Signal -
13	Rx1[B]P	1 <sup>st</sup> , 5 <sup>th</sup> LVDS Signal +	38	Rx3[E]P	3 <sup>rd</sup> , 7 <sup>th</sup> LVDS Signal +
14	Rx1[C]N	1 <sup>st</sup> , 5 <sup>th</sup> LVDS Signal -	39	GND	Ground
15	Rx1[C]P	1 <sup>st</sup> , 5 <sup>th</sup> LVDS Signal +	40	<b>NC</b>	<b>NOTE</b>
16	GND	Ground	41	<b>NC</b>	
17	Rx1CLK-	1 <sup>st</sup> , 5 <sup>th</sup> LVDS Clock -			
18	Rx1CLK+	1 <sup>st</sup> , 5 <sup>th</sup> LVDS Clock +			
19	GND	Ground			
20	Rx1[D]N	1 <sup>st</sup> , 5 <sup>th</sup> LVDS Signal -			
21	Rx1[D]P	1 <sup>st</sup> , 5 <sup>th</sup> LVDS Signal +			
22	Rx1[E]N	1 <sup>st</sup> , 5 <sup>th</sup> LVDS Signal -			
23	Rx1[E]P	1 <sup>st</sup> , 5 <sup>th</sup> LVDS Signal +			
24	GND	Ground			
25	Rx3[A]N	3 <sup>rd</sup> , 7 <sup>th</sup> LVDS Signal -			

### **NOTE**

**NC( No Connection) : These PINS are used only for SAMSUNG . (DO NOT CONNECT)**

<b>MODEL</b>	<b>LTA550HF02</b>	<b>Doc. No</b>	<b>06-002-G-090305</b>	<b>Page</b>	<b>14 / 29</b>
--------------	-------------------	----------------	------------------------	-------------	----------------

## 5. Input Terminal Pin Assignment

### 5.1. Input Signal & Power

Connector : FI-RE51S-HF (JAE)

Pin	Symbol	Description	Pin	Symbol	Description
1	12V	DC power supply	26	Rx4[A]P	4 <sup>th</sup> , 8 <sup>th</sup> LVDS Signal +
2	12V	DC power supply	27	Rx4[B]N	4 <sup>th</sup> , 8 <sup>th</sup> LVDS Signal -
3	12V	DC power supply	28	Rx4[B]P	4 <sup>th</sup> , 8 <sup>th</sup> LVDS Signal +
4	12V	DC power supply	29	Rx4[C]N	4 <sup>th</sup> , 8 <sup>th</sup> LVDS Signal -
5	12V	DC power supply	30	Rx4[C]P	4 <sup>th</sup> , 8 <sup>th</sup> LVDS Signal +
6	<b>NC</b>	<b>NOTE1</b>	31	GND	Ground
7	GND	Ground	32	Rx4CLK-	4 <sup>th</sup> , 8 <sup>th</sup> LVDS Clock -
8	GND	Ground	33	Rx4CLK+	4 <sup>th</sup> , 8 <sup>th</sup> LVDS Clock +
9	GND	Ground	34	GND	Ground
10	Rx2[A]N	2 <sup>nd</sup> , 6 <sup>th</sup> LVDS Signal -	35	Rx4[D]N	4 <sup>th</sup> , 8 <sup>th</sup> LVDS Signal -
11	Rx2[A]P	2 <sup>nd</sup> , 6 <sup>th</sup> LVDS Signal +	36	Rx4[D]P	4 <sup>th</sup> , 8 <sup>th</sup> LVDS Signal +
12	Rx2[B]N	2 <sup>nd</sup> , 6 <sup>th</sup> LVDS Signal -	37	Rx4[E]N	4 <sup>th</sup> , 8 <sup>th</sup> LVDS Signal -
13	Rx2[B]P	2 <sup>nd</sup> , 6 <sup>th</sup> LVDS Signal +	38	Rx4[E]P	4 <sup>th</sup> , 8 <sup>th</sup> LVDS Signal +
14	Rx2[C]N	2 <sup>nd</sup> , 6 <sup>th</sup> LVDS Signal -	39	GND	Ground
15	Rx2[C]P	2 <sup>nd</sup> , 6 <sup>th</sup> LVDS Signal +	40	<b>NC</b>	<b>NOTE1</b>
16	GND	Ground	41	<b>NC</b>	
17	Rx2CLK-	2 <sup>nd</sup> , 6 <sup>th</sup> LVDS Clock -	42	<b>NC</b>	
18	Rx2CLK+	2 <sup>nd</sup> , 6 <sup>th</sup> LVDS Clock +	43	<b>NC</b>	
19	GND	Ground	44	<b>NC</b>	
20	Rx2[D]N	2 <sup>nd</sup> , 6 <sup>th</sup> LVDS Signal -	45	LVDS_SEL	NOTE2
21	Rx2[D]P	2 <sup>nd</sup> , 6 <sup>th</sup> LVDS Signal +	46	<b>NC</b>	<b>NOTE1</b>
22	Rx2[E]N	2 <sup>nd</sup> , 6 <sup>th</sup> LVDS Signal -	47	<b>NC</b>	
23	Rx2[E]P	2 <sup>nd</sup> , 6 <sup>th</sup> LVDS Signal +	48	<b>NC</b>	
24	GND	Ground	49	<b>NC</b>	
25	Rx4[A]N	4 <sup>th</sup> , 8 <sup>th</sup> LVDS Signal -	50	<b>NC</b>	
			51	<b>NC</b>	<b>NOTE1</b>

**Note1) No Connection: These PINS are used only for SAMSUNG. (DO NOT CONNECT)**

Note2) LVDS OPTION : If this PIN is HIGH (3.3 V) → Normal LVDS format


LOW (GND) → JEIDA LVDS format

**SEQUENCE** : On =  $V_{DD}(T1) \geq LVDS\ Option \geq Interface\ Signal(T2)$

OFF =  $Interface\ Signal(T3) \geq LVDS\ Option \geq V_{DD}$

<b>MODEL</b>	<b>LTA550HF02</b>	<b>Doc. No</b>	<b>06-002-G-090305</b>	<b>Page</b>	<b>15 / 29</b>
--------------	-------------------	----------------	------------------------	-------------	----------------

Note(1) Pin number starts from Left side



**Fig. Connector diagram**

- a. Power GND pins should be connected to the LCD's metal chassis.
- b. All power input pins should be connected together.
- c. All NC pin should be separated from other signal or power.

MODEL	LTA550HF02	Doc. No	06-002-G-090305	Page	16 / 29
-------	------------	---------	-----------------	------	---------




## 5.2 Inverter Input Pin Configuration

Connector : JST, S14B-PHA-SM-TB(LF)

Pin No.	Pin Configuration (FUNCTION)
1	Vin (24 V)
2	Vin (24 V)
3	Vin (24 V)
4	Vin (24 V)
5	Vin (24 V)
6	GND
7	GND
8	GND
9	GND
10	GND
11	<b>No Connection (DO NOT CONNECT)</b>
12	Backlight On /Off [ON: 2.4 ~ 5.5 V, OFF: 0 ~ 0.8 V]
13	Dimming Control [ 0V: Min, 3.3V: Max ]
14	<b>No Connection (DO NOT CONNECT)</b>

## 5.3. Inverter Input Power Sequence



MODEL	LTA550HF02	Doc. No	06-002-G-090305	Page	17 / 29
-------	------------	---------	-----------------	------	---------

### 5.3 LVDS Interface

- LVDS Receiver : Tcon (merged)
- Data Format (JEIDA)

	LVDS pin	JEIDA -DATA	VESA-DATA
TxOUT/RxIN0	TxIN/RxOUT0	R4	R0
	TxIN/RxOUT1	R5	R1
	TxIN/RxOUT2	R6	R2
	TxIN/RxOUT3	R7	R3
	TxIN/RxOUT4	R8	R4
	TxIN/RxOUT6	R9	R5
	TxIN/RxOUT7	G4	G0
TxOUT/RxIN1	TxIN/RxOUT8	G5	G1
	TxIN/RxOUT9	G6	G2
	TxIN/RxOUT12	G7	G3
	TxIN/RxOUT13	G8	G4
	TxIN/RxOUT14	G9	G5
	TxIN/RxOUT15	B4	B0
	TxIN/RxOUT18	B5	B1
TxOUT/RxIN2	TxIN/RxOUT19	B6	B2
	TxIN/RxOUT20	B7	B3
	TxIN/RxOUT21	B8	B4
	TxIN/RxOUT22	B9	B5
	TxIN/RxOUT24	HSYNC	HSYNC
	TxIN/RxOUT25	VSYNC	VSYNC
	TxIN/RxOUT26	DEN	DEN
TxOUT/RxIN3	TxIN/RxOUT27	R2	R6
	TxIN/RxOUT5	R3	R7
	TxIN/RxOUT10	G2	G6
	TxIN/RxOUT11	G3	G7
	TxIN/RxOUT16	B2	B6
	TxIN/RxOUT17	B3	B7
	TxIN/RxOUT23	RESERVED	RESERVED
TxOUT/RxIN4	TxIN/RxOUT28	R0	R8
	TxIN/RxOUT29	R1	R9
	TxIN/RxOUT30	G0	G8
	TxIN/RxOUT31	G1	G9
	TxIN/RxOUT32	B0	B8
	TxIN/RxOUT33	B1	B9
	TxIN/RxOUT34	RESERVED	RESERVED

## 5.5 Input Signals, Basic Display Colors and Gray Scale of Each Color

COLOR	DISPLAY (8bit)	DATA SIGNAL																								GRAY SCALE LEVEL
		RED							GREEN							BLUE										
		R0	R1	R2	R3	R4	R5	R6	R7	G0	G1	G2	G3	G4	G5	G6	G7	B0	B1	B2	B3	B4	B5	B6	B7	
BASIC COLOR	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	-
	BLUE	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	-
	GREEN	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	-
	CYAN	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	-
	RED	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	-
	MAGENTA	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	-
	YELLOW	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	-
	WHITE	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	-
GRAY SCALE OF RED	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R0	
	DARK ↑	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1	
		0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R2	
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	R3~	
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	R252	
	LIGHT ↓	1	0	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R253	
		0	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R254	
	RED	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R255	
GRAY SCALE OF GREEN	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G0	
	DARK ↑	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G1	
		0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	G2	
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	G3~	
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	G252	
	LIGHT ↓	0	0	0	0	0	0	0	0	1	0	1	1	1	1	1	1	0	0	0	0	0	0	0	G253	
		0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	0	0	0	0	0	0	0	G254	
	GREEN	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	G255	
GRAY SCALE OF BLUE	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	B0	
	DARK ↑	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	B1	
		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	B2	
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	B3~	
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	B252	
	LIGHT ↓	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	1	1	1	1	1	B253	
		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	B254	
	BLUE	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	B255	

Note) Definition of Gray :

Rn : Red Gray, Gn : Green Gray, Bn : Blue Gray (n = Gray level)

Input Signal : 0 = Low level voltage, 1 = High level voltage

MODEL	LTA550HF02	Doc. No	06-002-G-090305	Page	19 / 29
-------	------------	---------	-----------------	------	---------

## 6. Interface Timing

### 6.1 Timing Parameters ( DE only mode )

SIGNAL	ITEM	SYMBOL	MIN.	TYP.	MAX.	Unit	NOTE
Clock	Frequency	$1/T_C$	240	297	310	MHz	-
Hsync		$F_H$	100	135	140	KHz	-
Vsync		$F_V$	90	120	125	Hz	-
Vertical Display Term	Active Display Period	$T_{VD}$	-	1080	-	Lines	-
	Vertical Total	$T_V$	1090	1125	1380	Lines	-
Horizontal Display Term	Active Display Period	$T_{HD}$	-	1920	-	Clocks	-
	Horizontal Total	$T_H$	2090	2200	2350	clocks	-

Note) This product is DE only mode. The input of Hsync & Vsync signal does not have an effect on normal operation.

(1) Test Point : TTL control signal and CLK at LVDS Tx input terminal in system


(2) Internal  $V_{DD} = 3.3V$

(3) Spread spectrum

- Modulation rate (max) :  $\pm 1.5 \%$

- Modulation Frequency : under 100KHz


## 6.2 Timing diagrams of interface signal ( DE only mode )



MODEL	LTA550HF02	Doc. No	06-002-G-090305	Page	21 / 29
-------	------------	---------	-----------------	------	---------

### 6.3 Power ON/OFF Sequence

To prevent a latch-up or DC operation of the LCD Module, the power on/off sequence should be as the diagram below.





- T1 : V<sub>DD</sub> rising time from 10% to 90%
- T2 : The time from V<sub>DD</sub> to valid data at power ON.
- T3 : The time from valid data off to V<sub>DD</sub> off at power Off.
- T4 : V<sub>DD</sub> off time for Windows restart
- T5 : The time from valid data to B/L enable at power ON.
- T6 : The time from valid data off to B/L disable at power Off.

- The supply voltage of the external system for the Module input should be the same as the definition of V<sub>DD</sub>.
- Apply the lamp voltage within the LCD operation range. When the back light turns on before the LCD operation or the LCD turns off before the back light turns off, the display may momentarily show abnormal screen.
- In case of V<sub>DD</sub> = off level, please keep the level of input signals low or keep a high impedance.
- T4 should be measured after the Module has been fully discharged between power off and on period.
- Interface signal should not be kept at high impedance when the power is on.

MODEL	LTA550HF02	Doc. No	06-002-G-090305	Page	22 / 29
-------	------------	---------	-----------------	------	---------


NO	PART NAME	CODE NO	SPECIFICATION	Q'TY	WEIGHT FINISH MATERIAL	UNFOLDED DIM. OF MATERIAL	REMARK
	OUTLINE DIMENSION(FRONT)		LTA550HF02-001				



SECTION A-A (2:1)

\* NOTES

- BACKLIGHT : CCFL
- CONNECTOR SPECIFICATION  
- TO SMP5 : -  
- TO LD LOGIC : -
- WEIGHT SPEC. : TBD
- Torque Spec. : Machine Screw ; 5.0 ~ 5.5 kgfcm  
Taplite Screw ; 3.0 ~ 3.5 kgfcm
- USER HOLE : -
- BLACK MATRIX SPEC  
- |A - B| ≤ 2.0 mm  
- |C - D| ≤ 2.0 mm



7. CHASSIS TOP & POL GAP SPEC : MAX1.5mm

PRELIMINARY

GENERAL TOLERANCE				REV	DATE	DESCRIPTION OF REVISION			REASON	CHG'D BY	
STEP	LEVEL 1	LEVEL 2	LEVEL 3	UNIT	mm	DRA'N BY	DES'D BY	CHK'D BY	APP'D BY	MODEL NAME	
0 < X ≤ 4	±0.05	±0.1	±0.2	SCALE	N/S	S.W. CHUNG	Y.H. LEE	J.H. CHUN		LTA550HF02-001	
4 < X ≤ 16	±0.08	±0.15	±0.3	TOLERANCE		2009.02.20	2009.02.23	2009.02.23		OUTLINE DIMENSION(FRONT)	
16 < X ≤ 64	±0.12	±0.25	±0.5	SPEC. NO						SHEET 1/2	
64 < X ≤ 256	±0.25	±0.4	±0.8	SAMSUNG ELECTRONICS							REV. 000






## 8. PACKING

### 8.1 CARTON (Internal Package)

(1) Packing Form

Corrugated fiberboard box and corrugated cardboard as shock absorber

(2) Packing Method



### 8.2 Packing Specification

Item	Specification	Remark
LCD Packing	13ea / (Packing-Pallet Box)	1. 221 Kg / LCD (13ea) 2. 13.4 Kg / Cushion-pallet (2ea) 3. 10.5Kg / Packing-Pallet Box (1ea) 4. Cushion-pallet Material : EPS 5. Packing-Pallet Box Material : SW3
Pallet	1Box / Pallet	1. Pallet weight = 10kg
Packing Direction	Vertical	
Total Pallet Size	H x V x height	1475mm(H) x 1150mm(V) x 935mm(height)
Total Pallet Weight	254.9kg	Pallet(10kg) + Module(221kg) + Cushion(up+bottom=13.4kg) + Pallet-BOX(10.5kg)

MODEL

LTA550HF02

Doc. No

06-002-G-090305


Page

25 / 29


## 9. MARKING & OTHERS

A nameplate bearing followed by is affixed to a shipped product at the specified location on each product.


- (1) Part number : LTA550HF02
- (2) Revision: Three letters
- (3) Lot number : X X X X XXX XX X



### (4) Nameplate Indication



### (5) Packing box attach



### (6) Others

- 1. After service part

Lamps cannot be replaced because of the narrow bezel structure.

MODEL	LTA550HF02	Doc. No	06-002-G-090305	Page	26 / 29
-------	------------	---------	-----------------	------	---------

## 10. General Precautions

### 10.1 Handling

- (a) When the Module is assembled, it should be attached to the system firmly using all mounting holes. Be careful not to twist and bend the Module.
- (b) Because the inverter use high voltage, it should be disconnected from power before it is assembled or disassembled.
- (c) Refrain from strong mechanical shock and / or any force to the Module.  
In addition to damage, this may cause improper operation or damage to the Module and CCFL back light.
- (d) Note that polarizers are very fragile and could be damage easily.  
Do not press or scratch the surface harder than a HB pencil lead.
- (e) Wipe off water droplets or oil immediately. If you leave the droplets for a long time, staining or discoloration may occur.
- (f) If the surface of the polarizer is dirty, clean it using absorbent cotton or soft cloth.
- (g) Desirable cleaners are water, IPA(Isopropyl Alcohol) or Hexane.  
Do not use Ketone type materials(ex. Acetone), Ethyl alcohol, Toluene, Ethyl acid or Methyl chloride. It might permanent damage to the polarizer due to chemical reaction.
- (h) If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth . In case of contact with hands, legs or clothes, it must be washed away with soap thoroughly.
- (i) Protect the module from Electrostatic discharge. Otherwise the ASIC IC or Semiconductor would be damaged.
- (j) Use finger-stalls with soft gloves in order to keep display clean during the incoming inspection and assembly process.
- (k) Do not disassemble the Module.
- (l) Do not disassemble shield case of inverter & LVDS board.
- (m) Do not connect N.C pins. (Samsung internal use only)
- (n) Protection film for polarizer on the Module should be slowly peeled off just before use so that the electrostatic charge can be minimized. Must put on antistatic glove while handle a module
- (o) Pins of I/F connector should not be touched directly with bare hands.

**MODEL**

**LTA550HF02**

**Doc. No**

**06-002-G-090305**

**Page**

**27 / 29**

## 10.2 Storage

- (a) Do not leave the Module in high temperature, and high humidity for a long time. It is highly recommended to store the Module with temperature from 0 to 35 °C and relative humidity of less than 70%.
- (b) Do not store the TFT-LCD Module in direct sunlight.
- (c) The Module should be stored in a dark place. It is prohibited to apply sunlight or fluorescent light in storing.

## 10.3 Operation

- (a) Do not connect or disconnect the Module in the "Power On" condition.
- (b) Power supply should always be turned on/off by the "Power on/off sequence"
- (c) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference should be done by system manufacturers. Grounding and shielding methods may be important to minimize the interference.
- (d) The cable between the back light connector and its inverter power supply should be connected directly with a minimized length. A longer cable between the back light and the inverter may cause lower luminance of lamp(CCFT) and may require higher startup voltage(Vs).

## 10.4 Operation Condition Guide

- (a) The LCD product should be operated under normal conditions.  
Normal condition is defined as below;
  - Temperature :  $20 \pm 15$  °C
  - Humidity :  $55 \pm 20$  %
  - Display pattern : continually changing pattern (Not stationary)
- (b) If the product will be used in extreme conditions such as high temperature, humidity, display patterns or operation time etc., It is strongly recommended to contact SEC for Application engineering advice. Otherwise, its reliability and function may not be guaranteed. Extreme conditions are commonly found at Airports, Transit Stations, Banks, Stock market, and Controlling systems.

<b>MODEL</b>	<b>LTA550HF02</b>	<b>Doc. No</b>	<b>06-002-G-090305</b>	<b>Page</b>	<b>28 / 29</b>
--------------	-------------------	----------------	------------------------	-------------	----------------

## 10.5 Others

- (a) Ultra-violet ray filter is necessary for outdoor operation.
- (b) Avoid condensation of water. It may result in improper operation or disconnection of electrode.
- (c) Do not exceed the absolute maximum rating value. ( supply voltage variation, input voltage variation, variation in part contents and environmental temperature, and so on)  
Otherwise the Module may be damaged.
- (d) If the Module keeps displaying the same pattern for a long period of time, the image may be "sticked " to the screen.  
To avoid image sticking, it is recommended to use a screen saver.
- (e) This Module has its circuitry PCB's on the rear side and should be handled carefully in order not to be stressed.
- (f) Please contact SEC in advance when you display the same pattern for a long time.

<b>MODEL</b>	<b>LTA550HF02</b>	<b>Doc. No</b>	<b>06-002-G-090305</b>	<b>Page</b>	<b>29 / 29</b>
--------------	-------------------	----------------	------------------------	-------------	----------------