



ELECTRONICS

**Samsung Secret**

Product Information

Model No. :  
Parts Code : V33A00040500

**Customer : Toshiba**

**DATE : 13. JAN. 2011**

**SAMSUNG TFT-LCD**  
**MODEL : LTA550HJ12**

The Information Described in this Specification is Preliminary and can be changed without prior notice

APPROVED BY <i>Heo Jeongmin</i>	DATE 13. JAN. 2011	PREPARED BY <i>Cho Eun Hae</i>	DATE 13. JAN. 2011
------------------------------------	-----------------------	-----------------------------------	-----------------------

LCD Business

Samsung Electronics Co . , LTD.

MODEL	LTA550HJ12	Doc. No	06-000-S-20110113	Page	1/26
-------	------------	---------	-------------------	------	------

## Contents

**Samsung Secret**

General Description .....	(3)
General Information .....	(3)
1. Absolute Maximum Ratings .....	(4)
1.1 TFT LCD Module Absolute Maximum Ratings	
1.2 LED Bar Unit Absolute Maximum Ratings	
2. Optical Characteristics .....	(6)
3. Electrical Characteristics .....	(9)
3.1 TFT LCD Module	
3.2 Back Light Unit	
3.3 LED Bar Unit	
4. Input Terminal Pin Assignment .....	(11)
4.1 Input Signal & Power	
4.2 Extended LED Cable Connector Input Pin Configuration	
4.3 LVDS Interface	
4.4 Input Signals, Basic Display Colors and Gray Scale of Each Color	
5. Interface Timing .....	(17)
5.1 Timing Parameters (DE only mode)	
5.2 Timing Diagrams of interface Signal (DE only mode)	
5.3 Power ON/OFF Sequence	
6. Outline Dimension .....	(20)
7. Packing .....	(22)
8. Marking & Others .....	(23)
9. General Precaution .....	(24)
9.1 Handling	
9.2 Storage	
9.3 Operation	
9.4 Operation Condition Guide	
9.5 Others	

## General Description

**Samsung Secret**

### Description

**LTA550HJ12** is a color active matrix liquid crystal display (LCD) that uses amorphous silicon TFT(Thin Film Transistor) as switching components. This model is composed of a TFT LCD panel, a driver circuit and a back light unit. The resolution of a 55.0" is 1,920 x 1,080 and this model can display up to 1.07 Billion colors with wide viewing angle of 89° or higher in all directions. This panel is intended to support applications to provide a excellent performance for Flat Panel Display such as Home-alone Multimedia TFT-LCD TV and High Definition TV.

### Features

- RoHS compliance (Pb-free)
- High contrast ratio & aperture ratio with wide color gamut
- SPVA(Super Patterned Vertical Align) mode
- Wide viewing angle ( $\pm 178^\circ$ )
- High speed response ( & Natural Motion (DFR: Double Frame Rate) )
- FHD resolution (16:9)
- Low Power consumption
- Edge Type LED (Light Emitted Diode) BLU
- DE (Data Enable) mode
- 4ch LVDS (Low Voltage Differential Signaling) interface (4pixel/clock)

### General Information

Items	Specification	Unit	Note
Module Size	1247.6(H) x 719.9(V)	mm	$\pm 1.0$ mm
	30.5(D)		
Weight	12.8	kg	$\pm 1$ kg
Pixel Pitch	0.21(H) x 0.63(V)	mm	
Active Display Area	1209.6(H) x 680.4(V)	mm	
Surface Treatment	Haze 5.0 %, Hard Coating 3H		Anti Glare
Display Colors	1.07 Billion	colors	10bit Dithering
Number of Pixels	1,920 x 1,080	pixel	
Pixel Arrangement	RGB vertical stripe		
Display Mode	Normally Black		
Luminance of White	400 (Typ.)	cd/m <sup>2</sup>	

MODEL

LTA550HJ12

Doc. No

06-000-S-20110113

Page

3/26

## 1. Absolute Maximum Ratings

If the condition exceeds maximum ratings, it can cause malfunction or unrecoverable damage to the device.

### 1.1 TFT LCD Module Absolute Maximum Ratings

( $V_{DD}=12V$ )

Item	Symbol	Min.	Max.	Unit	Note
Power Supply Voltage	$V_{DD}$	GND-0.5	13.2	V	(1)
Storage temperature	$T_{STG}$	-20	60	°C	(2)
Operating temperature	$T_{OPR}$	0	50	°C	
Surface temperature	$T_{SUR}$	0	60	°C	(3)
Shock ( non - operating )	X,Y,Z	-	30	G	(4)
Vibration ( non - operating )	$V_{NOP}$	-	1.5	G	(5)

Note (1)  $T_a = 25 \pm 2 \text{ }^\circ\text{C}$

(2) Temperature and relative humidity range are shown in the figure below.

a. 90 % RH Max. ( $T_a \leq 39 \text{ }^\circ\text{C}$ )


b. Relative Humidity is 90% or less. ( $T_a > 39 \text{ }^\circ\text{C}$ )

c. No condensation

(3) Although abnormal visual problems can be occurred in  $T_{SUR}$  range, the polarizer is not damaged in this range.

(4) 11ms, sine wave, one time for  $\pm X, \pm Y, \pm Z$  axis

(5) 10-300 Hz, Sweep rate 10min, 30min for X,Y,Z axis



**Fig. Temperature and Relative humidity range**

## 1.2 LED Bar Unit Absolute Maximum Ratings

**Samsung Secret**

Item	Symbol	Max.	Unit	Note
Operating Temperature Range	$T_{op}$	-20~+70	°C	
Storage temperature Range	$T_{STG}$	-30~+70	°C	
Junction Temperature	$T_j$	110	°C	LED package
Forward Current	$I_f$	200	mA	140mA@ / String
Forward Voltage	$V_f$	148	V	43 LEDs / @140mA @ $T_j$ 25°C
Thermal Resistance, Junction to Solder	$R_{th,JS}$	40K/W	K/W	LED package

## 2. Optical Characteristics

Samsung Secret

The optical characteristics should be measured in a dark room or equivalent.

Measuring equipment : TOPCON RD-80S, TOPCON SR-3, ELDIM EZ-Contrast

(Ta = 25 ± 2°C, VDD=12V, fv= 120Hz, f<sub>DCLK</sub> = 297.0MHz, LED Current = 140mA)

Item	Symbol	Condition	Min.	Typ.	Max.	Unit	Note
Contrast Ratio (Center of screen)	C/R		3000	5000	-		(1) SR-3
Response Time	G-to-G	Tg	-	8	-	msec	(3) RD-80S
Luminance of White (Center of screen)	Y <sub>L</sub>		330	400	-	cd/m <sup>2</sup>	(4) SR-3
Color Chromaticity (CIE 1931)	Red	Rx	Normal q <sub>L,R</sub> = 0 q <sub>U,D</sub> = 0  Viewing Angle	0.643	TYP. -0.03	TYP. +0.03	(5),(6) SR-3
		Ry		0.333			
	Green	Gx		0.304			
		Gy		0.614			
	Blue	Bx		0.153			
		By		0.054			
	White	Wx		0.280			
		Wy		0.290			
Color Gamut	-		-	72	-	%	(5) SR-3
Color Temperature	-		-	10,000	-	K	
Viewing Angle	Hor.	q <sub>L</sub>	C/R ≥ 10	75	89	-	Degree (6) EZ-Contrast
		q <sub>R</sub>		75	89	-	
	Ver.	q <sub>U</sub>		75	89	-	
		q <sub>D</sub>		75	89	-	
White Brightness Uniformity (9 Points)	B <sub>uni</sub>		-	-	25	%	(2) SR-3


### - Test Equipment Setup

The measurement should be executed in a stable, windless and dark room between 40min and 60min after lighting the back light at the given temperature for stabilization of the back light. This should be measured in the center of screen.


Environment condition : Ta = 25 ± 2 °C

MODEL	LTA550HJ12	Doc. No	06-000-S-20110113	Page	6/26
-------	------------	---------	-------------------	------	------

Photo detector	Field
SR-3	2°
RD-80S	1°



- Definition of test point



Note (1) Definition of Contrast Ratio (C/R)

: Ratio of gray max (Gmax) & gray min (Gmin) at the center point ⑤ of the panel

$$C/R = \frac{G_{\max}}{G_{\min}}$$

Gmax : Luminance with all pixels white

Gmin : Luminance with all pixels black


Note (2) Definition of 9 points brightness uniformity (Test pattern : Full White )

$$B_{uni} = 100 * \frac{(B_{max} - B_{min})}{B_{max}}$$

Bmax : Maximum brightness

Bmin : Minimum brightness

Note (3) Definition of Response time : Sum of Tr, Tf




Note (4) Definition of Luminance of White : Luminance of white at center point ⑤

Note (5) Definition of Color Chromaticity (CIE 1931)

Color coordinate of Red, Green, Blue & White at center point ⑤

Note (6) Definition of Viewing Angle

: Viewing angle range (C/R  $\geq 10$ )





### 3. Electrical Characteristics

#### 3.1 TFT LCD Module

The connector for display data & timing signal should be connected.

$T_a = 25^\circ\text{C} \pm 2^\circ\text{C}$

Item	Symbol	Min.	Typ.	Max.	Unit	Note
Voltage of Power Supply	$V_{DD}$	10.8	12.0	13.2	V	(1)
Current of Power Supply	(a) Black	-	700	-	mA	(2),(3)
	(b) White	-	700	-	mA	
	(c) H-Stripe	-	1300	1600	mA	
Vsync Frequency	$f_V$	95.0	120.0	125.0	Hz	
Hsync Frequency	$f_H$	120.0	135.0	140.0	kHz	
Main Frequency	$f_{DCLK}$	260.0	297.0	305.0	MHz	
Rush Current	$I_{RUSH}$	-	-	7	A	(4)

- Note (1) The ripple voltage should be controlled under 10% of  $V_{DD}$ .  
 (2)  $f_V=120\text{Hz}$ ,  $f_{DCLK} = 297.0\text{MHz}$ ,  $V_{DD} = 12.0\text{V}$ , DC Current.  
 (3) Power dissipation check pattern (LCD Module only)

a) Black Pattern




b) White Pattern



c) H-Stripe



#### (4) Measurement Conditions




Rush Current  $I_{RUSH}$  can be measured when  $T_{RUSH}$  is  $470 \mu\text{s}$ .

### 3.2 Back Light Unit

The back light unit contains Edge type White LEDs (Light Emitting Diode)

Ta=25 ± 2°C



Item	Symbol	Min.	Typ.	Max.	Unit	Note
Operating Life Time	Hr	-	43,000	-	Hour	(1),(2)

Note (1) It is defined as the time to take until the brightness reduces to 50% of its original value. [Operating condition : Ta = 25±2°C, For LED Package only. ]

(2) Test Condition : Tj 80°C, 140mA, 1,000Hr

### 3.2 LED Bar Unit

Item	Symbol	Min.	Typ.	Max.	Unit	Note
Forward Voltage	Vf	132	140	148	V	@140mA/String@Tj=25°C
Variation of Vf	ΔVf	-	-	5	V	4-String@1BLU

## 4. Input Terminal Pin Assignment

**Samsung Secret**

### 4.1.1 Input Signal & Power

Connector : FI-RE41S-HF (JAE/UJU)

Pin	Description		Pin	Symbol	Description
1	Vdd(12V)		21	ODD LVDS SIGNAL	Rx1[3]P
2	Vdd(12V)		22		Rx1[4]N
3	Vdd(12V)		23		Rx1[4]P
4	Vdd(12V)		24		GND
5	Vdd(12V)		25		Rx3[0]N
6	No Connection		26		Rx3[0]P
7	GND		27		Rx3[1]N
8	GND		28		Rx3[1]P
9	GND		29		Rx3[2]N
10	ODD LVDS SIGNAL	Rx1[0]N	30		Rx3[2]P
11		Rx1[0]P	31		GND
12		Rx1[1]N	32		Rx3CLK-
13		Rx1[1]P	33		Rx3CLK+
14		Rx1[2]N	34		GND
15		Rx1[2]P	35		Rx3[3]N
16		GND	36		Rx3[3]P
17		Rx1CLK-	37		Rx3[4]N
18		Rx1CLK+	38		Rx3[4]P
19		GND	39		GND
20		Rx1[3]N	40		No Connection
		41	No Connection		

Note) No Connection: This PINS are only used for SAMSUNG internal using.

4.1.2 Input Signal & Power

Connector : FI-RE51S-HF (JAE/UJU)

Pin	Description	Pin	Description	
1	Vdd(12V)	26	EVEN LVDS SIGNAL	Rx4[0]P
2	Vdd(12V)	27		Rx4[1]N
3	Vdd(12V)	28		Rx4[1]P
4	Vdd(12V)	29		Rx4[2]N
5	Vdd(12V)	30		Rx4[2]P
6	No Connection	31		GND
7	GND	32		Rx4CLK-
8	GND	33		Rx4CLK+
9	GND	34		GND
10	Rx2[0]N	35		Rx4[3]N
11	Rx2[0]P	36	Rx4[3]P	
12	Rx2[1]N	37	Rx4[4]N	
13	Rx2[1]P	38	Rx4[4]P	
14	Rx2[2]N	39	GND	
15	Rx2[2]P	40	No Connection	
16	GND	41	No Connection	
17	Rx2CLK-	42	No Connection	
18	Rx2CLK+	43	No Connection	
19	GND	44	No Connection	
20	Rx2[3]N	45	LVDS Option * Note(1)	
21	Rx2[3]P	46	No Connection	
22	Rx2[4]N	47	No Connection	
23	Rx2[4]P	48	No Connection	
24	GND	49	No Connection	
25	Rx4[0]N	50	No Connection	
		51	No Connection	

NOTE ) No connection : This Pins are only used for SAMSUNG internal using

Note) Pin number starts from Right side





Fig. Connector diagram

- a. All GND pins should be connected together and also be connected to the LCD's metal chassis.
- b. All power input pins should be connected together.
- c. All NC pins should be separated from other signal or power.

Note(1) LVDS OPTION : If this PIN HIGH ( 3.3V ) → Normal LVDS format  
 LOW ( GND ) → JEIDA LVDS format

SEQUENCE : On = VDD(T1) → LVDS Option → Interface Signal(T2)  
 OFF = Interface Signal(T3) → LVDS Option → VDD



#### 4.2 Extended LED Cable Connector Input Pin Configuration

Connector : Yeon-Ho, SMH200-07

Pin No.	Pin Configuration (FUNCTION)	
	Symbol	Remark
1	LED+	DC Voltage output for LED bar
2	LED4-	DC Current return from LED bar
3	LED3-	DC Current return from LED bar
4	NC	No Connection
5	LED+	DC Voltage output for LED bar
6	LED2-	DC Current return from LED bar
7	LED1-	DC Current return from LED bar

### 4.3 LVDS Interface

- LVDS Receiver : Tcon (merged)
- Data Format (JEIDA & Normal)

**Samsung Secret**

	LVDS pin	JEIDA -DATA	Normal -DATA
TxOUT/RxIN0	TxIN/RxOUT0	R4	R0
	TxIN/RxOUT1	R5	R1
	TxIN/RxOUT2	R6	R2
	TxIN/RxOUT3	R7	R3
	TxIN/RxOUT4	R8	R4
	TxIN/RxOUT6	R9	R5
	TxIN/RxOUT7	G4	G0
TxOUT/RxIN1	TxIN/RxOUT8	G5	G1
	TxIN/RxOUT9	G6	G2
	TxIN/RxOUT12	G7	G3
	TxIN/RxOUT13	G8	G4
	TxIN/RxOUT14	G9	G5
	TxIN/RxOUT15	B4	B0
	TxIN/RxOUT18	B5	B1
TxOUT/RxIN2	TxIN/RxOUT19	B6	B2
	TxIN/RxOUT20	B7	B3
	TxIN/RxOUT21	B8	B4
	TxIN/RxOUT22	B9	B5
	TxIN/RxOUT24	HSYNC	HSYNC
	TxIN/RxOUT25	VSYNC	VSYNC
	TxIN/RxOUT26	DEN	DEN
TxOUT/RxIN3	TxIN/RxOUT27	R2	R6
	TxIN/RxOUT5	R3	R7
	TxIN/RxOUT10	G2	G6
	TxIN/RxOUT11	G3	G7
	TxIN/RxOUT16	B2	B6
	TxIN/RxOUT17	B3	B7
	TxIN/RxOUT23	RESERVED	RESERVED
TxOUT/RxIN4	TxIN/RxOUT28	R0	R8
	TxIN/RxOUT29	R1	R9
	TxIN/RxOUT30	G0	G8
	TxIN/RxOUT31	G1	G9
	TxIN/RxOUT32	B0	B8
	TxIN/RxOUT33	B1	B9
	TxIN/RxOUT34	RESERVED	RESERVED

### 4.4 Input Signals, Basic Display Colors and Gray Scale of Each Color

COLOR	DISPLAY (8bit)	DATA SIGNAL																												GRAY SCALE LEVEL
		RED									GREEN									BLUE										
		R0	R1	R2	R3	R4	R5	R6	R7	R8	R9	G0	G1	G2	G3	G4	G5	G6	G7	G8	G9	B0	B1	B2	B3	B4	B5	B6	B7	
BASIC COLOR	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	-
	BLUE	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	-
	GREEN	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	-
	CYAN	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	-
	RED	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	-
	MAGENTA	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	-
	YELLOW	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	-
	WHITE	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	-
GRAY SCALE OF RED	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R0	
	DARK ↑	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1	
		0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R2	
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	R3~R1020
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	
	↓ LIGHT	1	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1021	
		0	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1022	
	RED	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1023	
GRAY SCALE OF GREEN	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G0	
	DARK ↑	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G1	
		0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G2	
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	G3~G1020	
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:		:
	↓ LIGHT	0	0	0	0	0	0	0	0	0	0	1	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	G1021	
		0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	G1022	
GREEN	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	G1023		
GRAY SCALE OF BLUE	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	B0	
	DARK ↑	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	B1	
		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	B2	
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	B3~B1020	
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:		:
	↓ LIGHT	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	1	1	1	1	1	B1021	
		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	B1022	
BLUE	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	B1023		

Note) Definition of Gray :

Rn : Red Gray, Gn : Green Gray, Bn : Blue Gray (n = Gray level)

Input Signal : 0 = Low level voltage, 1 = High level voltage



## 5. Interface Timing


### 5.1 Timing Parameters ( DE mode )

SIGNAL	ITEM	SYMBOL	MIN.	TYP.	MAX.	Unit	NOTE
Clock	Frequency	$1/T_C$	260.0	297.0	305.0	MHz	-
Hsync		$F_H$	120.0	135.0	140.0	KHz	-
Vsync		$F_V$	95.0	120.0	125.0	Hz	-
Vertical Display Term	Active Display Period	$T_{VD}$	-	1080	-	Lines	-
	Vertical Total	$T_V$	1092	1125	1380	Lines	-
Horizontal Display Term	Active Display Period	$T_{HD}$	-	1920	-	Clocks	-
	Horizontal Total	$T_H$	2090	2200	2350	clocks	-

Note) This product is DE mode. But the Hsync & Vsync signal must be inputted


- (1) Test Point : TTL control signal and CLK at LVDS Tx input terminal in system
- (2) Internal VDD = 3.3V

5.2 Timing diagrams of interface signal ( DE mode )



### 5.3 Power ON/OFF Sequence


To prevent a latch-up or DC operation of the LCD Module, the power on/off sequence should be as the diagram below.



- T1 :  $V_{DD}$  rising time from 10% to 90%
- T2 : The time from  $V_{DD}$  to valid data at power ON.
- T3 : The time from valid data off to  $V_{DD}$  off at power Off.
- T4 :  $V_{DD}$  off time for Windows restart
- T5 : The time from valid data to B/L enable at power ON.
- T6 : The time from valid data off to B/L disable at power Off.

- The supply voltage of the external system for the Module input should be the same as the definition of  $V_{DD}$ .
- Apply the lamp voltage within the LCD operation range. When the back light turns on before the LCD operation or the LCD turns off before the back light turns off, the display may momentarily show abnormal screen.
- In case of  $V_{DD} = \text{off level}$ , please keep the level of input signals low or keep a high impedance.
- T4 should be measured after the Module has been fully discharged between power off and on period.
- Interface signal should not be kept at high impedance when the power is on.
- In Case T5 is less than 1000msec and T6 is less than 100msec, Garbage Display can be seen. (It is not related to electrical function issue, Just for recommendation to prevent Garbage Display )


# 6. Outline Dimension (Front View)



PRELIMINARY

GENERAL TOLERANCE				REV	DATE	DESCRIPTION OF REVISION			REASON	CHGD BY
STEP	LEVEL 1	LEVEL 2	LEVEL 3	UNIT	mm	DRAWN BY	DES'D BY	CHKD BY	APP'D BY	MODEL NAME
1 - X - 4	±0.15	±0.1	±0.2	SCALE	1 / 1	HYJU				LTAS50HJ12-T11
4 - X - 16	±0.10	±0.15	±0.3	TOLERANCE		WJB				PART/SHEET NAME
16 - X - 64	±0.12	±0.25	±0.5							OUTLINE DIM(FRONT)
64 - X - 256	±0.25	±0.4	±0.8							SHEET 1 / 3
SAMSUNG ELECTRONICS										VER. 011

# 6. Outline Dimension (Rear View)




## 7. PACKING

### 7.1 CARTON (Internal Package)

(1) Packing Form

Corrugated fiberboard box and corrugated cardboard as shock absorber

(2) Packing Method




### 7.2 Packing Specification

Item	Specification	Remark
LCD Packing	23ea / Box (Packing-Pallet Box)	1. 294 kg / LCD (12.8kg x 23ea) 2. 18 Kg / Packing Box (1ea) 3. Packing Box Material : KLB, AK, CK 4. 0.6Kg/Slica-Gel (6ea)
Pallet	1Box / Pallet	1.Pallet weight = 8.8kg 2.Pallet Material : HDPE
Packing Direction	Vertical	
Total Pallet Size	H x V x height	1475mm(H) x 1150mm(V) x 995mm(height)
Total Pallet Weight	321.8 kg	Module (294 kg) + Packing BOX(18kg) + Pallet(8.8kg) + Slica-Gel(0.6Kg)


## 8. MARKING & OTHERS

A nameplate bearing followed by is affixed to a shipped product at the specified location on each product.


- (1) Part number : LTA550HJ12
- (2) Revision: Three letters
- (3) Lot number : X X X X XXX XX X



### (4) Nameplate Indication



### (5) Packing box attach



### (6) Others

- 1. After service part

Lamps cannot be replaced because of the narrow bezel structure.

MODEL	LTA550HJ12	Doc. No	06-000-S-20110113	Page	23/26
-------	------------	---------	-------------------	------	-------

## 9. General Precautions

### 9.1 Handling

- (a) When the Module is assembled, it should be attached to the system firmly using all mounting holes. Be careful not to twist and bend the Module.
- (b) Because the inverter use high voltage, it should be disconnected from power before it is assembled or disassembled.
- (c) Refrain from strong mechanical shock and / or any force to the Module.  
In addition to damage, this may cause improper operation or damage to the Module and CCFT back light.
- (d) Note that polarizers are very fragile and could be damage easily.  
Do not press or scratch the surface harder than a HB pencil lead.
- (e) Wipe off water droplets or oil immediately. If you leave the droplets for a long time, staining or discoloration may occur.
- (f) If the surface of the polarizer is dirty, clean it using absorbent cotton or soft cloth.
- (g) Desirable cleaners are water, IPA(Isopropyl Alcohol) or Hexane.  
Do not use Ketone type materials(ex. Acetone), Ethyl alcohol, Toluene, Ethyl acid or Methyl chloride. It might permanent damage to the polarizer due to chemical reaction.
- (h) If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth . In case of contact with hands, legs or clothes, it must be washed away with soap thoroughly.
- (i) Protect the module from Electrostatic discharge. Otherwise the ASIC IC or semiconductor would be damaged.
- (j) Use finger-stalls with soft gloves in order to keep display clean during the incoming inspection and assembly process.
- (k) Do not disassemble the Module.
- (l) Do not disassemble shield case of inverter & LVDS board
- (m) Do not connect N.C pins. (Samsung internal use only)
- (n) Protection film for polarizer on the Module should be slowly peeled off just before use so that the electrostatic charge can be minimized. Must put on antistatic glove while handling a module
- (o) Pins of I/F connector should not be touched directly with bare hands.



## 9.2 Storage

**Samsung Secret**

- (a) Do not leave the Module in high temperature, and high humidity for a long time. It is highly recommended to store the Module with temperature from 0 to 35 °C and relative humidity of less than 70%.
- (b) Do not store the TFT-LCD Module in direct sunlight.
- (c) The Module should be stored in a dark place. It is prohibited to apply sunlight or fluorescent light in storing.
- (d) Storage condition of the Carton as below.

Item	Unit	Min.	Max.
Storage Temperature	(°C)	10	40
Storage Humidity	(%rH)	35	75
Storage Life	6 Months		
Storage Condition	<ul style="list-style-type: none"> <li>- . Prohibit direct sunlight</li> <li>- . Ventilation in storehouse and Control changing temperature is within limits of environment</li> <li>- . Put it on pallet, don't put it on floor, and store them with removing form wall.</li> <li>- . Don't wet Out-Box and avoid rain.</li> <li>- . Without condensation.</li> <li>- . Etc. Avoid harmful Condition.</li> </ul>		
Long-term Storage Process	More than 3months Storage or Low temp. Delivery/under5°C Storage, → On the 20°C 50%rH Condition, More than 24hr release.		

## 9.3 Operation

- (a) Do not connect or disconnect the Module in the "Power On" condition.
- (b) Power supply should always be turned on/off by the "Power on/off sequence"
- (c) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference should be done by system manufacturers. Grounding and shielding methods may be important to minimize the interference.
- (d) The cable between the back light connector and its inverter power supply should be connected directly with a minimized length. A longer cable between the back light and the inverter may cause lower luminance of LED and may require higher startup voltage(Vs).

## 9.4 Operation Condition Guide

- (a) The LCD product should be operated under normal conditions.  
Normal condition is defined as below;
- Temperature :  $20 \pm 15^{\circ}\text{C}$
  - Humidity :  $55 \pm 20\%$
  - Display pattern : continually changing pattern (Not stationary)
- (b) If the product will be used in extreme conditions such as high temperature, humidity, display patterns or operation time etc., It is strongly recommended to contact SEC for Application engineering advice. Otherwise, its reliability and function may not be guaranteed. Extreme conditions are commonly found at Airports, Transit Stations, Banks, Stock market, and Controlling systems.

## 9.5 Others

- (a) Ultra-violet ray filter is necessary for outdoor operation.
- (b) Avoid condensation of water. It may result in improper operation or disconnection of electrode.
- (c) Do not exceed the absolute maximum rating value. ( supply voltage variation, input voltage variation, variation in part contents and environmental temperature, and so on)  
Otherwise the Module may be damaged.
- (d) If the Module keeps displaying the same pattern for a long period of time, the image may be "sticked" to the screen.  
To avoid image sticking, it is recommended to use a screen saver.
- (e) This Module has its circuitry PCB's on the rear side and should be handled carefully in order not to be stressed.
- (f) Please contact SEC in advance when you display the same pattern for a long time.