



Photocoupler
Product Data Sheet
LTV-155E

Spec No. :DS70-2013-0016
Effective Date: 09/22/2022
Revision: D

LITE-ON DCC
RELEASE

BNS-OD-FC001/A4

Photocoupler LTV-155E series

1.0 Amp Output Current IGBT Gate Drive Optocoupler with Rail-to-Rail Output Voltage, High CMR.

1. DESCRIPTION

The LTV-155E optocoupler is ideally suited for driving power IGBTs and MOSFETs used in motor control inverter applications and inverters in power supply system. It contains an AlGaAs LED optically coupled to an integrated circuit with a power output stage. The 1.0A peak output current is capable of directly driving most IGBTs with ratings up to 1200 V/50 A. For IGBTs with higher ratings, the LTV-155E series can be used to drive a discrete power stage which drives the IGBT gate.

The Optocoupler operational parameters are guaranteed over the temperature range from -40°C ~ +105°C.

1.1 Features


- 1.0 A maximum peak output current
 - 0.8 A minimum peak output current
 - Rail-to-rail output voltage
 - 200 ns maximum propagation delay
 - 100 ns maximum propagation delay difference
 - 35 kV/us minimum Common Mode Rejection (CMR) at $V_{CM} = 1500$ V
 - $I_{CC} = 3.0$ mA maximum supply current
 - Wide operating range: 10 to 30 Volts (V_{CC})
 - Guaranteed performance over temperature $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$.
 - MSL Level 1
 - Safety approval:
 - UL/ cUL Recognized 3750 $V_{RMS}/1$ min
 - IEC/EN/DIN EN 60747-5-5 $V_{IORM} = 565$ V_{peak}

1.2 Applications

- Plasma Display Panel .
 - IGBT/MOSFET gate drive
 - Uninterruptible power supply (UPS)
 - Industrial Inverter
 - Induction heating

Functional Diagram

Pin No. and Internal connection diagram




Truth Table

LED	High side	Low side	V_o
OFF	OFF	ON	Low
ON	ON	OFF	High

Note: A $0.1\mu\text{F}$ bypass capacitor must be connected between Pin 4 and 6

Photocoupler LTV-155E series

2. PACKAGE DIMENSIONS



Part No : LTV-155E

Notes :


1. The first digit is year date code, second and third digit are work week
2. Factory identification mark (W :China-CZ)
3. "V" for VDE option

Dimensions are all in Millimeters.


Photocoupler LTV-155E series

3. TAPING DIMENSIONS

3.1 LTV-155E



3.1 LTV-155E-TP



Description	Symbol	Dimension in mm (inch)
Tape wide	W	12±0.3 (0.47)
Pitch of sprocket holes	P ₀	4±0.1 (0.15)
Distance of compartment	F	5.5±0.1 (0.217)
	P ₂	2±0.1 (0.079)
Distance of compartment to compartment	P ₁	8±0.1 (0.315)

Quantities Per Reel

Package Type	LTV-155E series
Quantities (pcs)	3000

Photocoupler
LTV-155E series

4. RATING AND CHARACTERISTICS

4.1 Absolute Maximum Ratings at Ta=25°C

Parameter	Symbol	Min	Max	Unit	Note
Storage Temperature	T _{stg}	-55	+125	°C	
Operating Temperature	T _{opr}	-40	+105	°C	
Output IC Junction Temperature	T _J		125	°C	
Total Output Supply Voltage	(V _{CC} -V _{EE})	0	35	V	
Average Forward Input Current	I _F		25	mA	
Reverse Input Voltage	V _R		5	V	
Peak Transient Input Current	I _{F(TRAN)}		1	A	1
"High" Peak Output Current	I _{OH(Peak)}		1.0	A	2
"Low" Peak Output Current	I _{OL(Peak)}		1.0	A	2
Input Current (Rise/Fall Time)	t _{r(IN)} / t _{f(IN)}		500	ns	3
Output Voltage	V _{O(Peak)}	-0.5	V _{cc}	V	
Power Dissipation	P _I		40	mW	
Output Power Dissipation	P _O		250	mW	
Total Power Dissipation	P _T		295	mW	
Lead Solder Temperature	T _{sol}		260	°C	

Note: Ambient temperature = 25°C, unless otherwise specified. Stresses exceeding the absolute maximum ratings can cause permanent damage to the device. Exposure to absolute maximum ratings for long periods of time can adversely affect reliability.

Note: Note: A ceramic capacitor (0.1 µF) should be connected between pin 6 and pin 4 to stabilize the operation of a high gain linear amplifier. Otherwise, this Photocoupler may not switch properly. The bypass capacitor should be placed within 1 cm of each pin.

Note 1: Pulse width (PW) ≤ 1 µs, 300 pps

Note 2: Exponential waveform. Pulse width ≤ 0.3 µs, f ≤ 15 kHz

Note 3: The rise and fall times of the input on-current should be less than 500 ns

4.2 Recommended Operating Conditions

Parameter	Symbol	Min.	Max.	Unit
Operating Temperature	T _A	-30	105	°C
Supplier Voltage	V _{CC}	10	30	V
Input Current (ON)	I _{F(ON)}	7	16	mA
Input Voltage (OFF)	V _{F(OFF)}	-3.0	0.8	V

Photocoupler LTV-155E series

4.3 Electrical optical characteristics at $T_A=25^\circ\text{C}$

	Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition	Figure	Note
Input	Input Forward Voltage	V_F	1.2	1.37	1.8	V	$I_F = 10\text{mA}$	13	—
	Input Forward Voltage Temperature Coefficient	$\Delta V_F / \Delta T$	—	-1.237	—	$\text{mV}/^\circ\text{C}$	$I_F = 10\text{mA}$	—	—
	Input Reverse Voltage	BV_R	5	—	—	V	$I_R = 10\mu\text{A}$	—	—
	Input Threshold Current (Low to High)	I_{FLH}	—	1.9	5	mA	$V_O > 5\text{V}, I_O = 0\text{A}$	6, 7 ,18	—
	Input Threshold Voltage (High to Low)	V_{FHL}	0.8	—	—	V	$V_O < 5\text{V}, I_O = 0\text{A}$	—	—
	Input Capacitance	C_{IN}	—	33	—	pF	$f = 1\text{ MHz}, V_F = 0\text{ V}$	—	—
Output	High Level Supply Current	I_{CCH}	—	1.9	3.0	mA	Output Open, $I_F = 7\text{ to }16\text{ mA}$	4, 5	—
	Low Level Supply Current	I_{CCL}	—	2.1	3.0	mA	Output Open, $V_F = -3\text{ to }+0.8\text{ V}$		—
	High level output current	I_{OH}	—	—	-0.3	A	$V_O = (V_{CC} - 1.5\text{ V})$	16	1
			—	—	-0.8		$V_O = (V_{CC} - 3\text{ V})$		2
	Low level output current	I_{OL}	0.3	—	—	A	$V_O = (V_{EE} + 1.5\text{ V})$	17	1
			0.8	—	—		$V_O = (V_{EE} + 3\text{ V})$		2
	High level output voltage	V_{OH}	$V_{CC} - 0.6$	$V_{CC} - 0.35$	—	V	$I_F = 10\text{mA},$ $I_O = -100\text{mA}$	1, 2, 14	—
	Low level output voltage	V_{OL}	—	$V_{EE} + 0.25$	$V_{EE} + 0.4$	V	$I_F = 0\text{mA}, I_O = 100\text{mA}$	3, 15	—
	UVLO Threshold	V_{UVLO+}	—	7.8	—	V	$V_O > 5\text{V}, I_F = 10\text{ mA}$	19	—
		V_{UVLO-}	—	6.7	—	V	$V_O < 5\text{V}, I_F = 10\text{ mA}$		—
	UVLO Hysteresis	$UVLO_{HYS}$	—	1.1	—	V	—	—	—

All Typical values at $T_A = 25^\circ\text{C}$ and $V_{CC} - V_{EE} = 30\text{ V}$, unless otherwise specified; all minimum and maximum specifications are at recommended operating condition. (Refer to 4.2)

Note 1: Maximum pulse width = 50 μs .

Note 2: Maximum pulse width = 10 μs .

Photocoupler
LTV-155E series

5. SWITCHING SPECIFICATION

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition	Figure	Note
Propagation Delay Time to High Output Level	t_{PHL}	50	120	200	ns	$R_g = 47\Omega$, $C_g = 3nF$, $f = 10 \text{ kHz}$, Duty Cycle = 50% $I_F = 7 \text{ to } 16 \text{ mA}$, $V_{CC} = 15 \text{ to } 30V$ $V_{EE} = \text{ground}$	8, 9, 10, 11, 12, 20	—
Propagation Delay Time to Low Output Level	t_{PLH}	50	110	200				—
Pulse Width Distortion	PWD	—	10	70				—
Propagation delay difference between any two parts or channels	PDD	100	—	100				3
Output Rise Time (20 to 80%)	Tr	—	35	—				—
Output Fall Time (80 to 20%)	Tf	—	35	—				—
Common mode transient immunity at high level output	$ CMH $	35	50	—	kV/μs	$T_A = 25^\circ C$, $I_F = 10 \text{ to } 16 \text{ mA}$, $V_{CM} = 1500 V$, $V_{CC} = 30 V$	21	1
Common mode transient immunity at low level output	$ CML $	35	50	—	kV/μs	$T_A = 25^\circ C$, $V_F = 0 V$, $V_{CM} = 1500 V$, $V_{CC} = 30 V$		2

All Typical values at $T_A = 25^\circ C$ and $V_{CC} - V_{EE} = 30 V$, unless otherwise specified; all minimum and maximum specifications are at recommended operating condition. (Refer to 4.2)

Note 1: CM_H is the maximum rate of rise of the common mode voltage that can be sustained with the output voltage in the logic high state ($V_O > 15 V$).

Note 2: CM_L is the maximum rate of fall of the common mode voltage that can be sustained with the output voltage in the logic low state ($V_O < 1 V$).

Note 3: The difference between t_{PHL} and t_{PLH} between any two parts series parts under same test conditions.

Photocoupler
LTV-155E series

6. ISOLATION CHARACTERISTICS

Parameter	Test Conditions	Symbol	Min.	Typ	Max.	Unit	Note
Withstand Insulation Test Voltage	RH ≤ 40-60%, t = 1min, T _A = 25°C	V _{Iso}	3750	—	—	V	1, 2
Input-Output Resistance	V _{I-O} = 500V DC	R _{I-O}	—	10 ¹²	—	Ω	1
Input-Output Capacitance	f = 1MHz, T _A = 25°C	C _{I-O}	—	0.92	—	pF	1

All Typical values at T_A = 25°C unless otherwise specified. All minimum and maximum specifications are at recommended operating condition. (Refer to 4.2)

Note 1: Device is considered a two terminal device: pins 1 and 3 are shorted together and pins 4, 5 and 6 are shorted together.

Note 2: According to UL1577, each photocoupler is tested by applying an insulation test voltage 4500V_{RMS} for one second (leakage current less than 10uA). This test is performed before the 100% production test for partial discharge

Photocoupler LTV-155E series

7. TYPICAL PERFORMANCE CURVES & TEST CIRCUITS




Figure 1: High output rail voltage vs. Temperature




Figure 2: V_{OH} vs. Temperature




Figure 3: V_{OL} vs. Temperature




Figure 4: I_{CC} vs. Temperature




Figure 5: I_{CC} vs. V_{CC}




Figure 6: I_{FLH} hysteresis



LITEON®
OPTOELECTRONICS

Data Sheet

Photocoupler LTV-155E series





Figure 7: I_{FLH} vs. Temperature

Figure 8: Propagation delays vs. V_{CC}




Figure 9: Propagation delays vs. I_F




Figure 10: Propagation delays vs. Temperature




Figure 11: Propagation delays vs. R_g




Figure 12: Propagation delays vs. C_g


Photocoupler
LTV-155E series


Figure 13: Input current vs. Forward voltage








 Figure 14 : V_{OH} Test Circuit

 Figure 15 : V_{OL} Test Circuit

 Figure 16 : I_{OH} Test Circuit

 Figure 17 : I_{OL} Test Circuit

 Figure 18 : I_{FLH} Test Circuit


Figure 19 : UVLO Test Circuit

Photocoupler LTV-155E series





Figure 20 : tr, tf, t_{PLH} and t_{PHL} Test Circuit and Waveforms





Figure 21 : CMR Test Circuit and Waveforms


Photocoupler LTV-155E series

8. TEMPERATURE PROFILE OF SOLDERING

8.1 IR Reflow soldering (JEDEC-STD-020C compliant)

One time soldering reflow is recommended within the condition of temperature and time profile shown below. Do not solder more than three times.

Profile item	Conditions
Preheat	
- Temperature Min (T_{Smin})	150°C
- Temperature Max (T_{Smax})	200°C
- Time (min to max) (t_s)	90±30 sec
Soldering zone	
- Temperature (T_L)	217°C
- Time (t_L)	60 sec
Peak Temperature (T_P)	260°C
Ramp-up rate	3°C / sec max.
Ramp-down rate	3~6°C / sec



Photocoupler LTV-155E series

8.2 Wave soldering (JEDEC22A111 compliant)


One time soldering is recommended within the condition of temperature.

Temperature: 260+0/-5°C

Time: 10 sec.

Preheat temperature: 25 to 140°C

Preheat time: 30 to 80 sec.



8.3 Hand soldering by soldering iron

Allow single lead soldering in every single process. One time soldering is recommended.

Temperature: 380+0/-5°C

Time: 3 sec max.

Photocoupler
LTV-155E series

9. NAMING RULE

Part Number Options	
	LTV-155E
	LTV-155E-TP
	LTV155E-V
	LTV155ETP-V
Definition of Suffix	Remark
"155E"	LiteOn model name
"no suffix"	Pin 1 location at upper right of the tape
"TP"	Pin 1 location at lower left of the tape
"V"	VDE approved option

10. Notes:

- LiteOn is continually improving the quality, reliability, function or design and LiteOn reserves the right to make changes without further notices.
- The products shown in this publication are designed for the general use in electronic applications such as office automation equipment, communications devices, audio/visual equipment, electrical application and instrumentation.
- For equipment/devices where high reliability or safety is required, such as space applications, nuclear power control equipment, medical equipment, etc, please contact our sales representatives.
- When requiring a device for any "specific" application, please contact our sales in advice.
- If there are any questions about the contents of this publication, please contact us at your convenience.
- The contents described herein are subject to change without prior notice.
- Immerge unit's body in solder paste is not recommended.