

AU OPTRONICS CORPORATION

Product Specification

19.0" SXGA Color TFT-LCD Module

Model Name: M190EN04 V.3

Approved by	Prepared by
<i>CC Chiu</i>	<i>Winni Chen</i>

DDBU Marketing Division / AU Optronics corporation

Customer	Checked & Approved by

Product Specification

19.0" SXGA Color TFT-LCD Module **Model Name: M190EN04** **V.3**

Preliminary Specifications
 Final Specifications

Note: This Specification is subject to change without notice.

Contents

1.0 Handling Precautions	6
2.0 General Description	7
2.1 Display Characteristics	7
2.2 Optical Characteristics	8
3.0 Functional Block Diagram.....	12
4.0 Absolute Maximum Ratings	13
4.1 TFT LCD Module	13
4.2 Backlight Unit	13
4.3 Absolute Ratings of Environment.....	13
5.0 Electrical characteristics	14
5.1 TFT LCD Module	14
5.1.1 Power Specification	14
5.1.2 Signal Electrical Characteristics	15
5.2 Backlight Unit	16
6.0 Signal Characteristic	17
6.1 Pixel Format Image	17
6.2 The input data format.....	17
6.3 Signal Description.....	18
6.4.1 Timing Characteristics	20
6.4.2 Timing diagram	20
6.5 Power ON/OFF Sequence	21
7.0 Connector & Pin Assignment	22
7.1 TFT LCD Module	22
7.2 Backlight Unit	23
7.3 Signal for Lamp connector	23
8.0 Vibration, Shock, and Drop.....	23
8.1 Vibration & Shock	23
8.2 Drop test.....	24
9.0 Environment.....	24
9.1 Temperature and Humidity	24
9.1.1 Operating Conditions.....	24
9.1.2 Shipping Conditions	24
9.2 Atmospheric Pressure.....	24
9.3 Thermal Shock	24
10.0 Reliability	25
10.1 Failure Criteria	25
10.2 Failure Rate.....	25

10.2.1 Usage 25

10.2.1 Component De-rating 25

10.3 On/OFF Cycle 25

11.0 Safety 26

11.1 Sharp Edge Requirements 26

11.2 Materials 26

11.2.1 Toxicity 26

11.2.2 Flammability 26

11.3 Capacitors 26

12.0 Other requirement 26

12.1 National Test Lab Requirement 26

12.2 Label 26

13.0 Mechanical Characteristics 27

Record of Revision

Version and Date	Page	Old description	New Description	Remark
0.1 2004/08/01	All	First Edition for Customer	All	

1.0 Handling Precautions

- 1) Since front polarizer is easily damaged, pay attention not to scratch it.
- 2) Be sure to turn off power supply when inserting or disconnecting from input connector.
- 3) Wipe off water drop immediately. Long contact with water may cause discoloration or spots.
- 4) When the panel surface is soiled, wipe it with absorbent cotton or other soft cloth.
- 5) Since the panel is made of glass, it may break or crack if dropped or bumped on hard surface.
- 6) Since CMOS LSI is used in this module, take care of static electricity and insure human earth when handling.
- 7) Do not open nor modify the Module Assembly.
- 8) Do not press the reflector sheet at the back of the module to any directions.
- 9) In case if a module has to be put back into the packing container slot after once it was taken out from the container, do not press the center of the CCFL reflector edge. Instead, press at the far ends of the CCFL reflector edge softly. Otherwise the TFT module may be damaged.
- 10) At the insertion or removal of the Signal Interface Connector, be sure not to rotate nor tilt the Interface Connector of the TFT module.
- 11) After installation of the TFT module into an enclosure (Desktop monitor Bezel, for example), do not twist nor bend the TFT Module even momentary. At designing the enclosure, it should be taken into consideration that no bending/twisting forces are applied to the TFT module from outside. Otherwise the TFT module may be damaged.

2.0 General Description

This specification applies to the 19.0 inch Color TFT-LCD Module M190EN04.

The display supports the SXGA (1280(H) x 1024(V) screen format and 262K colors (RGB 6-bits).

All input signals are 2 Channel LVDS interface compatible.

This module does not contain an inverter card for backlight.

2.1 Display Characteristics

The following items are characteristics summary on the table under 25 °C condition:


ITEMS	Unit	SPECIFICATIONS
Screen Diagonal	[mm]	480(19")
Active Area	[mm]	376.32 (H) x 301.056 (V)
Pixels H x V		1280(x3) x 1024
Pixel Pitch	[mm]	0.294 (per one triad) x 0.294
Pixel Arrangement		R.G.B. Vertical Stripe
Display Mode		Normally White
White Luminance (Center)	[cd/m ²]	250 cd/m ² @7mA (Typ)
Contrast Ratio		450 : 1 (Typ)
Optical Response Time	[msec]	16ms (Typ, on/off)
Nominal Input Voltage VDD	[Volt]	+5.0 V
Power Consumption (VDD line + CCFL line)	[Watt]	28W(Typ) (w/o Inverter, All black pattern) (PDD=7.5 W, PCFL=19.6 W @Lamp=7.0mA)
Weight	[Grams]	2700 (Max)
Physical Size	[mm]	396(W) x 324(H) x 18(D) (Typ)
Electrical Interface		R/G/B data, Clock
Support Color		262k colors (RGB 6-bit data)
Surface Treatment		Glare, Hard Coating, 2H
Temperature Range		
Operating	[°C]	0 to +50
Storage (Shipping)	[°C]	-20 to +60

2.2 Optical Characteristics

The optical characteristics are measured under stable conditions at 25°C:

Item	Unit	Conditions	Min.	Typ.	Max.	Note
Viewing Angle	[degree]	Horizontal (Right)	65	70	-	
	[degree]	CR = 10 (Left)	65	70	-	
	[degree]	Vertical (Up)	65	70	-	
	[degree]	CR = 10 (Down)	60	65	-	
		Horizontal (Right)		>80		
		CR = 5 (Left)		>80		
		Vertical (Up)		>80		
		CR = 5 (Down)		>80		
Contrast ratio		Normal Direction	250	450		
Response Time	[msec]	Raising Time	-	4	5	Note 1
	[msec]	Falling Time	-	12	20	Note 1
	[msec]	Raising + Falling	-	16	25	Note 1
Color / Chromaticity Coordinates (CIE)		Red x	0.604	0.634	0.664	
		Red y	0.324	0.354	0.384	
		Green x	0.27	0.3	0.33	
		Green y	0.585	0.615	0.645	
		Blue x	0.108	0.138	0.168	
		Blue y	0.047	0.077	0.107	
Color Coordinates (CIE) White		White x	0.28	0.31	0.34	
		White y	0.30	0.33	0.36	
White Luminance at CCFL 7.0mA (central point)	[cd/m ²]		200	250	-	
Luminance Uniformity	[%]		70	75	-	Note 2
Crosstalk (in75Hz)	[%]				1.5	Note 3
Flicker	dB				-20	Note 4
TC0-03 Compliance						Note 5


Equipment	Pattern Generator, Power Supply, Digital Voltmeter, Luminance meter (PR 880, BM-5A , BM 7 ,CS-1000, & EZContrast*)
Aperture	1° with 100cm VD or 2° with 50cm viewing distance
Test Point	Center (VESA point 9)
Environment	< 1 lux




* EZ Contrast is different measurement tool with very close viewing distance.

Note 1: Definition of Response time

The output signals of photodetector are measured when the input signals are changed from “Black” to “White” (rising time), and from “White” to “Black ”(falling time), respectively. The response time is interval between the 10% and 90% of amplitudes.




Note 2: Brightness uniformity of these 9 points is defined as below



$$\text{Uniformity} = \frac{\text{Minimum Luminance in 9 points (1 - 9)}}{\text{Maximum Luminance in 9 Points (1 - 9)}}$$

Note 3: Crosstalk is defined as below :




Unit: percentage of dimension of display area


$|L_A - L_{A'}| / L_A \times 100\% = 1.5\% \text{ max.}$, L_A and L_B are brightness at location A and B

$|L_B - L_{B'}| / L_B \times 100\% = 1.5\% \text{ max.}$, $L_{A'}$ and $L_{B'}$ are brightness at location A' and B'

Note 4: Test Patern: Subchecker Pattern



Method: Record dBV & DC value with (WESTAR)TRD-100




$$\text{Flicker (dB)} = 20 \log \frac{\text{AC Level(at 30 Hz)}}{\text{DC Level}}$$

Note5: Tuning the brightness and contrast function in OSD let the luminance to 125 cd/m². When tuning the brightness to 125cd/m², the function on OSD should not restrict our V-T curve. In other word, the higher contrast, the range of panel's V-T curve will be more extensive to get the better performance. If it is not possible to achieve the test luminance by this procedure it is suitable to tune contrast higher and brightness lower.

3.0 Functional Block Diagram

The following diagram shows the functional block of the 19.0 inches Color TFT/LCD Module:



JAE FI-XB30SSL-HF15

JST BHSR-02VS-1

Mating Type: FI-X30HL

Mating Type: SM02B-BHSS-1-TB

4.0 Absolute Maximum Ratings

Absolute maximum ratings of the module is as following:

4.1 TFT LCD Module

Item	Symbol	Min	Max	Unit	Conditions
Logic/LCD Drive Voltage	VIN	+4.5	+5.5	[Volt]	Note 1,2

4.2 Backlight Unit

Item	Symbol	Min	Max	Unit	Conditions
CCFL Current	ICFL	-	7.5	[mA] rms	Note 1,2

4.3 Absolute Ratings of Environment


Item	Symbol	Min	Max	Unit	Conditions
Operating Humidity	HOP	8	95	[%RH]	Note 3
Storage Temperature	TST	-20	+60	[°C]	Note 3
Storage Humidity	HST	8	95	[%RH]	Note 3

Note 1: With in Ta (25°C)

Note 2: Permanent damage to the device may occur if exceed maximum values

Note 3: For quality performance, please refer to AUO IIS(Incoming Inspection Standard).

Relative Humidity %



5.0 Electrical characteristics


5.1 TFT LCD Module

5.1.1 Power Specification

Input power specifications are as follows;

Symbol	Parameter	Min	Typ	Max	Units	Condition
VDD	Logic/LCD Drive Voltage	4.5	5	5.5	[Volt]	±10%
IDD	VDD current	-	1500	1900	[mA]	Vin=5V, All Black Pattern, at 75Hz. +30%,for max.
Irush	LCD Inrush Current	-	-	2.5	[A]	Note
PDD	VDD Power	-	7.5	10	[Watt]	Vin=5V, All Black Pattern, at 75Hz. +30%,for max.
VDDrp	Allowable Logic/LCD Drive Ripple Voltage			100	[mV] p-p	
VDDns	Allowable Logic/LCD Drive Ripple Voltage			100	[mV] p-p	

Note: Measurement conditions:



5.1.2 Signal Electrical Characteristics


Input signals shall be low or Hi-Z state when V_{in} is off

It is recommended to refer the specifications of SN75LVDS82DGG (Texas Instruments) in detail.

Each signal characteristics are as follows;

Symbol	Parameter	Min	Typ	Max	Units	Condition
VTH	Differential Input High Threshold	-	-	+100	[mV]	$V_{ICM} = 1.2V$ Note
VTL	Differential Input Low Threshold	-100	-	-	[mV]	$V_{ICM} = 1.2V$ Note
VID	Input Differential Voltage	100	400	600	[mV]	Note
VICM	Differential Input Common Mode Voltage	+1.0	+1.2	+1.35	[V]	$V_{TH}/V_{TL} = \pm 100mV$ Note

Note: LVDS Signal Waveform



5.2 Backlight Unit

Parameter guideline for CCFL Inverter

Symbol	Parameter	Min.	Typ.	Max.	Unit	Condition
ISCFL	CCFL standard current	6.5	7.0	7.5	[mA] rms	(Ta=25°C) Note 1
IRCFL	CCFL operation range	3.0	7.0	7.5	[mA] rms	(Ta=25°C)
FCFL	CCFL Frequency	40	50	80	[KHz]	(Ta=25°C) Note 2
ViCFL (0°C)	CCFL Ignition Voltage (End of the lamp wire connector)	1800	-	-	[Volt] rms	(Ta=0°C) Note 3
ViCF (25°C)	CCFL Ignition Voltage (End of the lamp wire connector)	1500	-	-	[Volt] rms	(Ta=25°C) Note 3
VCFL	CCFL Operation Voltage	-	700 @7.0mA	860 @6.5mA	[Volt] rms	(Ta=25°C) Note 4
PCFL	CCFL Power consumption (for reference)	-	19.6	22	[Watt]	(Ta=25°C) Note 5
LTCFL	CCFL life Time	40,000	50,000	-	[Hour]	(Ta=25°C) Note 6

Note 1: CCFL standard current is measured at 25±2°C..

Note 2: CCFL Frequency should be carefully determined to avoid interference between inverter and TFT LCD

Note 3: ViCFL means Ignition Voltage for both ends of the lamp, and CCFL inverter should be able to give out a power that has a generating capacity of over 1800 voltage. Lamp units need 1800 voltage minimum for ignition

Note 4: CCFL operation voltage is measured at 25±2°C.

Note 5: The variance of CCFL power consumption is ±10%. Calculator value for reference


(ICFL×VCFL×4=PCFL).

Note 6: Definition of life: brightness becomes 50% or less than the minimum luminance value of CCFL..The typical life time of CCFL is on the condition at 7.0mA lamp current.


6.0 Signal Characteristic


6.1 Pixel Format Image

Following figure shows the relationship of the input signals and LCD pixel format.



6.2 The input data format






6.3 Signal Description

The module using one LVDS receiver SN75LVDS82(Texas Instruments) or compatible. LVDS is a differential signal technology for LCD interface and high speed data transfer device. Transmitter shall be SN75LVDS83(negative edge sampling) or compatible. The first LVDS port(RxOxxx) transmits odd pixels while the second LVDS port(RxExxx) transmits even pixels.

PIN #	SIGNAL NAME	DESCRIPTION
1	RxO0-	Negative LVDS differential data input (Odd data)
2	RxO0+	Positive LVDS differential data input (Odd data)
3	RxO1-	Negative LVDS differential data input (Odd data)
4	RxO1+	Positive LVDS differential data input (Odd data)
5	RxO2-	Negative LVDS differential data input (Odd data, H-Sync,V-Sync,DSPTMG)
6	RxO2+	Positive LVDS differential data input (Odd data, H-Sync,V-Sync,DSPTMG)
7	GND	Power Ground
8	RxOC-	Negative LVDS differential clock input (Odd clock)
9	RxOC+	Positive LVDS differential clock input (Odd clock)
10	RxO3-	Negative LVDS differential data input (Odd data)
11	RxO3+	Positive LVDS differential data input (Odd data)
12	RxE0-	Negative LVDS differential data input (Even clock)
13	RxE0+	Positive LVDS differential data input (Even data)
14	GND	Power Ground
15	RxE1-	Positive LVDS differential data input (Even data)

16	RxE1+	Negative LVDS differential data input (Even data)
17	GND	Power Ground
18	RxE2-	Negative LVDS differential data input (Even data)
19	RxE2+	Positive LVDS differential data input (Even data)
20	RxEC-	Negative LVDS differential clock input (Even clock)
21	RxEC+	Positive LVDS differential clock input (Even clock)
22	RxE3-	Negative LVDS differential data input (Even data)
23	RxE3+	Positive LVDS differential data input (Even data)
24	GND	Power Ground
25	NC	-
26	NC	-
27	NC	-
28	POWER	Power
29	POWER	Power
30	POWER	Power

Note1: Start from left side





Note2: Input signals of odd and even clock shall be the same timing.

6.4.1 Timing Characteristics

Basically, interface timings described here is not actual input timing of LCD module but output timing of SN75LVDS82DGG (Texas Instruments) or equivalent. **Note:** Typical value refer to VESA STANDARD


Signal	Item	Symbol	MIN	TYP	MAX	Unit
DTCLK	Freq.	Fdck	50	67.5	70	MHz
DTCLK	Cycle	Tck	14.2	14.8	20	ns
+V-Sync	Frame Rate	1/Tv	56.25	75	77	Hz
+V-Sync	Cycle	Tv	13	13.33	17.78	ms
+V-Sync	Cycle	Tv	1035	1066	2047	lines
+V-Sync	Active level	Tva	3	3		lines
+V-Sync	V-back porch	Tvb	7	38	63	lines
+V-Sync	V-front porch	Tvf	1	1		lines
+DSPTMG	V-Line	m	-	1024	-	lines
+H-Sync	Scan rate	1/Th	-	80.06	-	KHz
+H-Sync	Cycle	Th	800	844	1023	Tck
+H-Sync	Active level	Tha (*1)	4	56		Tck
+H-Sync	Back porch	Thb (*1)	4	124		Tck
+H-Sync	Front porch	Thf	4	24		Tck
+DSPTMG	Display Pixels	n	-	640	-	Tck

6.4.2 Timing diagram



6.5 Power ON/OFF Sequence

Vin power and lamp on/off sequence is as follows. Interface signals are also shown in the chart. Signals from any system shall be Hi-Z state or low level when Vin is off.



Symbol	Values			Unit
	Min	Typ	Max	
T1	0	-	10	[ms]
T2	0.5	40	50	[ms]
T3	300	-	-	[ms]
T4	300	-	-	[ms]
T5	0.5	16	50	[ms]
T6	0.5	-	10	[ms]
T7	1000	-	-	[ms]

7.0 Connector & Pin Assignment

Physical interface is described as for the connector on module.

These connectors are capable of accommodating the following signals and will be following components.

7.1 TFT LCD Module

Connector Name / Designation	Interface Connector / Interface card
Manufacturer	JAE or compatible
Type Part Number	FI-XB30SSL-HF15
Mating Housing Part Number	FI-X30HL

Pin#	Signal Name	Pin#	Signal Name
1	RxO0-	2	RxO0+
3	RxO1-	4	RxO1+
5	RxO2-	6	RxO2+
7	GND	8	RxOC-
9	RxOC+	10	RxO3-
11	RxO3+	12	RxE0-
13	RxE0+	14	GND
15	RxE1-	16	RxE1+
17	GND	18	RxE2-
19	RxE2+	20	RxEC-
21	RxEC+	22	RxE3-
23	RxE3+	24	GND
25	NC	26	NC
27	NC	28	Power
29	Power	30	Power

7.2 Backlight Unit

Connector Name / Designation	Lamp Connector / Backlight lamp
Manufacturer	JST
Type Part Number	BHSR-02VS-1
Mating Type Part Number	SM02B-BHSS-1-TB

7.3 Signal for Lamp connector

	Connector No.	Pin No.	Input	Color	Function
Upper	CN1	1	Hot1	Pink	High Voltage
		2	Cold1	White	Low Voltage
	CN2	1	Hot2	Blue	High Voltage
		2	Cold2	Black	Low Voltage
Lower	CN3	1	Hot1	Pink	High Voltage
		2	Cold1	White	Low Voltage
	CN4	1	Hot2	Blue	High Voltage
		2	Cold2	Black	Low Voltage

8.0 Vibration, Shock, and Drop

8.1 Vibration & Shock

Vibration Test Spec:

- I Frequency: 10 - 200Hz
- I Sweep: 30 Minutes each Axis (X, Y, Z)
- I Acceleration: 1.5G(10~200Hz P- P)
- I Test method:

Acceleration (G)	1.5
Frequency (Hz)	10~200~10
Active time (min)	30

Shock Test Spec:

Acceleration (G) -a	50
Active time -b	20 ms
Wave form	Half-sin
Times	1

- I Direction: $\pm X$, $\pm Y$, $\pm Z$

8.2 Drop test

Package test: The drop height is 60cm.

9.0 Environment

The display module will meet the provision of this specification during operating condition or after storage or shipment condition specified below. Operation at 10% beyond the specified range will not cause physical damage to the unit.

9.1 Temperature and Humidity

9.1.1 Operating Conditions

The display module operates error free, when operated under the following conditions;

Temperature	0 °C to 50 °C
Relative Humidity	8% to 95%
Wet Bulb Temperature	39.0 °C

9.1.2 Shipping Conditions

The display module operates error free, after the following conditions;

Temperature	-20 °C to 60 °C
Relative Humidity	8% to 95%
Wet Bulb Temperature	39.0 °C

9.2 Atmospheric Pressure

The display assembly is capable of being operated without affecting its operations over the pressure range as following specified;

	Pressure	Note
Maximum Pressure	1040hPa	0m = sea level
Minimum Pressure	674hPa	3048m = 10.000 feet

Note : Non-operation attitude limit of this display module = 30,000 feet. = 9145 m.

9.3 Thermal Shock

The display module will not sustain damage after being subjected to 100 cycles of rapid temperature change. A cycle of rapid temperature change consists of varying the temperature from -20°C to 60°C, and back again.

Thermal shock cycle	-20 °C for 30min
	60 °C for 30min

Power is not applied during the test. After temperature cycling, the unit is placed in normal room ambient for at least 4 hours before powering on.

10.0 Reliability

This display module and the packaging of that will comply following standards.

10.1 Failure Criteria

The display assembly will be considered as failing unit when it no longer meets any of the requirements stated in this specification. Only as for maximum white luminance, following criteria is applicable.

- I **Maximum white Luminance shall be 125cd/m² or more.**

10.2 Failure Rate

The average failure rate of the display module (from first power-on cycle till 1,000 hours later) will not exceed 1.0%. The average failure rate of the display module from 1,000 hours until 16,000 hours will not exceed 0.7% per 1000 hours.

10.2.1 Usage

The assumed usage for the above criteria is:

- I 220 power-on hours per month
- I 500 power on/off cycles per month
- I Maximum brightness setting
- I Operation to be within office environment (25⁰C typical)

10.2.1 Component De-rating

All the components used in this device will be checked the load condition to meet the failure rate criteria.

10.3 On/OFF Cycle

The display module will be capable of being operated over the following ON/OFF Cycles.

ON/OFF	Value	Cycles
+Vin and CCFL power	30,000	10 seconds on / 10 seconds off

11.0 Safety

11.1 Sharp Edge Requirements

There will be no sharp edges or comers on the display assembly that could cause injury.

11.2 Materials

11.2.1 Toxicity

There will be no carcinogenic materials used anywhere in the display module. If toxic materials are used, they will be reviewed and approved by the responsible ADT Toxicologist.

11.2.2 Flammability

All components including electrical components that do not meet the flammability grade UL94-V1 in the module will complete the flammability rating exception approval process.

The printed circuit board will be made from material rated 94-V1 or better. The actual UL flammability rating will be printed on the printed circuit board.

11.3 Capacitors

If any polarized capacitors are used in the display assembly, provisions will be made to keep them from being inserted backwards.

12.0 Other requirement

12.1 National Test Lab Requirement


The display module will satisfy all requirements for compliance to

UL 1950, First Edition
CSA C22.2 No.950-M89
EEC 950
EN 60 950


U.S.A. Information Technology Equipment
 Canada, Information Technology Equipment
 International, Information Technology Equipment
 International, Information Processing Equipment
 (European Norm for IEC950)

12.2 Label



The label is on the panel as shown below:




13.0 Mechanical Characteristics




REV	ECO. NO.	DESCRIPTION	BY	DATE
ΔA	-	-	VILLE CHU	2003/09/03
-	-	-	IVY SHU	2004/03/29
-	-	-	IVY SHU	2004/03/18



DETAIL 2
SCALE 3.000



SECTION A-A




DETAIL 1
SCALE 3.000

The design is the property of AU Optonics Corp. and should not be disclosed to any third party without prior permission of AU Optonics Corp.




LEVEL	GENERAL TOLERANCE	FINISH	CHECKED	DATE	BY	REV
1-1	±0.15	1	ANDRY SU	2003/09/03		
1-2	±0.15	1	ANDRY SU	2003/09/03		
1-3	±0.15	1	ANDRY SU	2003/09/03		
1-4	±0.15	1	ANDRY SU	2003/09/03		
1-5	±0.15	1	ANDRY SU	2003/09/03		
1-6	±0.15	1	ANDRY SU	2003/09/03		
1-7	±0.15	1	ANDRY SU	2003/09/03		
1-8	±0.15	1	ANDRY SU	2003/09/03		
1-9	±0.15	1	ANDRY SU	2003/09/03		
1-10	±0.15	1	ANDRY SU	2003/09/03		
1-11	±0.15	1	ANDRY SU	2003/09/03		
1-12	±0.15	1	ANDRY SU	2003/09/03		
1-13	±0.15	1	ANDRY SU	2003/09/03		
1-14	±0.15	1	ANDRY SU	2003/09/03		
1-15	±0.15	1	ANDRY SU	2003/09/03		
1-16	±0.15	1	ANDRY SU	2003/09/03		
1-17	±0.15	1	ANDRY SU	2003/09/03		
1-18	±0.15	1	ANDRY SU	2003/09/03		
1-19	±0.15	1	ANDRY SU	2003/09/03		
1-20	±0.15	1	ANDRY SU	2003/09/03		
1-21	±0.15	1	ANDRY SU	2003/09/03		
1-22	±0.15	1	ANDRY SU	2003/09/03		
1-23	±0.15	1	ANDRY SU	2003/09/03		
1-24	±0.15	1	ANDRY SU	2003/09/03		
1-25	±0.15	1	ANDRY SU	2003/09/03		
1-26	±0.15	1	ANDRY SU	2003/09/03		
1-27	±0.15	1	ANDRY SU	2003/09/03		
1-28	±0.15	1	ANDRY SU	2003/09/03		
1-29	±0.15	1	ANDRY SU	2003/09/03		
1-30	±0.15	1	ANDRY SU	2003/09/03		
1-31	±0.15	1	ANDRY SU	2003/09/03		
1-32	±0.15	1	ANDRY SU	2003/09/03		
1-33	±0.15	1	ANDRY SU	2003/09/03		
1-34	±0.15	1	ANDRY SU	2003/09/03		
1-35	±0.15	1	ANDRY SU	2003/09/03		
1-36	±0.15	1	ANDRY SU	2003/09/03		
1-37	±0.15	1	ANDRY SU	2003/09/03		
1-38	±0.15	1	ANDRY SU	2003/09/03		
1-39	±0.15	1	ANDRY SU	2003/09/03		
1-40	±0.15	1	ANDRY SU	2003/09/03		
1-41	±0.15	1	ANDRY SU	2003/09/03		
1-42	±0.15	1	ANDRY SU	2003/09/03		
1-43	±0.15	1	ANDRY SU	2003/09/03		
1-44	±0.15	1	ANDRY SU	2003/09/03		
1-45	±0.15	1	ANDRY SU	2003/09/03		
1-46	±0.15	1	ANDRY SU	2003/09/03		
1-47	±0.15	1	ANDRY SU	2003/09/03		
1-48	±0.15	1	ANDRY SU	2003/09/03		
1-49	±0.15	1	ANDRY SU	2003/09/03		
1-50	±0.15	1	ANDRY SU	2003/09/03		
1-51	±0.15	1	ANDRY SU	2003/09/03		
1-52	±0.15	1	ANDRY SU	2003/09/03		
1-53	±0.15	1	ANDRY SU	2003/09/03		
1-54	±0.15	1	ANDRY SU	2003/09/03		
1-55	±0.15	1	ANDRY SU	2003/09/03		
1-56	±0.15	1	ANDRY SU	2003/09/03		
1-57	±0.15	1	ANDRY SU	2003/09/03		
1-58	±0.15	1	ANDRY SU	2003/09/03		
1-59	±0.15	1	ANDRY SU	2003/09/03		
1-60	±0.15	1	ANDRY SU	2003/09/03		
1-61	±0.15	1	ANDRY SU	2003/09/03		
1-62	±0.15	1	ANDRY SU	2003/09/03		
1-63	±0.15	1	ANDRY SU	2003/09/03		
1-64	±0.15	1	ANDRY SU	2003/09/03		
1-65	±0.15	1	ANDRY SU	2003/09/03		
1-66	±0.15	1	ANDRY SU	2003/09/03		
1-67	±0.15	1	ANDRY SU	2003/09/03		
1-68	±0.15	1	ANDRY SU	2003/09/03		
1-69	±0.15	1	ANDRY SU	2003/09/03		
1-70	±0.15	1	ANDRY SU	2003/09/03		
1-71	±0.15	1	ANDRY SU	2003/09/03		
1-72	±0.15	1	ANDRY SU	2003/09/03		
1-73	±0.15	1	ANDRY SU	2003/09/03		
1-74	±0.15	1	ANDRY SU	2003/09/03		
1-75	±0.15	1	ANDRY SU	2003/09/03		
1-76	±0.15	1	ANDRY SU	2003/09/03		
1-77	±0.15	1	ANDRY SU	2003/09/03		
1-78	±0.15	1	ANDRY SU	2003/09/03		
1-79	±0.15	1	ANDRY SU	2003/09/03		
1-80	±0.15	1	ANDRY SU	2003/09/03		
1-81	±0.15	1	ANDRY SU	2003/09/03		
1-82	±0.15	1	ANDRY SU	2003/09/03		
1-83	±0.15	1	ANDRY SU	2003/09/03		
1-84	±0.15	1	ANDRY SU	2003/09/03		
1-85	±0.15	1	ANDRY SU	2003/09/03		
1-86	±0.15	1	ANDRY SU	2003/09/03		
1-87	±0.15	1	ANDRY SU	2003/09/03		
1-88	±0.15	1	ANDRY SU	2003/09/03		
1-89	±0.15	1	ANDRY SU	2003/09/03		
1-90	±0.15	1	ANDRY SU	2003/09/03		
1-91	±0.15	1	ANDRY SU	2003/09/03		
1-92	±0.15	1	ANDRY SU	2003/09/03		
1-93	±0.15	1	ANDRY SU	2003/09/03		
1-94	±0.15	1	ANDRY SU	2003/09/03		
1-95	±0.15	1	ANDRY SU	2003/09/03		
1-96	±0.15	1	ANDRY SU	2003/09/03		
1-97	±0.15	1	ANDRY SU	2003/09/03		
1-98	±0.15	1	ANDRY SU	2003/09/03		
1-99	±0.15	1	ANDRY SU	2003/09/03		
1-100	±0.15	1	ANDRY SU	2003/09/03		

REV	ECN NO	DESCRIPTION	IP	DATE
1A	-	-	WALLE CHU	2003/09/01
1B	-	-	IYV SHU	2004/03/09
1C	-	-	IYV SHU	2004/03/19

NOTE:
 1.PRELIMINARY DRAWING FOR REFERENCE ONLY.
 2.THE DIMENSION EXCLUDES DEFORMATION.
 3.MODULE THICKNESS SHOULD BE 18mm MAX.
 4.TOLERANCE WITHOUT NOTICED TO BE±0.5mm.
 5.LAMP CABLE CONNECTOR TO BE JST BHSR-02VS-1
 6.I/F CONNECTOR TO BE JAE FI-X30SSL-HF.
 7.M3 USER HOLE SCREW TORQUE 4.0kg-cm MAX.
 8.USER HOLE SCREW PENETRATION 4.5mm MAX.
 9.DIMENSION TOLERANCE $|A-B| \leq 1.0$, $|C-D| \leq 1.0$



CHECK NOTE 9



This drawing is the property of AU Optronics Corp. and should not be disclosed to any third party without prior permission of AU Optronics Corp.

FORM N2 - AUPD-040-006 Ver.0

NO.	SCALE	PROJ	FILE	DATE	REVISION	DRW	APP	CHK	INSP	DATE
1	0.800			2003/11/17						

NO.	REV	DATE	BY	CHK	APP	DESCRIPTION
1	1	2003/11/17	ANDRY SU			APPEARANCE
2	2	2003/11/17	ANDRY SU			APPEARANCE
3	3	2003/11/17	ANDRY SU			APPEARANCE
4	4	2003/11/17	ANDRY SU			APPEARANCE
5	5	2003/11/17	ANDRY SU			APPEARANCE
6	6	2003/11/17	ANDRY SU			APPEARANCE
7	7	2003/11/17	ANDRY SU			APPEARANCE
8	8	2003/11/17	ANDRY SU			APPEARANCE
9	9	2003/11/17	ANDRY SU			APPEARANCE
10	10	2003/11/17	ANDRY SU			APPEARANCE
11	11	2003/11/17	ANDRY SU			APPEARANCE