



MA1046-1

For 1.9 GHz - Power Amplifier

MA1046-1

DESCRIPTION

The MA1046-1 is a 1.9 GHz band power amplifier ($P_o = +3.1W$), constructed by 3 stages of GaAs MESFET, RF matching circuit, and DC bias circuit. The shield cap is made of metal. Input and Output impedances are designed to 50Ω .


FEATURES

$P_o = +35.0$ dBm, Gain = +32 dB (min.) @1.9 GHz
 $V_{d1, 2} = +6.0V$, $V_{d3} = +10.0V$
 $V_{g1, 2} = -5.0V$, $V_{g3} = 3.0V$

APPLICATION

Power amplifier for PHS base station/Japan.

OUTLINE DRAWING



- Note: 1. Dimension of leads: 0.25×0.5
 2. Tolerance of dimension of leads interval: ± 0.3
 3. Tolerance of dimension except indications: ± 0.3
 4. Surface Leads: Tin Plating (Iron) (Material)

Amplifier Specifications (MA1046-1)

1. Maximum Ratings ($T_a = 25^\circ C$)

No.	Items	Symbol	Condition	Standard	Unit
1	Case temperature	T_c		$-20 \sim +70$	$^\circ C$
2	Storage temperature	T_{stg}		$-40 \sim +95$	$^\circ C$
3	Voltage	V_{D12}, V_{D3}	$V_{G12} = -5.0V, V_{G3} = -3.0V$	$V_{D12} = 7.0V, V_{D3} = 11.0V$	V
4	Gate Voltage	V_{G12}, V_{G3}	$V_{D12} = 6.0V, V_{D3} = 10.0V$	$V_{G12} = -8.0V, V_{G3} = -8.0V$	V
5	Input Power	P_{in}		+10 dBm	dBm

2. Electrical Performances ($T_c = +25^\circ C, V_{D1, 2} = 6V, V_{D3} = 10V, V_{G1, 2} = -5V, V_{G3} = -3V, Z_g = Z_l = 50\Omega$)

No.	Items	Symbol	Condition	Standard			Unit		
				Min	Type	Max			
1	Frequency	f		1895	---	1918	MHz		
2	Power Gain	G	$P_o = +35$ dBm $\pi / 4$ Shift QPSK Modulation -PN9	33	---	---	dB		
3	Temperature Characteristics (Power Gain)			---	---	± 2	dB		
4	Gain Variation	ΔG		---	---	± 0.5	dB		
5	Drain Current	I_{D12}		---	---	400	mA		
		I_{D3}		---	---	1400	mA		
6	Gate Current	I_{G12}		---	---	2	mA		
		I_{G3}		---	---	5	mA		
7	ACP	$\Delta 600$ kHz	ACP1	---	---	-65	dBc		
		$\Delta 900$ kHz	ACP2	---	---	-70	dBc		
8	Occupied Band Width	---		---	---	288	KHz		
9	Input VSWR	ρ_{in}	$P_o = +35$ dBm Non-modulation	---	---	2.0	---		
10	Spurious	In Band		---	---	---	-70	dBc	
		Out Band		---	$f \leq 6$ GHz	---	---	-60	dBc
		2 nd		2 SP	---	---	-30	dBc	
	3 rd	3 SP	---	---	---	-45	dBc		
11	Stability against load variation	---	$P_o = +35$ dBm Load VSWR = 1:3 All Phase	---	---	---	There is no abnormal oscillating signal more than -60 dBc		
12	Intensity against load variation	---	$P_o = +35$ dBm $Z_l = OPEN, SHORT$ 10 seconds each	---	---	---	There is no damage		

MA1046-1 $P_{in} - P_{out}$. ACP.

