

MA3062WA

Silicon planer type

Constant voltage, constant current, waveform clipper and surge absorption circuit

■ Features

- Mini type package (3-pin)
- Two anode-common wiring of MA3062

■ Absolute Maximum Ratings (Ta= 25°C)

| Parameter | Symbol | Rating | Unit |
|--|--------------------------|-------------------|------|
| Average forward current | $I_{F(AV)}$ | 100* ¹ | mA |
| Instantaneous forward current | I_{FRM} | 200* ¹ | mA |
| Total power dissipation | P_{tot} * ² | 100* ¹ | mW |
| Non-repetitive reverse surge power dissipation | P_{ZSM} * ³ | 15 | W |
| Junction temperature | T_j | 150 | °C |
| Storage temperature | T_{stg} | - 55 to + 150 | °C |

*¹ Working value in a single piece

*² With a printed-circuit board

*³ $t=100\mu s, T_j=150^\circ C$

■ Electrical Characteristics (Ta= 25°C)*¹

| Parameter | Symbol | Condition | min | typ | max | Unit |
|--|----------------------|-------------------|-----|-----|-----|---------------|
| Forward voltage | V_F | $I_F=10mA$ | | 0.8 | 0.9 | V |
| Zener voltage | V_Z * ² | $I_Z= 5mA$ | 5.8 | 6.2 | 6.6 | V |
| Operating resistance | R_Z | $I_Z= 5mA$ | | 6 | 20 | Ω |
| Reverse current | I_R | $V_R= 4V$ | | | 3 | μA |
| Temperature coefficient of zener voltage | S_Z * ³ | $I_Z= 5mA$ | 0.4 | 2.3 | 3.7 | $mV/^\circ C$ |
| Terminal capacitance | C_t | $V_R= 0V, f=1MHz$ | | 90 | 130 | pF |


Note 1. Rated input/output frequency : 5MHz

2. *¹ : The V_Z value is for the temperature of 25°C. In other cases, carry out the temperature compensation.

*² : Guaranteed at 20ms after power application

*³ : $T_j= 25$ to $150^\circ C$

■ Marking



■ Internal Connection

