

**2:1 Flux Coupled Transformer
5-200MHz**

**MABACT0048
V1P**

Features


- Surface Mount
- 2:1 Impedance
- Excellent amplitude and phase balance
- 260°C Reflow Compatible
- RoHS* Compliant
- Available on Tape and Reel. Reel quantity 2000

Description


M/A-COM's MABACT0048 is a 2:1 RF Flux Coupled transformer in a low cost, surface mount package. Ideally suited for high volume CATV/Broadband applications. Suitable for use in 50 and 75 Ohm systems.



Schematic



Case Style: SM-164



Dimensions in inches [mm] Tolerance: .xx ± .02, .xxx ± .010

Pin Configuration

Pin No.	Function
1	Secondary Dot (output 1)
2	Centre Tap (ground)
3	Secondary (output 2)
4	Primary (Ground)
5	Primary Dot (Input)

Note: Reference Application Note **M513** for reel size information.

Ordering Information

Part Number	Package
MABACT0048TR	2000 piece reel

* Restrictions on Hazardous Substances, European Union Directive 2002/95/EC.

M/A-COM Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice. M/A-COM makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does M/A-COM assume any liability whatsoever arising out of the use or application of any product(s) or information.

- **North America** Tel: 800.366.2266 / Fax: 978.366.2266
- **Europe** Tel: 44.1908.574.200 / Fax: 44.1908.574.300
- **Asia/Pacific** Tel: 81.44.844.8296 / Fax: 81.44.844.8298

Visit www.macom.com for additional data sheets and product information.

**2:1 Flux Coupled Transformer
5-200MHz**

**MABACT0048
V1P**

Electrical Specifications: $T_A = 25^\circ\text{C}$, $Z_0 = 75\Omega$


Parameter	Test Conditions	Units	Min	Typ	Max
Insertion Loss	5 - 65 MHz	dB	-	0.25	0.4
Insertion Loss	65 - 200 MHz	dB	-	0.4	0.9
Amplitude Unbalance (Nominal 0dB)	5 - 65 MHz	dB	-	± 0.02	± 0.15
Phase Unbalance (Nominal 180°)	5 - 50 MHz	°	-	± 0.00	± 2.00
Input Return Loss	5 - 200 MHz	dB	18	22	-

Absolute Maximum Ratings ^{1,2}

Parameter	Absolute Maximum
Max Input Power	250mW
DC current	30mA
Operating Temperature	-40°C to +85°C
Storage Temperature	-55°C to +100°C

1. Exceeding any one or combination of these limits may cause permanent damage to this device.
2. M/A-COM does not recommend sustained operation near these survivability limits.

Recommended PCB Configuration




**2:1 Flux Coupled Transformer
5-200MHz**


**MABACT0048
V1P**

Typical Performance Curves: $T_A = 25^\circ\text{C}$, $Z_0 = 75\Omega$


Insertion Loss (coupled pin 5 to pin 3)




Insertion Loss (through pin 5 to pin 1)



Amplitude Unbalance



Phase Balance



Input Return Loss

