

Features


- Glass passivated bridge rectifiers
- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Low forward voltage drop
- High temperature soldering guaranteed: 260°C/10 seconds



Package:
TO-269AA (MBS)

Mechanical Data

- Case: Molded plastic body over passivated junctions
- Terminals: plated leads solderable per MIL-STD-750, Method 2026
- Mounting position: any
- Weight: 0.078oz., 0.22g



Schematic Diagram

Maximum Ratings and Electrical Characteristics

($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	MB2ST	MB4ST	MB6ST	MB8ST	MB10ST	Unit
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	200	400	600	800	1000	V
Maximum Average Forward Output Current (see Fig.1) on glass-epoxy P.C.B on aluminum substrate	$I_{F(AV)}$			0.5 ⁽¹⁾			A
				0.8 ⁽²⁾			
Peak Forward Surge Current (8.3 ms single half sine-wave superimposed on rated load, JEDEC method)	I_{FSM}			30			A
Rating for Fusing ($t < 8.3\text{ms}$)	I^2t			3.0			A^2sec
Maximum Instantaneous Forward Voltage Drop per Leg at 0.4A	V_F			1.00			V
Maximum DC Reverse Current at Rated DC Blocking Voltage per Leg	I_R			5			μA
				100			
Typical Thermal Resistance per Leg	$R_{\theta JA}$ $R_{\theta JA}$ $R_{\theta JL}$			85 ⁽¹⁾			$^\circ\text{C}/\text{W}$
				70 ⁽²⁾			
				20 ⁽¹⁾			
Typical Junction Capacitance at 4.0V, 1.0MHz	C_J			13			pF
Operating Junction and Storage Temperature Range	T_J, T_{STG}			-55 to +150			$^\circ\text{C}$

Notes: 1. On glass epoxy P.C.B. mounted on 0.05×0.05 "($1.3 \times 1.3\text{mm}$) pads

2. On aluminum substrate P.C.B. with an area of 0.8×0.8 "($20 \times 20\text{mm}$) mounted on 0.05×0.05 "($1.3 \times 1.3\text{mm}$) solder pad

Ratings and Characteristics Curves ($T_A = 25^\circ\text{C}$ unless otherwise noted)




Figure 1. Derating Curve for Output Rectified Current




Figure 4. Typical Reverse Leakage Characteristics Per Leg




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current Per Leg




Figure 5. Typical Junction Capacitance Per Leg




Figure 3. Typical Forward Voltage Characteristics Per Leg

Package Outline Dimensions

in inches (millimeters)

TO-269AA (MBS)

