


MB1F THRU MB10F**SURFACE MOUNT FAST SWITCHING RECTIFIER****REVERSE VOLTAGE 50 to 1000 Volts FORWARD CURRENT 1.0 Ampere****FEATURES**

- ◆ Glass passivated chip junction.
- ◆ Ideal for surface mounted applications.
- ◆ Low leakage.
- ◆ High forward surge current capability.
- ◆ High temperature soldering guaranteed:
260°C/10 seconds at terminals.

Mechanical Data

- ◆ Case: Molded plastic body.
- ◆ Epoxy: UL94V-0 rate flame retardant.
- ◆ Polarity: Molded on body.
- ◆ Lead: Plated terminals solderable per MIL-STD-202E method 208C.
- ◆ Weight: 0.003 ounce, 0.1 gram.

MBF**Dimensions in inches and (millimeters)****MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS****Rating at 25°C ambient temperature unless otherwise specified.****Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%**

PARAMETER	SYMBOL	MB1F	MB2F	MB3F	MB4F	MB6F	MB8F	MB10F	UNIT
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Output Current, 0.06 " (1.5mm) lead length at $T_A=40^\circ\text{C}$ (Note 2)	$I_{(AV)}$	1.0							A
Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	30							A
Rating for Fusing ($t < 8.3\text{ms}$)	I^2t	10							A ² s
Maximum Instantaneous Forward Voltage drop Per Bridge element 1.0A	V_F	1.1							V
Maximum DC Reverse Current at $T_A=25^\circ\text{C}$ at Rated DC Blocking voltage $T_A=125^\circ\text{C}$	I_R	5.0							μA
		0.5							mA
Typical Junction Capacitance (Note 1)	C_J	25							pF
Typical Thermal Resistance (Note 2)	$R_{\theta JC}$	40							°C/W
Operating and Storage Temperature Range	T_J, T_{STG}	-55 to +150							°C

Note: 1. Measured at 1.0MHz and applied reverse voltage of 4.0 Volts.

2. Unit mounted on P.C.B. with 0.95"×1.15" copper pads.


MB1F THRU MB10F

SURFACE MOUNT FAST SWITCHING RECTIFIER


REVERSE VOLTAGE 50 to 1000 Volts FORWARD CURRENT 1.0 Ampere

RATING AND CHARACTERISTIC CURVES MB1F THRU MB10F


F1G.1-FORWARD CURRENT
DERATING CURVE




F1G.2-MAXIMUM NON-REPETITIVE PEAK
FORWARD SURGE CURRENT




F1G.3-TYPICAL INSTANTANEOUS
FORWARD CHARACTERISTICS



F1G.4-TYPICAL REVERSE
CHARACTERISTICS



F1G.5-TYPICAL JUNCTION CAPACITANCE



Note: Specifications are subject to change without notice. For more detail and update, please visit our website.