

1A SURFACE MOUNT GLASS PASSIVATED BRIDGE RECTIFIER
Feature

- Glass Passivated Chip Junction
- Reverse Voltage - 100 to 1000 V
- Forward Current - 1 A
- High Surge Current Capability
- Designed for Surface Mount Application

Mechanical Characteristics

- Case: MBF
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 75mg 0.0026oz

Maximum Ratings and Electrical characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20%.

Parameter	Sym bol	MB1F -10	MB2F -10	MB4F -10	MB6F -10	MB8F -10	MB10 F-10	U nit s
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	100	200	400	600	800	1000	V
Maximum RMS voltage	V _{RMS}	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V _{DC}	100	200	400	600	800	1000	V
Average Rectified Output Current at Ta=50°C	I _O	1.0						A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)	I _{FSM}	35						A
Maximum Forward Voltage at 1.0 A	V _F	1.1						V
Maximum DC Reverse Current @T _A =25°C at Rated DC Blocking Voltage @T _A =125°C	I _R	5 40						μA
Typical Junction Capacitance (Note 1)	C _j	13						pF
Typical Thermal Resistance (Note 2)	R _{θJA} R _{θjI}	85 30						°C /W
Operating and Storage Temperature Range	T _J , T _{ST} G	-55 to +150						°C

Note:

1. Measured at 1MHz and applied reverse voltage of 4 V D.C.
2. Mounted on glass epoxy PC board with 4 × (5 × 5mm²) copper pad.

Typical Characteristics




Fig.1 Average Rectified Output Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Instantaneous Forward Characteristics




Fig.4 Typical Junction Capacitance





Fig.5 Maximum Non-Repetitive Peak Forward Surge Current

Product dimension (MBF)



Unit:mm

Dim	Inches		Millimeters	
	MIN	MAX	MIN	MAX
A	177.00	197.00	4.50	5.00
B	142.00	161.00	3.60	4.10
C	5.90	8.70	0.15	0.22
D	--	8.00	--	0.20
E	252.00	276.00	6.40	7.00
G	20.00	43.00	0.50	1.10
H	51.00	67.00	1.30	1.70
K	91.00	106.00	2.30	2.70
L	47.00	63.00	1.20	1.60
F	20.00	31.00	0.50	0.80

IMPORTANT NOTICE

 and **Prisemi**[®] are registered trademarks of **Prisemi Electronics Co., Ltd (Prisemi)** ,Prisemi reserves the right to make changes without further notice to any products herein. Prisemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Prisemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. “Typical” parameters which may be provided in Prisemi data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including “Typicals” must be validated for each customer application by customer’s technical experts. Prisemi does not convey any license under its patent rights nor the rights of others. The products listed in this document are designed to be used with ordinary electronic equipment or devices, Should you intend to use these products with equipment or devices which require an extremely high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), please be sure to consult with our sales representative in advance.

Website: <http://www.prisemi.com>

For additional information, please contact your local Sales Representative.

©Copyright 2009, Prisemi Electronics

 **Prisemi**[®] is a registered trademark of Prisemi Electronics.

All rights are reserved.