

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

MBR1020FCT **THRU MBR10100FCT**

10 Amp Schottky Barrier Rectifier 20 to 100 Volts

Features

- High surge capacity
- High Efficiency
- Low Power Loss
- Low Forward Voltage , High Current Capability Lead Free Finish/Rohs Compliant (Note1) ("P"Suffix designates Compliant. See ordering information)
- Halogen free available upon request by adding suffix "-HF" Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

Maximum Ratings

- Operating Junction Temperature: -50°C to +150°C
- Storage Temperature: -50°C to +150°C


MCC	Device	Maximum	Maximum	Maximum
Catalog	Marking	Recurrent	RMS	DC
Number		Peak	Voltage	Blocking
		Reverse		Voltage
		Voltage		
MBR1020FCT	MBR1020FCT	20V	14V	20V
MBR1030FCT	MBR1030FCT	30V	21V	30V
MBR1040FCT	MBR1040FCT	40V	28V	40V
MBR1045FCT	MBR1045FCT	45V	31.5V	45V
MBR1050FCT	MBR1050FCT	50V	35V	50V
MBR1060FCT	MBR1060FCT	60V	42V	60V
MBR1080FCT	MBR1080FCT	80V	56V	80V
MBR10100FCT	MBR10100FCT	100V	70V	100V

Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	I _{F(AV)}	10 A	T _C = 100°C
Peak Forward Surge Current	I _{FSM}	120A	8.3ms, half sine
Maximum Instantaneous Forward Voltage 1020FCT-1045FCT 1050FCT-1060FCT 1080FCT-10100FCT	V _F	.70V .75V .85V	T _J = 25°C I _{FM} = 5A;
Maximum DC Reverse Current At Rated DC Blocking Voltage	I _R	0.1mA 50mA	T _C = 25°C T _C = 100°C

Notes: 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.

ITO-220AB




DIMENSIONS						
	INCHES		ММ			
DIM	MIN	MAX	MIN	MAX	NOTE	
Α	.583	.642	14.80	16.30		
В		.406		10.30		
С	.100	.112	2.55	2.85		
D	.248	.272	6.30	6.90		
Е		.161		4.10		
F		.071		1.80		
G	.512	.543	13.00	13.80		
Н	.100		2.55			
- 1		.035		0.90		
J		.032		0.80		
K	.118	.134	3.00	3.40	Ø	
L		.189		4.80		
M		.130		3.30		
N	.098	.114	2.50	2.90		
0		.055		1.40		

MBR1020FCT thru MBR10100FCT



Micro Commercial Components






Fig. 1-FORWARD CURRENT DERATING CURVE

Fig. 2-TYPICAL INSTNATANEOUS FORWARD CHARACTERISTIC




Fig. 3-MAXIMUM NON-REPETITIVE SURGE CURRENT



Ordering Information

Device	Packing
(Part Number)-BP	Bulk;1Kpcs/Box

Note: Adding "-HF" suffix for halogen free, eg. Part Number-BP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.