



Data Sheet

Customer :

Product : High Power Schottky Diode

Part No.: MBR1040CT/MBR1060CT/MBR10100CT/MBR10150CT
MBR10200CT/MBR10250CT

Issued Date: 11-Jan-11

Edition : REV.A



RoHS Compliant

VIKING TECH CORPORATION
光頓科技股份有限公司

No.70, Kuanfu N. Rad.,
Hsin Chu Industrial Park,
Hukou Hsiang, Hsin Chu Hsien,
303, Taiwan
TEL:886-3-5972931
FAX:886-3-5972935•886-3-5973494
E-mail:sales@viking.com.tw

VIKING TECH CORPORATION KAOHSIUNG BRANCH
光頓科技股份有限公司高雄分公司

No.248-3, Sin-Sheng Rd., Cian-Jhen Dist., Kaohsiung,
806, Taiwan
TEL:886-7-8217999
FAX:886-7-8228229
E-mail:sales@viking.com.tw

WUXI TMTEC CO., LTD.
無錫泰銘電子有限公司

No.1A,(Xixia Road),Machinery & Industry Park,
National Hi-Tech Industrial Development Zone of
Wuxi, Wuxi, Jiangsu Province, China
Zip Code:214028
TEL:86-510-85203339
FAX:86-510-85203667•86-510-85203977
E-mail:wuxisales@tmtec.com.tw

Produced by (QC)	Checked (QC)	Approved by (QC)	Prepared by (Sales)	Accepted by (Customer)
11-Jan-11	11-Jan-11	11-Jan-11	11-Jan-11	
Kris	Ann	J.C Liu		




10 Amperes High Power Schottky Barrier Rectifiers

Voltage : 40 to 250Volts

■ Features

- For use in low voltage, high frequency inverters, free wheeling and polarity protection applications
- Low power loss, high efficiency
- High current capability, low forward voltage drop
- High surge capability
- Guardring for over voltage protection
- Ultra high-speed switching
- Silicon epitaxial planar chip, metal silicon junction
- Lead-free parts meet environmental standards of MIL-STD-19500/228



■ Mechanical Data

Epoxy : UL94-V0 rated flame retardant

Case : JEDEC TO-220AB molded plastic body over

Terminals : Axial leads, Solderable per MIL-STD-202, Method 208 guaranteed


Polarity : Color band denotes cathode end

Mounting Position : Any

Weight : Approximated 2.25 gram

Package : 50pcs per Tube

■ Package Dimensions in millimeters(inches): TO-220AB



■ Maximum Ratings And Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

Parameter	Symbol	MBR1040CT	MBR1060CT	MBR10100CT	MBR10150CT	MBR10200CT	MBR10250CT	Unit
Marking Code		MBR1040CT	MBR1060CT	MBR10100CT	MBR10150CT	MBR10200CT	MBR10250CT	
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	40	60	100	150	200	250	V
Maximum RMS Voltage	V _{RMS}	28	42	70	105	140	175	V
Maximum DC Blocking Voltage	V _{DC}	40	60	100	150	200	250	V
Maximum Forward Voltage@5A, T _A =25°C @5A, T _A =125°C @10A, T _A =25°C	V _F	0.70 0.57 0.84	0.79 0.70 0.95	0.81 0.71 0.95	0.87 0.77 1.0	0.90 0.80 1.0	0.95 0.85 -	V
Operating Temperature	T _J	-50 ~ +150						°C

Parameter	Conditions	Symbol	Min.	Typ.	Max.	Unit
Forward Rectified Current	See Fig.1	I _O			10	A
Forward Surge Current	8.3ms single half sine-wave superimposed on rate load (JEDEC method)	I _{FSM}			125	A
Reverse Current	V _R =V _{RRM} , T _A =25°C	I _R			0.1	mA
	V _R =V _{RRM} , T _A =125°C				10	
Thermal Resistance	Junction to ambient	R _{θJA}		30		°C/W
Diode Junction Capacitance	f=1MHz and applied 4V DC reverse voltage	C _J		150		pF
Storage Temperature		T _{STG}	-50		+150	°C

■ Rated and Characteristic Curve

Fig. 1 - Forward Current Derating Curve




Fig. 2 - Maximum Non-Repetitive Peak Forward Surge Current




Fig. 3.1 - Typical Instantaneous Forward Characteristics




Fig. 3.2 - Typical Instantaneous Forward Characteristics




Fig. 3.3 - Typical Instantaneous Forward Characteristics




Fig. 4 - Typical Reverse Characteristics

