

# MBR1040FCT THRU MBR10200FCT

## List

List..... 1

Package outline..... 2

Features..... 2

Mechanical data..... 2

Maximum ratings .....2

Rating and characteristic curves..... 3

Pinning information.....4

Marking..... 4

Tube packing.....4

Suggested thermal profiles for soldering processes..... 5

High reliability test capabilities.....6



# MBR1040FCT THRU MBR10200FCT

## 10A High Barrier Power Schottky Rectifiers - 40V-200V


### Features

- 150°C operating junction temperature.
- Low power loss, high efficiency.
- High current capability
- High surge capability.
- Guardring for overvoltage protection.
- Low stored charge majority carrier conduction
- Silicon epitaxial planar chip, metal silicon junction.
- Lead-free parts meet environmental standards of MIL-STD-19500 /228
- Suffix "-H" indicates Halogen-free parts, ex. MBR1040FCT-H.

### Mechanical data

- Epoxy : UL94-V0 rated flame retardant
- Case : JEDEC ITO-220AB molded plastic body over passivated chip
- Lead : Axial leads, solderable per MIL-STD-202, Method 208 guaranteed
- Polarity: As marked
- Mounting Position : Any
- Weight : Approximated 1.70 gram

### Package outline



### Maximum ratings and Electrical Characteristics (AT $T_A=25^\circ\text{C}$ unless otherwise noted)

| PARAMETER                 | CONDITIONS                                  | Symbol          | MIN. | TYP. | MAX. | UNIT               |
|---------------------------|---|-----------------|------|------|------|--------------------|
| Forward rectified current | See Fig. 1                                  | $I_O$           |      |      | 10.0 | A                  |
| Forward surge current     | 8.3ms single half sine-wave (JEDEC methode) | $I_{FSM}$       |      |      | 125  | A                  |
| Reverse current           | $V_R = V_{RRM}$ $T_J = 25^\circ\text{C}$    | $I_R$           |      |      | 0.1  | mA                 |
|                           | $V_R = V_{RRM}$ $T_J = 125^\circ\text{C}$   |                 |      |      | 15   |                    |
| Thermal resistance        | Junction to case                            | $R_{\theta JC}$ |      | 3.0  |      | $^\circ\text{C/W}$ |
| Storage temperature       |   | $T_{STG}$       | -65  |      | +175 | $^\circ\text{C}$   |

| SYMBOLS     | $V_{RRM}^{*1}$<br>(V) | $V_{RMS}^{*2}$<br>(V) | $V_R^{*3}$<br>(V) | $V_F^{*4}$<br>(V) | $V_F^{*5}$<br>(V) | Operating temperature<br>$T_J$ , ( $^\circ\text{C}$ ) |
|-------------|-----------------------|-----------------------|-------------------|-------------------|-------------------|---|
| MBR1040FCT  | 40                    | 28                    | 40                | 0.70              | 0.84              | -55 to +150   |
| MBR1045FCT  | 45                    | 31.5                  | 45                |                   |                   |   |
| MBR1050FCT  | 50                    | 35                    | 50                | 0.80              | 0.95              |   |
| MBR1060FCT  | 60                    | 42                    | 60                |                   |                   |   |
| MBR1080FCT  | 80                    | 56                    | 80                | 0.85              | 1.00              |   |
| MBR10100FCT | 100                   | 70                    | 100               |                   |                   |   |
| MBR10150FCT | 150                   | 105                   | 150               | 0.95              | 1.00              |   |
| MBR10200FCT | 200                   | 140                   | 200               |                   |                   |   |

\*1 Repetitive peak reverse voltage

\*2 RMS voltage

\*3 Continuous reverse voltage

\*4 Maximum forward voltage  
 $I_F = 5.0\text{A}$ ,  $25^\circ\text{C}$

\*5 Maximum of forward voltage  
 $I_F = 10.0\text{A}$ ,  $25^\circ\text{C}$

## Rating and characteristic curves (MBR1040FCT THRU MBR10200FCT)

FIG. 1 – FORWARD CURRENT DERATING CURVE




FIG. 2 – MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3-TYPICAL REVER CHARACTERISTICS




FIG.4-TYPICAL FORWARD CHARACTERISTICS







FIG.5 – TYPICAL JUNCTION CAPACITANCE



# MBR1040FCT THRU MBR10200FCT

## Pinning information

| Pin                                      | Simplified outline  | Symbol  |
|--|---|---|
| Pin1 anode<br>Pin2 cathode<br>Pin3 anode |  |  |

## Marking

| Type number | Marking code |
|-------------|--------------|
| MBR1040FCT  | MBR1040FCT   |
| MBR1045FCT  | MBR1045FCT   |
| MBR1050FCT  | MBR1050FCT   |
| MBR1060FCT  | MBR1060FCT   |
| MBR1080FCT  | MBR1080FCT   |
| MBR10100FCT | MBR10100FCT  |
| MBR10150FCT | MBR10150FCT  |
| MBR10200FCT | MBR10200FCT  |


## Tube packing

| PACKAGE   | TUBE (pcs) | TUBE SIZE (m/m) | BOX (pcs) | INNER BOX (m/m) | CARTON SIZE (m/m) | CARTON (pcs) | APPROX. GROSS WEIGHT (kg) |
|-----------|------------|-----------------|-----------|-----------------|-------------------|--------------|---------------------------|
| ITO-220AB | 50         | 535*32*7.0      | 2000      | 550*167*75      | 570*345*170       | 8,000        | 23.0                      |

# MBR1040FCT THRU MBR10200FCT

## Suggested thermal profiles for soldering processes

### 1. Lead free temperature profile wave-soldering



# MBR1040FCT THRU MBR10200FCT

## High reliability test capabilities

| Item Test                         | Conditions   | Reference                     |
|-----------------------------------|--|-------------------------------|
| 1. Solder Resistance              | at $260\pm 5^{\circ}\text{C}$ for $10\pm 2\text{sec}$ .<br>immerse body into solder $1/16''\pm 1/32''$                                     | MIL-STD-750D<br>METHOD-2031   |
| 2. Solderability                  | at $245\pm 5^{\circ}\text{C}$ for 5 sec.   | MIL-STD-202F<br>METHOD-208    |
| 3. High Temperature Reverse Bias  | $V_R=80\%$ rate at $T_J=150^{\circ}\text{C}$ for 168 hrs.  | MIL-STD-750D<br>METHOD-1038   |
| 4. Forward Operation Life         | Rated average rectifier current at $T_A=25^{\circ}\text{C}$ for 500hrs.  | MIL-STD-750D<br>METHOD-1027   |
| 5. Intermittent Operation Life    | $T_A = 25^{\circ}\text{C}$ , $I_F = I_O$<br>On state: power on for 5 min.<br>off state: power off for 5 min.<br>on and off for 500 cycles. | MIL-STD-750D<br>METHOD-1036   |
| 6. Pressure Cooker                | $15P_{SIG}$ at $T_A=121^{\circ}\text{C}$ for 4 hrs.  | JESD22-A102                   |
| 7. Temperature Cycling            | $-55^{\circ}\text{C}$ to $+125^{\circ}\text{C}$ dwelled for 30 min.<br>and transferred for 5min. total 10 cycles.                          | MIL-STD-750D<br>METHOD-1051   |
| 8. Forward Surge                  | 8.3ms single half sine-wave , one surge.   | MIL-STD-750D<br>METHOD-4066-2 |
| 9. Humidity                       | at $T_A=85^{\circ}\text{C}$ , RH=85% for 1000hrs.  | MIL-STD-750D<br>METHOD-1021   |
| 10. High Temperature Storage Life | at $175^{\circ}\text{C}$ for 1000 hrs.   | MIL-STD-750D<br>METHOD-1031   |