



MBR3045C

主要参数 MAIN CHARACTERISTICS

$I_{F(AV)}$	30 (2×15) A
V_{RRM}	45V
T_j	150 °C
$V_{F(max)}$	0.56V (@ $T_j=125^{\circ}C$)

用途

- 高频开关电源
- 低压续流电路和保护电路

产品特性

- 共阴结构
- 低功耗，高效率
- 良好的高温特性
- 有过压保护环，高可靠性
- 环保（RoHS）产品

APPLICATIONS

- High frequency switch power supply
- Free wheeling diodes, polarity protection applications


FEATURES

- Common cathode structure
- Low power loss, high efficiency
- High Operating Junction Temperature
- Guard ring for overvoltage protection, High reliability
- RoHS product


封装 Package




TO-220




TO-220HF




TO-263



TO-262



TO-3PB



订货信息 ORDER MESSAGE

订货型号 Order codes	印记 Marking	封装 Package	无卤素 Halogen Free	包装 Packaging	器件重量 Device Weight
MBR3045CZ	MBR3045C	TO-220	否 NO	条管 Tube	1.98 g(typ)
MBR3045CZR	MBR3045C	TO-220	是 YES	条管 Tube	1.98 g(typ)
MBR3045CHF	MBR3045C	TO-220HF	否 NO	条管 Tube	1.70 g(typ)
MBR3045CHFR	MBR3045C	TO-220HF	是 YES	条管 Tube	1.70 g(typ)
MBR3045CS	MBR3045C	TO-263	否 NO	条管 Tube	1.90 g(typ)
MBR3045CSR	MBR3045C	TO-263	是 YES	条管 Tube	1.90 g(typ)
MBR3045CS	MBR3045C	TO-263	否 NO	编带 Reel	1.90 g(typ)
MBR3045CSR	MBR3045C	TO-263	是 YES	编带 Reel	1.90 g(typ)
MBR3045CB	MBR3045C	TO-262	否 NO	条管 Tube	1.70 g(typ)
MBR3045CBR	MBR3045C	TO-262	是 YES	条管 Tube	1.70 g(typ)
MBR3045CAB	MBR3045C	TO-3PB	否 NO	条管 Tube	5.20 g(typ)
MBR3045CABR	MBR3045C	TO-3PB	是 YES	条管 Tube	5.20 g(typ)



**绝对最大额定值 ABSOLUTE RATINGS** ($T_c=25^{\circ}\text{C}$)

项 目 Parameter			符 号 Symbol	数 值 Value	单 位 Unit
最大反向重复峰值电压 Repetitive peak reverse voltage			V_{RRM}	45	V
最大直流阻断电压 Maximum DC blocking voltage			V_{DC}	45	V
正向平均整流电流 Average forward current	$T_c=125^{\circ}\text{C}$ (TO-220, TO-262, TO-263, TO-3PB)	整个器件 per device	$I_{F(AV)}$	30	A
	$T_c=100^{\circ}\text{C}$ (TO-220HF)	单 侧 per diode		15	
正向峰值浪涌电流 Surge non repetitive forward current (额定负载 8.3ms 半正弦波—按 JEDEC 方法) 8.3 ms single half-sine-wave (JEDEC Method)			I_{FSM}	200	A
最高结温 Maximum junction temperature			T_j	150	$^{\circ}\text{C}$
储存温度 Storage temperature range			T_{STG}	-40~+150	$^{\circ}\text{C}$

电特性 ELECTRICAL CHARACTERISTICS

项 目 Parameter	测试条件 Tests conditions		最小值 Value(min)	典型值 Value(typ)	最大值 Value(max)	单位 Unit
I_R	$T_j=25^{\circ}\text{C}$	$V_R=V_{RRM}$			50	μA
	$T_j=125^{\circ}\text{C}$				30	mA
V_F	$T_j=25^{\circ}\text{C}$	$I_F=15\text{A}$		0.58	0.62	V
	$T_j=125^{\circ}\text{C}$			0.52	0.56	V

热特性 THERMAL CHARACTERISTICS


项 目 Parameter		符 号 Symbol	最小值 Value(min)	最大值 Value(max)	单 位 Unit
结到管壳的热阻 Thermal resistance from junction to case	TO-220	$R_{th(j-c)}$		1.6	$^{\circ}\text{C/W}$
	TO-263			1.6	
	TO-262			1.6	
	TO-3PB			1.8	
	TO-220HF			2.3	

特征曲线 ELECTRICAL CHARACTERISTICS (curves)




MBR3045C


I_F vs V_F




I_R vs V_R



$I_F(AV)$ vs T_C



C_T vs V_R




外形尺寸 PACKAGE MECHANICAL DATA

TO-220

单位 Unit : mm







符号 symbol	MIN	MAX
A	4.40	4.80
B	1.10	1.40
b	0.70	0.95
c	0.28	0.48
c1	0.32	0.52
D	14.45	16.00
D2	8.20	9.20
E	9.60	10.40
e	2.39	2.69
F	1.20	1.35
L	13.05	14.05
L2	3.70	3.90
Q	2.40	3.00
Q1	2.20	2.90
P	3.50	4.00

外形尺寸 PACKAGE MECHANICAL DATA
TO-263

单位 Unit : mm



编带 REEL




产品尺寸规格 (UNIT:mm)					
规格	W	A0	E	F	D
尺寸	24 ± 0.3	10.9 ± 0.2	1.75 ± 0.2	11.5 ± 0.2	1.5 +0.2/-0.1
规格	D1	P0	P2	P	T
尺寸	1.5 +0.2/-0.1	4 ± 0.2	2 ± 0.2	16 ± 0.2	0.35 ± 0.05
规格	K0	B0			
尺寸	4.9 ± 0.2	16.0 ± 0.2			

外形尺寸 PACKAGE MECHANICAL DATA

TO-262


单位 Unit : mm



符号 symbol	MIN	MAX
A	4.40	4.90
B	1.10	1.40
b	0.70	0.95
c	0.30	0.60
c1	0.33	0.63
D2	8.20	9.20
E	9.60	10.50
e	2.39	2.69
F	1.20	1.35
L	13.11	14.61
L2	3.55	4.05
Q	1.10	1.40
Q1	2.65	2.85

外形尺寸 PACKAGE MECHANICAL DATA
TO-220HF


单位 Unit : mm



符 号 Symbol	Min	Max
A	4.0	5.0
B1	0.87	1.27
b	0.72	0.92
c	0.5	0.70
D	15.0	16.5
D2	7.8	9.4
E	9.62	10.62
e	2.54(typ)	
F	2.3	3.3
L	12.0	14.0
L2	3.1	3.5
ΦP	3.0	3.4
Q	3.15	3.55
Q1	2.2	2.5

外形尺寸 PACKAGE MECHANICAL DATA
TO-3PB

单位 Unit : mm



符号 Symbol	MIN	MAX
A	4.60	5.00
B	2.90	3.20
B1	1.90	2.20
b	0.90	1.10
c	0.50	0.70
D	19.40	20.40
E	15.40	15.80
e	5.45(TYP)	
F	1.40	1.60
L	19.50	20.50
L2	3.30	3.70
Q	4.90	5.10
Q1	1.30	1.50
P	3.10	3.50

注意事项

1. 吉林华微电子股份有限公司的产品销售分为直销和销售代理，无论哪种方式，订货时请与公司核实。
2. 购买时请认清公司商标，如有疑问请与公司本部联系。

NOTE

1. Jilin Sino-microelectronics co., Ltd sales its product either through direct sales or sales agent , thus, for customers, when ordering , please check with our company.
2. We strongly recommend customers check carefully on the trademark when buying our product, if there is any question, please don't be hesitate to contact us.

**联系方式****吉林华微电子股份有限公司**

公司地址：吉林省吉林市深圳街 99 号

邮编：132013

总机：86-432-64678411

传真：86-432-64665812

网址：www.hwdz.com.cn**市场营销部**

地址：吉林省吉林市深圳街 99 号

邮编：132013

电话：86-432-64675588

64675688

64678411-3098/3099

传真：86-432-64671533

CONTACT**JILIN SINO-MICROELECTRONICS CO., LTD.**

ADD: No.99 Shenzhen Street, Jilin City, Jilin Province, China.

Post Code: 132013

Tel: 86-432-64678411

Fax: 86-432-64665812

Web Site: www.hwdz.com.cn**MARKET DEPARTMENT**

ADD: No.99 Shenzhen Street, Jilin City, Jilin Province, China.

Post Code: 132013

Tel: 86-432-64675588

64675688

64678411-3098/3099

Fax: 86-432-64671533

附录（Appendix）：修订记录（Revision History）

日期 Date	旧版本 Last Rev.	新版本 New Rev.	修订内容 Description of Changes
2015-3-4	201404A	201503B	Deleted TO-220B spec.

