



Data Sheet

Customer :

Product : High Power Schottky Diode

Part No.: MBRF3040CT/MBRF3060CT/MBRF30100CT/MBRF30150CT
MBRF30200CT/MBRF30250CT

Issued Date: 11-Jan-11

Edition : REV.A



VIKING TECH CORPORATION
光韻科技股份有限公司

No.70, Kuanfu N. Rad.,
Hsin Chu Industrial Park,
Hukou Hsiang, Hsin Chu Hsien,
303, Taiwan

TEL:886-3-5972931
FAX:886-3-5972935•886-3-5973494
E-mail:sales@viking.com.tw

VIKING TECH CORPORATION KAOHSIUNG BRANCH
光韻科技股份有限公司高雄分公司

No.248-3, Sin-Sheng Rd., Cian-Jhen Dist., Kaohsiung,
806, Taiwan

TEL:886-7-8217999
FAX:886-7-8228229
E-mail:sales@viking.com.tw

WUXI TMTEC CO., LTD.
無錫泰銘電子有限公司

No.1A,(Xixia Road),Machinery & Industry Park,
National Hi-Tech Industrial Development Zone of
Wuxi, Wuxi, Jiangsu Province, China
Zip Code:214028

TEL:86-510-85203339
FAX:86-510-85203667•86-510-85203977
E-mail:wuxisales@tmtec.com.tw

Produced by (QC)	Checked (QC)	Approved by (QC)	Prepared by (Sales)	Accepted by (Customer)
11-Jan-11	11-Jan-11	11-Jan-11	11-Jan-11	
Kris	Ann	J.C Liu		




30 Amperes High Power Schottky Barrier Rectifiers

Voltage : 40 to 250Volts

■ Features


- For use in low voltage, high frequency inverters, free wheeling and polarity protection applications
- Low power loss, high efficiency
- High current capability, low forward voltage drop
- High surge capability
- Guardring for overvoltage protection
- Ultra high-speed switching
- Silicon epitaxial planar chip, metal silicon junction
- Lead-free parts meet environmental standards of MIL-STD-19500/228



■ Mechanical Data

Epoxy : UL94-V0 rated flame retardant
Case : JEDEC ITO-220AB molded plastic body over passivated chip
Lead : Axial lead, solderable per MIL-STD-202, Method 208 guaranteed
Polarity : Color band denotes cathode end
Mounting Position : Any
Weight : Approximated 2.25 gram
Packaging : 50pcs per Tube

■ Package Dimensions in inches(millimeters): ITO-220AB



■ Maximum Ratings And Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load.
 For capacitive load, derate current by 20%.

Parameter	Symbol	MBRF3040CT	MBRF3060CT	MBRF30100CT	MBRF30150CT	MBRF30200CT	MBRF30250CT	Unit
Marking Code		MBRF3040CT	MBRF3060CT	MBRF30100CT	MBRF30150CT	MBRF30200CT	MBRF30250CT	
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	40	60	100	150	200	250	V
Maximum RMS Voltage	V_{RMS}	28	42	70	105	140	175	V
Maximum DC Blocking Voltage	V_{DC}	40	60	100	150	200	250	V
Maximum Forward Voltage@ 15A, $T_A=25^\circ C$	V_F	0.70	0.79	0.81	0.87	0.90	0.95	V
@ 15A, $T_A=125^\circ C$		0.57	0.70	0.71	0.77	0.80	0.85	
@ 30A, $T_A=25^\circ C$		0.84	0.95	0.95	1.0	1.0	-	
Operating Temperature	T_J	-50 ~ +150						$^\circ C$

Parameter	Conditions	Symbol	Min.	Typ.	Max.	Unit
Forward Rectified Current	See Fig.1	I_O			30	A
Forward Surge Current	8.3ms single half sine-wave superimposed on rate load (JEDEC method)	I_{FSM}			200	A
Reverse Current	$V_R=V_{RRM}, T_A=25^\circ C$	I_R			0.1	mA
	$V_R=V_{RRM}, T_A=125^\circ C$				10	
Thermal Resistance	Junction to ambient	$R_{\theta JA}$		30		$^\circ C/W$
Diode Junction Capacitance	f=1MHz and applied 4V DC reverse voltage	C_J		150		pF
Storage Temperature		T_{STG}	-50		+150	$^\circ C$

Rated and Characteristic Curve

Fig. 1 - Forward Current Derating Curve




Fig. 2 - Maximum Non-Repetitive Peak Forward Surge Current




Fig. 3A - Typical Instantaneous Forward Characteristics




Fig. 3B - Typical Instantaneous Forward Characteristics




Fig. 3C - Typical Instantaneous Forward Characteristics




Fig. 4 - Typical Reverse Characteristics

