


P & N-Channel 30-V (D-S) MOSFET

These miniature surface mount MOSFETs utilize High Cell Density process. Low $r_{DS(on)}$ assures minimal power loss and conserves energy, making this device ideal for use in power management circuitry. Typical applications are PWMDC-DC converters, power management in portable and battery-powered products such as computers, printers, battery charger, telecommunication power system, and telephones power system.

- Low $r_{DS(on)}$ Provides Higher Efficiency and Extends Battery Life
- Miniature SO-8 Surface Mount Package Saves Board Space
- High power and current handling capability
- Low side high current DC-DC Converter applications

PRODUCT SUMMARY		
V_{DS} (V)	$r_{DS(on)}$ m(Ω)	I_D (A)
30	40 @ $V_{GS} = 4.5V$	6.0
	31 @ $V_{GS} = 10V$	6.9
-30	80 @ $V_{GS} = -4.5V$	-4.2
	52 @ $V_{GS} = -10V$	-5.2



ABSOLUTE MAXIMUM RATINGS (T _A = 25 °C UNLESS OTHERWISE NOTED)						
Parameter			Symbol	N-Channel	P-Channel	Units
Drain-Source Voltage			V _{DS}	30	-30	V
Gate-Source Voltage			V _{GS}	±20	±20	
Continuous Drain Current ^a	T _A =25°C	I _D	6.9	-5.2	A	
	T _A =70°C		5.4	-6.8		
Pulsed Drain Current ^b			I _{DM}	20		-20
Continuous Source Current (Diode Conduction) ^a			I _S	1.3	-1.3	A
Power Dissipation ^a	T _A =25°C	P _D	2.1	2.1	W	
	T _A =70°C		1.3	1.3		
Operating Junction and Storage Temperature Range			T _J , T _{stg}	-55 to 150		°C

THERMAL RESISTANCE RATINGS				
Parameter		Symbol	Maximum	Units
Maximum Junction-to-Case ^a	$t \leq 5 \text{ sec}$	$R_{\theta JC}$	40	$^\circ\text{C/W}$
Maximum Junction-to-Ambient ^a	$t \leq 5 \text{ sec}$	$R_{\theta JA}$	60	$^\circ\text{C/W}$

Notes

- Surface Mounted on 1" x 1" FR4 Board.
- Pulse width limited by maximum junction temperature

SPECIFICATIONS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)

Parameter	Symbol	Test Conditions	Limits				Unit
			Ch	Min	Typ	Max	
Static							
Gate-Threshold Voltage	V _{GS(th)}	V _{GS} = V _{DS} , I _D = 250 uA	N	1			V
		V _{GS} = V _{DS} , I _D = -250 uA	P	-1.0			
Gate-Body Leakage	I _{GSS}	V _{GS} = -20 V, V _{DS} = 0 V	P			±100	nA
		V _{GS} = 20 V, V _{DS} = 0 V	N			±100	
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = -24 V, V _{GS} = 0 V	P			-1	uA
		V _{DS} = 24 V, V _{GS} = 0 V	N			1	
On-State Drain Current ^A	I _{D(on)}	V _{DS} = 5 V, V _{GS} = 10 V	N	20			A
		V _{DS} = -5 V, V _{GS} = -10 V	P	-20			
Drain-Source On-Resistance ^A	r _{DS(on)}	V _{GS} = 10 V, I _D = 6.9 A	N			31	mΩ
		V _{GS} = 4.5 V, I _D = 6 A				40	
		V _{GS} = -10 V, I _D = -5.2 A	P			52	
		V _{GS} = -4.5 V, I _D = -4.2 A				80	
Forward Tranconductance ^A	g _{fs}	V _{DS} = 15 V, I _D = 6.9 A	N		25		S
		V _{DS} = -15 V, I _D = -5.2 A	P		10		
Dynamic							
Total Gate Charge	Q _g	N-Channel V _{DS} =15V, V _{GS} =10V, I _D =6.9A P-Channel V _{DS} =-15V, V _{GS} =-10V, I _D =-5.2A	N		4.0		nC
Gate-Source Charge	Q _{gs}		P		10		
			N		1.1		
			P		2.2		
			N		1.4		
Gate-Drain Charge	Q _{gd}		P		1.7		
Turn-On Delay Time	t _{d(on)}	N-Chaneel V _{DD} =15V, V _{GS} =10V, I _D =1A , R _{GEN} =6Ω, P-Channel V _{DD} =-15V, V _{GS} =-10V, I _D =-1A RGEN=6Ω	N		8		nS
Rise Time	t _r		P		10		
			N		5		
Turn-Off Delay Time	t _{d(off)}		P		2.8		
			N		23		
Fall-Time	t _f		P		53.6		
			N		3		
			P		46		

Notes

- Pulse test: $PW \leq 300\mu\text{s}$ duty cycle $\leq 2\%$.
- Guaranteed by design, not subject to production testing.

FREESCALE reserves the right to make changes without further notice to any products herein. Freescale makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Freescale assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in Freescale data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Freescale does not convey any license under its patent rights nor the rights of others. Freescale products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Freescale product could create a situation where personal injury or death may occur. Should Buyer purchase or use Freescale products for any such unintended or unauthorized application, Buyer shall indemnify and hold Freescale and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Freescale was negligent regarding the design or manufacture of the part. Freescale is an Equal Opportunity/Affirmative Action Employer.

Typical Electrical Characteristics (N-Channel)




Figure 1. On-Region Characteristics




Figure 2. Body Diode Forward Voltage Variation with Source Current and Temperature




Figure 3. On Resistance Vs V_{GS} Voltage




Figure 4. Capacitance Characteristics




Figure 5. Gate Charge Characteristics




Figure 6. On-Resistance Variation with Temperature

Typical Electrical Characteristics (N-Channel)




Figure 7. Transfer Characteristics




Figure 9. Vth Gate to Source Voltage Vs Temperature




Figure 8. On-Resistance with Gate to Source Voltage




Figure 10. Single Pulse Maximum Power Dissipation




Figure 11. Transient Thermal Response Curve

Typical Electrical Characteristics (P-Channel)




Figure 1. On-Region Characteristics




Figure 2. Body Diode Forward Voltage Variation with Source Current and Temperature




Figure 3. On Resistance Vs Vgs Voltage




Figure 4. Capacitance Characteristics




Figure 5. Gate Charge Characteristics




Figure 6. On-Resistance Variation with Temperature

Typical Electrical Characteristics (P-Channel)




Figure 7. Transfer Characteristics




Figure 8. On-Resistance with Gate to Source Voltage




Figure 9. Vth Gate to Source Voltage Vs Temperature




Figure 10. Single Pulse Maximum Power Dissipation

Normalized Thermal Transient Junction to Ambient






Figure 11. Transient Thermal Response Curve

Package Information

SO-8: 8LEAD



Dim	MILLIMETERS		INCHES	
	Min	Max	Min	Max
A	1.35	1.75	0.053	0.069
A ₁	0.10	0.20	0.004	0.008
B	0.35	0.51	0.014	0.020
C	0.19	0.25	0.0075	0.010
D	4.80	5.00	0.189	0.196
E	3.80	4.00	0.150	0.157
e	1.27 BSC		0.050 BSC	
H	5.80	6.20	0.228	0.244
h	0.25	0.50	0.010	0.020
L	0.50	0.93	0.020	0.037
q	0°	8°	0°	8°

