

MOTOROLA Semiconductors

3501 ED BLUESTEIN BLVD., AUSTIN, TEXAS 78721


Advance Information

1.5 AND 2.0 MHZ COMPONENTS FOR THE M6800 MICROCOMPUTER SYSTEM

The eight devices described in this data sheet extend the operating frequency of the M6800 Microcomputer Family. The block diagrams and device operation are the same as for the basic M6800-series components.

- Fully Hardware and Software Compatible with the M6800 Family
- Power Dissipation Approximately 20% Lower Than on Standard MC6800 Series
- Clock Specification Improved for Reduced Complexity of Clock Generator/Driver Circuitry
- The MC6821 and its higher-frequency versions provide drive capability of two TTL loads on all A- and B-side buffers, improving the drive capability of the MC6820.

M6800 MICROCOMPUTER FAMILY
BLOCK DIAGRAM



1.5 MHz 2.0 MHz

MC68A00•MC68B00 MPU

MC68A21•MC68B21 PIA

MC68A50•MC68B50 ACIA

MCM68A10•MCM68B10 RAM

MOS

(N-CHANNEL, SILICON-GATE)

MICROPROCESSOR SYSTEM COMPONENTS



NOT SHOWN: L SUFFIX
CERAMIC PACKAGE
CASE 715

For additional information on these devices—including block diagrams, signal descriptions, device operation and pin assignments—refer to the *M6800 Microcomputer System Design Data* brochure.

MICROPROCESSING UNIT (MPU)

MC68A00 • MC68B00

ELECTRICAL CHARACTERISTICS ($V_{CC} = 5.0 \text{ V}$, $\pm 5\%$, $V_{SS} = 0$, $T_A = 0$ to 70°C unless otherwise noted.)

Characteristic	Symbol	Min	Typ	Max	Unit
Input High Voltage Logic ϕ_1, ϕ_2	V_{IH} V_{IHC}	$V_{SS} + 2.0$ $V_{CC} - 0.6$	—	V_{CC} $V_{CC} + 0.3$	Vdc
Input Low Voltage Logic ϕ_1, ϕ_2	V_{IL} V_{ILC}	$V_{SS} - 0.3$ $V_{SS} - 0.3$	—	$V_{SS} + 0.8$ $V_{SS} + 0.4$	Vdc
Input Leakage Current ($V_{in} = 0$ to 5.25 V , $V_{CC} = \text{max}$) ($V_{in} = 0$ to 5.25 V , $V_{CC} = 0.0 \text{ V}$)	I_{in}	— —	1.0 —	2.5 100	μA_{dc}
Three-State (Off State) Input Current ($V_{in} = 0.4$ to 2.4 V , $V_{CC} = \text{max}$)	I_{TSI}	— —	2.0 —	10 100	μA_{dc}
Output High Voltage ($I_{Load} = -205 \mu\text{A}_{dc}$, $V_{CC} = \text{min}$) ($I_{Load} = -145 \mu\text{A}_{dc}$, $V_{CC} = \text{min}$) ($I_{Load} = -100 \mu\text{A}_{dc}$, $V_{CC} = \text{min}$)	V_{OH} D0-D7 A0-A15, R/W, VMA BA	$V_{SS} + 2.4$ $V_{SS} + 2.4$ $V_{SS} + 2.4$	— — —	— — —	Vdc
Output Low Voltage ($I_{Load} = 1.6 \text{ mA}_{dc}$, $V_{CC} = \text{min}$)	V_{OL}	—	—	$V_{SS} + 0.4$	Vdc
Power Dissipation	P_D	—	0.5	1.0	W
Capacitance # ($V_{in} = 0$, $T_A = 25^\circ\text{C}$, $f = 1.0 \text{ MHz}$)	C_{in} ϕ_1 ϕ_2 D0-D7 Logic Inputs A0-A15, R/W, VMA	— — — —	— — 10 6.5	35 70 12.5 10	pF
Frequency of Operation	MC68A00 MC68B00	f 0.1 0.1	— —	1.5 2.0	MHz
Clock Timing (Figure 1)	MC68A00 MC68B00	t_{cyc}	0.666 0.50	10 10	μs
Cycle Time	MC68A00 MC68B00	$PW_{\phi H}$	230 180	9500 9500	ns
Clock Pulse Width (Measured at $V_{CC} - 0.6 \text{ V}$)	ϕ_1, ϕ_2 — MC68A00 ϕ_1, ϕ_2 — MC68B00	t_{ut}	600 440	— —	ns
Total ϕ_1 and ϕ_2 Up Time	MC68A00 MC68B00	$t_{\phi r}, t_{\phi f}$	5.0	100	ns
Rise and Fall Times (Measured between $V_{SS} + 0.4$ and $V_{CC} - 0.6$)		t_d	0	9100	ns
Delay Time or Clock Separation (Measured at $V_{OV} = V_{SS} + 0.6 \text{ V}$)					

*Except TRQ and NMI, which require a $3.0 \text{ k}\Omega$ pullup load resistor for wire-OR capability at optimum operation.

#Capacitances are periodically sampled rather than 100% tested.



READ/WRITE TIMING

Characteristic	Symbol	MC68A00			MC68B00			Unit
		Min	Typ	Max	Min	Typ	Max	
Address Delay C = 90 pF C = 30 pF	t _{AD}	—	—	180	—	—	150	ns
—	—	—	—	165	—	—	135	ns
Peripheral Read Access Time $t_{ac} = t_{ut} - (t_{AD} + t_{DSR})$	t _{acc}	—	—	360	—	—	250	ns
Data Setup Time (Read)	t _{DSR}	60	—	—	40	—	—	ns
Input Data Hold Time	t _H	10	—	—	10	—	—	ns
Output Data Hold Time	t _H	10	25	—	10	25	—	ns
Address Hold Time (Address, R/W, VMA)	t _{AH}	10	75	—	10	75	—	ns
Enable High Time for DBE Input	t _{EH}	280	—	—	220	—	—	ns
Data Delay Time (Write)	t _{DDW}	—	165	200	—	—	160	ns
Processor Controls								
Processor Control Setup Time	t _{PCS}	200	—	—	200	—	—	ns
Processor Control Rise and Fall Time	t _{PCr} , t _{PCf}	—	—	100	—	—	100	ns
Bus Available Delay	t _{BA}	—	—	270	—	—	270	ns
Three-State Enable	t _{TSE}	—	—	40	—	—	40	ns
Three-State Delay	t _{TSD}	—	—	270	—	—	270	ns
Data Bus Enable Down Time During ϕ_1 Up Time	t _{DBE}	150	—	—	70	—	—	ns
Data Bus Enable Rise and Fall Times	t _{DBEr} , t _{DBEf}	—	—	25	—	—	25	ns

FIGURE 1 – CLOCK TIMING WAVEFORM





FIGURE 2 – READ/WRITE TIMING WAVEFORM

Measurement point for ϕ_1 and ϕ_2 are shown below.
Other measurements are the same as for MC6800.



PERIPHERAL INTERFACE ADAPTER (PIA)
MC68A21 • MC68B21

ELECTRICAL CHARACTERISTICS ($V_{CC} = 5.0 \text{ V} \pm 5\%$, $V_{SS} = 0$, $T_A = 0$ to 70°C unless otherwise noted.)

Characteristic	Symbol	Min	Typ	Max	Unit
Input High Voltage	V_{IH}	$V_{SS} + 2.0$	—	V_{CC}	Vdc
Input Low Voltage	V_{IL}	$V_{SS} - 0.3$	—	$V_{SS} + 0.8$	Vdc
Input Leakage Current ($V_{in} = 0$ to 5.25 Vdc)	I_{in}	—	1.0	2.5	μAdc
Three-State (Off State) Input Current ($V_{in} = 0.4$ to 2.4 Vdc)	I_{TSI}	—	2.0	10	μAdc
Input High Current ($V_{IH} = 2.4 \text{ Vdc}$)	I_{IH}	-200	-400	—	μAdc
Input Low Current ($V_{IL} = 0.4 \text{ Vdc}$)	I_{IL}	—	-1.3	-2.4	mAdc
Output High Voltage ($I_{Load} = -205 \mu\text{Adc}$) ($I_{Load} = -200 \mu\text{Adc}$)	V_{OH}	$V_{SS} + 2.4$ $V_{SS} + 2.4$	— —	— —	Vdc
Output Low Voltage ($I_{Load} = 1.6 \text{ mAdc}$) ($I_{Load} = 3.2 \text{ mAdc}$)	V_{OL}	— —	— —	$V_{SS} + 0.4$ $V_{SS} + 0.4$	Vdc
Output High Current (Sourcing) ($V_{OH} = 2.4 \text{ Vdc}$) ($V_O = 1.5 \text{ Vdc}$, the current for driving other than TTL, e.g., Darlington Base)	I_{OH}	-205 -100 -1.0	— — -2.5	— — -10	μAdc μAdc mAdc
Output Leakage Current (Off State) ($V_{OH} = 2.4 \text{ Vdc}$)	I_{LOH}	—	1.0	10	μAdc
Power Dissipation	P_D	—	—	550	mW
Capacitance ($V_{in} = 0$, $T_A = 25^\circ\text{C}$, $f = 1.0 \text{ MHz}$)	C_{in}	— — —	— — —	12.5 10 7.5	pF
	C_{out}	—	—	5.0	pF

NOTE:

The PA0–PA7 Peripheral Data lines and the CA2 Peripheral Control line can drive two standard TTL loads. In the input mode, the internal pullup resistor on these lines represents a maximum of 1.5 standard TTL loads.



TIMING CHARACTERISTICS ($V_{CC} = 5.0 \text{ V} \pm 5\%$, $V_{SS} = 0$, $T_A = 0$ to 70°C unless otherwise noted.)

Characteristic	Symbol	MC68A21		MC68B21		Unit
		Min	Max	Min	Max	
Peripheral Data Setup Time	t_{PDSU}	135	—	100	—	ns
Peripheral Data Hold Time	t_{PDH}	0	—	0	—	ns
Delay Time, Enable negative transition to CA2 negative transition	t_{CA2}	—	0.670	—	0.5	μs
Delay Time, Enable negative transition to CA2 positive transition	t_{RS1}	—	0.670	—	0.5	μs
Rise and Fall Times for CA1 and CA2 input signals	t_r, t_f	—	1.0	—	1.0	μs
Delay Time from CA1 active transition to CA2 positive transition	t_{RS2}	—	1.35	—	1.0	μs
Delay Time, Enable negative transition to Peripheral Data Valid	t_{PDW}	—	0.670	—	0.5	μs
Delay Time, Enable negative transition to Peripheral CMOS Data Valid ($V_{CC} - 30\%$, V_{CC} ; Figure 6, Load C)	t_{CMOS}	—	1.35	—	1.0	μs
Delay Time, Enable positive transition to CB2 negative transition	t_{CB2}	—	0.670	—	0.5	μs
Delay Time, Peripheral Data Valid to CB2 negative transition	t_{DC}	20	—	20	—	ns
Delay Time, Enable positive transition to CB2 positive transition	t_{RS1}	—	0.670	—	0.5	μs
Peripheral Control Output Pulse Width, CA2/CB2	PW_{CT}	550	—	550	—	ns
Rise and Fall Time for CB1 and CB2 input signals	t_r, t_f	—	1.0	—	1.0	μs
Delay Time, CB1 active transition to CB2 positive transition	t_{RS2}	—	1.35	—	1.0	μs
Interrupt Release Time, IRQA and IRQB	t_{IR}	—	1.1	—	0.85	μs
Interrupt Response Time	t_{RS3}	—	1.0	—	1.0	μs
Interrupt Input Pulse Width	PW_I	500	—	500	—	ns
Reset Low Time*	t_{RL}	0.66	—	0.5	—	μs

*The Reset line must be high a minimum of 1.0 μs before addressing the PIA.

BUS TIMING CHARACTERISTICS ($V_{CC} = 5.0 \text{ V} \pm 5\%$, $V_{SS} = 0$, $T_A = 0$ to 70°C unless otherwise noted.)**READ**

Characteristic	Symbol	MC68A21		MC68B21		Unit
		Min	Max	Min	Max	
Enable Cycle Time	t_{cycE}	0.666	—	0.50	—	μs
Enable Pulse Width, High	PW_{EH}	0.280	—	0.22	—	μs
Enable Pulse Width, Low	PW_{EL}	0.280	—	0.21	—	μs
Setup Time, Address and R/W Valid to Enable positive transition	t_{AS}	140	—	70	—	ns
Data Delay Time	t_{DDR}	—	220	—	180	ns
Data Hold Time	t_H	10	—	10	—	ns
Address Hold Time	t_{AH}	10	—	10	—	ns
Rise and Fall Time for Enable input	t_{Er}, t_{Ef}	—	25	—	25	ns





WRITE

Enable Cycle Time	t_{cycE}	0.666	—	0.50	—	μs
Enable Pulse Width, High	PW_{EH}	0.280	—	0.22	—	μs
Enable Pulse Width, Low	PW_{EL}	0.280	—	0.21	—	μs
Setup Time, Address and R/W Valid to Enable positive transition	t_{AS}	140	—	70	—	ns
Data Setup Time	t_{DSW}	80	—	60	—	ns
Data Hold Time	t_H	10	—	10	—	ns
Address Hold Time	t_{AH}	10	—	10	—	ns
Rise and Fall Time for Enable input	t_{Er}, t_{Ef}	—	25	—	25	ns



NOTES:

- Figures shown are only those needed to define new measurements *not* specified on the MC6820 data sheet (page 39 of M6800 Microcomputer System Design Data). Refer to that data sheet, or to the new MC6821 data sheet, for further information.
- On all tests, measurements on the Enable pulse are at 0.8 V and 2.0 V.

FIGURE 4 – PERIPHERAL CONTROL OUTPUT PULSE WIDTH**FIGURE 3 – PERIPHERAL DATA HOLD TIME
(Read Mode)****FIGURE 5 – INTERRUPT PULSE WIDTH and $\overline{\text{IRQ}}$ RESPONSE****FIGURE 6 – BUS TIMING TEST LOADS**

ASYNCHRONOUS COMMUNICATIONS INTERFACE ADAPTER (ACIA)

MC68A50 • MC68B50

ELECTRICAL CHARACTERISTICS ($V_{CC} = 5.0 \text{ V} \pm 5\%$, $V_{SS} = 0$, $T_A = 0$ to 70°C unless otherwise noted.)

Characteristic	Symbol	Min	Typ	Max	Unit
Input High Voltage	V_{IH}	$V_{SS} + 2.0$	—	V_{CC}	Vdc
Input Low Voltage	V_{IL}	$V_{SS} - 0.3$	—	$V_{SS} + 0.8$	Vdc
Input Leakage Current ($V_{in} = 0$ to 5.25 Vdc)	I_{in}	—	1.0	2.5	μAdc
Three-State (Off State) Input Current ($V_{in} = 0.4$ to 2.4 Vdc)	I_{TSI}	—	2.0	10	μAdc
Output High Voltage ($I_{Load} = -205 \mu\text{Adc}$, Enable Pulse Width $< 25 \mu\text{s}$) ($I_{Load} = -100 \mu\text{Adc}$, Enable Pulse Width $< 25 \mu\text{s}$)	V_{OH}	$V_{SS} + 2.4$ $V_{SS} + 2.4$	— —	— —	Vdc
Output Low Voltage ($I_{Load} = 1.6 \text{ mA}$, Enable Pulse Width $< 25 \mu\text{s}$)	V_{OL}	—	—	$V_{SS} + 0.4$	Vdc
Output Leakage Current (Off State) ($V_{OH} = 2.4 \text{ Vdc}$)	I_{LOH}	—	1.0	10	μAdc
Power Dissipation	P_D	—	300	525	mW
Capacitance ($V_{in} = 0$, $T_A = 25^\circ\text{C}$, $f = 1.0 \text{ MHz}$)	C_{in}	— —	10 7.0	12.5 7.5	pF
	C_{out}	— —	— —	10 5.0	pF
Minimum Clock Pulse Width, Low	PW_{CL}	600	—	—	ns
Minimum Clock Pulse Width, High	PW_{CH}	600	—	—	ns
Clock Frequency	f_C	— —	— —	500 800	kHz
Clock-to-Data Delay for Transmitter	t_{TDD}	—	—	1.0	μs
Receive Data Setup Time	t_{RDSSU}	500	—	—	ns
Receive Data Hold Time	t_{RDH}	500	—	—	ns
Interrupt Request Release Time	t_{IR}	—	—	1.2	μs
Request-to-Send Delay Time	t_{RTS}	—	—	1.0	μs
Input Transition Times (Except Enable)	$t_{r,tf}$	—	—	1.0*	μs

* $1.0 \mu\text{s}$ or 10% of the pulse width, whichever is smaller.

BUS TIMING CHARACTERISTICS ($V_{CC} = 5.0 \text{ V} \pm 5\%$, $V_{SS} = 0$, $T_A = 0$ to 70°C unless otherwise noted.)

READ

Characteristic	Symbol	MC68A50		MC68B50		Unit
		Min	Max	Min	Max	
Enable Cycle Time	t_{cycE}	0.666	—	0.50	—	μs
Enable Pulse Width, High	PW_{EH}	0.28	25	0.22	25	μs
Enable Pulse Width, Low	PW_{EL}	0.28	—	0.21	—	μs
Setup Time, Address and R/W Valid to Enable positive transition	t_{AS}	140	—	70	—	ns
Data Delay Time	t_{DDR}	—	220	—	180	ns
Data Hold Time	t_H	10	—	10	—	ns
Address Hold Time	t_{AH}	10	—	10	—	ns
Rise and Fall Time for Enable input	t_{Er}, t_{Ef}	—	25	—	25	ns

WRITE

Enable Cycle Time	t_{cycE}	0.666	—	0.50	—	μs
Enable Pulse Width, High	PW_{EH}	0.28	25	0.22	25	μs
Enable Pulse Width, Low	PW_{EL}	0.28	—	0.21	—	μs
Setup Time, Address and R/W Valid to Enable positive transition	t_{AS}	140	—	70	—	ns
Data Setup Time	t_{DSW}	80	—	60	—	ns
Data Hold Time	t_H	10	—	10	—	ns
Address Hold Time	t_{AH}	10	—	10	—	ns
Rise and Fall Time for Enable input	t_{Er}, t_{Ef}	—	25	—	25	ns



RANDOM ACCESS MEMORY (RAM)
MCM68A10 • MCM68B10

DC CHARACTERISTICS ($V_{CC} = 5.0 \text{ V} \pm 5\%$, $V_{SS} = 0$, $T_A = 0$ to 70°C unless otherwise noted.)

Characteristic	Symbol	Min	Typ	Max	Unit
Input Current (A_n , R/W, CS_n , \overline{CS}_n) ($V_{in} = 0$ to 5.25 V)	I_{in}	—	—	2.5	$\mu\text{A}/\text{d}$
Output High Voltage ($I_{OH} = -205 \mu\text{A}$)	V_{OH}	2.4	—	—	Vdc
Output Low Voltage ($I_{OL} = 1.6 \text{ mA}$)	V_{OL}	—	—	0.4	Vdc
Output Leakage Current (Three-State) ($CS = 0.8 \text{ V}$ or $\overline{CS} = 2.0 \text{ V}$, $V_{out} = 0.4 \text{ V}$ to 2.4 V)	I_{LO}	—	—	10	$\mu\text{A}/\text{d}$
Supply Current ($V_{CC} = 5.25 \text{ V}$, all other pins grounded, $T_A = 0^\circ\text{C}$)	I_{CC}	—	—	80	mAdc

AC CHARACTERISTICS

READ CYCLE ($V_{CC} = 5.0 \text{ V} \pm 5\%$, $V_{SS} = 0$, $T_A = 0$ to 70°C unless otherwise noted.)

Characteristic	Symbol	MCM68A10		MCM68B10		Unit
		Min	Max	Min	Max	
Read Cycle Time	$t_{cyc(R)}$	360	—	250	—	ns
Access Time	t_{acc}	—	360	—	250	ns
Address Setup Time	t_{AS}	20	—	20	—	ns
Address Hold Time	t_{AH}	0	—	0	—	ns
Data Delay Time (Read)	t_{DDR}	—	220	—	180	ns
Read to Select Delay Time	t_{RCS}	0	—	0	—	ns
Data Hold from Address	t_{DHA}	10	—	10	—	ns
Output Hold Time	t_H	10	—	10	—	ns
Data Hold from Write	t_{DHW}	10	60	10	60	ns

WRITE CYCLE ($V_{CC} = 5.0 \text{ V} \pm 5\%$, $V_{SS} = 0$, $T_A = 0$ to 70°C unless otherwise noted.)

Characteristic	Symbol	MCM68A10		MCM68B10		Unit
		Min	Max	Min	Max	
Write Cycle Time	$t_{cyc(W)}$	360	—	250	—	ns
Address Setup Time	t_{AS}	20	—	20	—	ns
Address Hold Time	t_{AH}	0	—	0	—	ns
Chip Select Pulse Width	t_{CS}	250	—	210	—	ns
Write to Chip Select Delay Time	t_{WCS}	0	—	0	—	ns
Data Setup Time (Write)	t_{DSW}	80	—	60	—	ns
Input Hold Time	t_H	10	—	10	—	ns



MOTOROLA Semiconductor Products Inc.

3501 ED BLUESTEIN BLVD., AUSTIN, TEXAS 78721 • A SUBSIDIARY OF MOTOROLA INC.