


**3-TERMINAL 1A NEGATIVE VOLTAGE REGULATORS**

The MC79XX series of three-terminal negative regulators are available in TO-220 package and with several fixed output voltages, making them useful in a wide range of applications. Each type employs internal current limiting, thermal shut-down and safe area protection, making it essentially indestructible.

**FEATURES**


- Output Current in Excess of 1A
- Output Voltages of -5, -6, -8, -12, -15, -18, -24V
- Internal Thermal Overload Protection
- Short Circuit Protection
- Output Transistor Safe-Area Compensation



**ORDERING INFORMATION**

Device	Output Voltage Tolerance	Package	Operating Temperature
MC79XXCT (LM79XXCT) (KA79XX)	± 4%	TO-220	0 ~+125°C
KA79XXA	± 2%		

**BLOCK DIAGRAM**



**ABSOLUTE MAXIMUM RATINGS** ( $T_A=+25^{\circ}\text{C}$ , unless otherwise specified)

Characteristic	Symbol	Value	Unit
Input Voltage	$V_I$	-35	V
Thermal Resistance Junction-Cases	$R_{\theta JC}$	5	$^{\circ}\text{C}/\text{W}$
Junction-Air	$R_{\theta JA}$	65	$^{\circ}\text{C}/\text{W}$
Operating Temperature Range	$T_{OPR}$	0 ~ +125	$^{\circ}\text{C}$
Storage Temperature Range	$T_{STG}$	-65 ~ +150	$^{\circ}\text{C}$

**LM7905 ELECTRICAL CHARACTERISTICS**

( $V_I = 10\text{V}$ ,  $I_O = 500\text{mA}$ ,  $0^{\circ}\text{C} \leq T_J \leq +125^{\circ}\text{C}$ ,  $C_I = 2.2\mu\text{F}$ ,  $C_O = 1\mu\text{F}$ , unless otherwise specified.)

Characteristic	Symbol	Test Conditions	Min	Typ	Max	Unit
Output Voltage	$V_O$	$T_J = +25^{\circ}\text{C}$	-4.8	-5.0	-5.2	V
		$I_O = 5\text{mA}$ to $1\text{A}$ , $P_O = 15\text{W}$ $V_I = -7$ to $-20\text{V}$	-4.75	-5.0	-5.25	
Line Regulation	$\Delta V_O$	$T_J = +25^{\circ}\text{C}$ $V_I = -7$ to $-20\text{V}$ $I_O = 1\text{A}$		5	50	mV
		$V_I = -8$ to $-12\text{V}$ $I_O = 1\text{A}$		2	25	
		$V_I = -7.5$ to $-25\text{V}$		7	50	
		$V_I = -8$ to $-12\text{V}$ $I_O = 1\text{A}$		7	50	
Load Regulation	$\Delta V_O$	$I_O = 5\text{mA}$ to $1.5\text{A}$		10	100	mV
		$T_J = +25^{\circ}\text{C}$ $I_O = 250$ to $750\text{mA}$		3	50	
Quiescent Current	$I_Q$	$T_J = +25^{\circ}\text{C}$		3	6	mA
Quiescent Current Change	$\Delta I_Q$	$I_O = 5\text{mA}$ to $1\text{A}$		0.05	0.5	mA
		$V_I = -8$ to $-25\text{V}$		0.1	0.8	
Temperature Coefficient of $V_D$	$\Delta V_O/\Delta T$	$I_O = 5\text{mA}$		-0.4		mV/ $^{\circ}\text{C}$
Output Noise Voltage	$V_N$	$f = 10\text{Hz}$ to $100\text{KHz}$ $T_A = +25^{\circ}\text{C}$		40		$\mu\text{V}$
Ripple Rejection	RR	$f = 120\text{Hz}$ , $I_O = -35\text{V}$ $\Delta V_I = 10\text{V}$	54	60		dB
Dropout Voltage	$V_D$	$T_J = +25^{\circ}\text{C}$ $I_O = 1\text{A}$		2		V
Short Circuit Current	$I_{SC}$	$T_J = +25^{\circ}\text{C}$ , $V_I = -35\text{V}$		300		mA
Peak Current	$I_{PK}$	$T_J = +25^{\circ}\text{C}$		2.2		A

\* Load and line regulation are specified at constant junction temperature. Changes in  $V_O$  due to heating effects must be taken into account separately. Pulse testing with low duty is used.

**LM7906 ELECTRICAL CHARACTERISTICS**(V<sub>I</sub> = 11V, I<sub>O</sub> = 500mA, 0°C ≤ T<sub>J</sub> ≤ +125°C, C<sub>I</sub> = 2.2μF, C<sub>O</sub> = 1μF, unless otherwise specified.)

Characteristic	Symbol	Test Conditions	Min	Typ	Max	Unit
Output Voltage	V <sub>O</sub>	T <sub>J</sub> = +25°C	- 5.75	- 6	- 6.25	V
		I <sub>O</sub> = 5mA to 1A, P <sub>O</sub> 15W V <sub>I</sub> = - 9 to - 21V	- 5.7	- 6	- 6.3	
Line Regulation	ΔV <sub>O</sub>	T <sub>J</sub> = 25°C	V <sub>I</sub> = - 8 to - 25V	10	120	mV
			V <sub>I</sub> = - 9 to - 12V	5	60	
Load Regulation	ΔV <sub>O</sub>	T <sub>J</sub> = + 25°C I <sub>O</sub> = 5mA to 1.5A		10	120	mV
		T <sub>J</sub> = + 25°C I <sub>O</sub> = 250 to 750mA		3	60	
Quiescent Current	I <sub>O</sub>	T <sub>J</sub> = + 25°C		3	6	mA
Quiescent Current Change	ΔI <sub>O</sub>	I <sub>O</sub> = 5mA to 1A			0.5	mA
		V <sub>I</sub> = - 9 to - 25V			1.3	
Temperature Coefficient of V <sub>O</sub>	ΔV <sub>O</sub> /ΔT	I <sub>O</sub> = 5mA		-0.5		mV/°C
Output Noise Voltage	V <sub>N</sub>	f = 10Hz to 100KHz T <sub>A</sub> = + 25°C		130		μV
Ripple Rejection	RR	f = 120Hz ΔV <sub>I</sub> = 10V	54	60		dB
Dropout Voltage	V <sub>D</sub>	T <sub>J</sub> = + 25°C I <sub>O</sub> = 1A		2		V
Short Circuit Current	I <sub>SC</sub>	T <sub>J</sub> = +25°C, V <sub>I</sub> = -35V		300		mA
Peak Current	I <sub>PK</sub>	T <sub>J</sub> = +25°C		2.2		A

\* Load and line regulation are specified at constant junction temperature. Changes in V<sub>O</sub> due to heating effects must be taken into account separately. Pulse testing with low duty is used.

**LM7908 ELECTRICAL CHARACTERISTICS**(V<sub>I</sub> = 14V, I<sub>O</sub> = 500mA, 0°C ≤ T<sub>J</sub> ≤ +125°C, C<sub>I</sub> = 2.2μF, C<sub>O</sub> = 1μF, unless otherwise specified.)

Characteristic	Symbol	Test Conditions	Min	Typ	Max	Unit
Output Voltage	V <sub>O</sub>	T <sub>J</sub> = +25°C	-7.7	-8	-8.3	V
		I <sub>O</sub> = 5mA to 1A, P <sub>O</sub> 15W V <sub>I</sub> = -1.5 to -23V	-7.6	-8	-8.4	
Line Regulation	ΔV <sub>O</sub>	T <sub>J</sub> = 25°C		10	100	mV
		V <sub>I</sub> = -10.5 to -25V V <sub>I</sub> = -11 to -17V		5	80	
Load Regulation	ΔV <sub>O</sub>	T <sub>J</sub> = +25°C I <sub>O</sub> = 5mA to 1.5A		12	160	mV
		T <sub>J</sub> = +25°C I <sub>O</sub> = 250 to 750mA		4	80	
Quiescent Current	I <sub>Q</sub>	T <sub>J</sub> = +25°C		3	6	mA
Quiescent Current Change	ΔI <sub>Q</sub>	I <sub>O</sub> = 5mA to 1A		0.05	0.5	mA
		V <sub>I</sub> = -11.5 to -25V		0.1	1	
Temperature Coefficient of V <sub>O</sub>	ΔV <sub>O</sub> /ΔT	I <sub>O</sub> = 5mA		-0.6		mV/°C
Output Noise Voltage	V <sub>N</sub>	f = 10Hz to 100KHz T <sub>A</sub> = +25°C		175		μV
Ripple Rejection	RR	f = 120Hz ΔV <sub>I</sub> = 10V	54	60		dB
Dropout Voltage	V <sub>D</sub>	T <sub>J</sub> = +25°C I <sub>O</sub> = 1A		2		V
Short Circuit Current	I <sub>SC</sub>	T <sub>J</sub> = +25°C, V <sub>I</sub> = -35V		300		mA
Peak Current	I <sub>PK</sub>	T <sub>J</sub> = +25°C		2.2		A

\* Load and line regulation are specified at constant junction temperature. Changes in V<sub>O</sub> due to heating effects must be taken into account separately. Pulse testing with low duty is used.

**LM7909 ELECTRICAL CHARACTERISTICS**(V<sub>I</sub> = 14V, I<sub>O</sub> = 500mA, 0°C ≤ T<sub>J</sub> ≤ +125°C, C<sub>I</sub> = 2.2μF, C<sub>O</sub> = 1μF, unless otherwise specified)

Characteristic	Symbol	Test Conditions	Min	Typ	Max	Unit
Output Voltage	V <sub>O</sub>	T <sub>J</sub> = +25°C	-8.7	-9.0	-9.3	V
		I <sub>O</sub> = 5mA to 1A, P <sub>O</sub> = 15W V <sub>I</sub> = -1.5 to -23V	-8.6	-9.0	-9.4	
Line Regulation	ΔV <sub>O</sub>	T <sub>J</sub> = 25°C	V <sub>I</sub> = -10.5 to -25V	10	180	mV
			V <sub>I</sub> = -11 to -17V	5	90	
Load Regulation	ΔV <sub>O</sub>	T <sub>J</sub> = +25°C I <sub>O</sub> = 5mA to 1.5A		12	180	mV
		T <sub>J</sub> = +25°C I <sub>O</sub> = 250 to 750mA		4	90	
Quiescent Current	I <sub>Q</sub>	T <sub>J</sub> = +25°C		3	6	mA
Quiescent Current Change	ΔI <sub>Q</sub>	I <sub>O</sub> = 5mA to 1A		0.05	0.5	mA
		V <sub>I</sub> = -11.5 to -25V		0.1	1	
Temperature Coefficient of V <sub>O</sub>	ΔV <sub>O</sub> /ΔT	I <sub>O</sub> = 5mA		-0.6		mV/°C
Output Noise Voltage	V <sub>N</sub>	f = 10Hz to 100KHz T <sub>A</sub> = +25°C		175		μV
Ripple Rejection	RR	f = 120Hz ΔV <sub>I</sub> = 10V	54	60		dB
Dropout Voltage	V <sub>D</sub>	T <sub>J</sub> = +25°C I <sub>O</sub> = 1A		2		V
Short Circuit Current	I <sub>SC</sub>	T <sub>J</sub> = +25°C, V <sub>I</sub> = -35V		300		mA
Peak Current	I <sub>PK</sub>	T <sub>J</sub> = +25°C		2.2		A

\* Load and line regulation are specified at constant junction temperature. Changes in V<sub>O</sub> due to heating effects must be taken into account separately. Pulse testing with low duty is used.

**LM7912 ELECTRICAL CHARACTERISTICS**(V<sub>I</sub> = 18V, I<sub>O</sub> = 500mA, 0°C ≤ T<sub>J</sub> ≤ +125°C, C<sub>I</sub> = 2.2μF, C<sub>O</sub> = 1μF, unless otherwise specified.)

Characteristic	Symbol	Test Conditions	Min	Typ	Max	Unit
Output Voltage	V <sub>O</sub>	T <sub>J</sub> = +25°C	-11.5	-12	-12.5	V
		I <sub>O</sub> = 5mA to 1A, P <sub>O</sub> 15W V <sub>I</sub> = -15.5 to -27V	-11.4	-12	-12.6	
Line Regulation	ΔV <sub>O</sub>	T <sub>J</sub> = 25°C	V <sub>I</sub> = -14.5 to -30V	12	240	mV
			V <sub>I</sub> = -16 to -22V	6	120	
Load Regulation	ΔV <sub>O</sub>	T <sub>J</sub> = +25°C		12	240	mV
		I <sub>O</sub> = 5mA to 1.5A				
Quiescent Current	I <sub>Q</sub>	T <sub>J</sub> = +25°C		3	6	mA
			I <sub>O</sub> = 250 to 750mA		4	
Quiescent Current Change	ΔI <sub>Q</sub>	I <sub>O</sub> = 5mA to 1A		0.05	0.5	mA
			V <sub>I</sub> = -15 to -30V		0.1	
Temperature Coefficient of V <sub>O</sub>	ΔV <sub>O</sub> /ΔT	I <sub>O</sub> = 5mA		-0.8		mV/°C
Output Noise Voltage	V <sub>N</sub>	f = 10Hz to 100KHz T <sub>A</sub> = +25°C		200		μV
Ripple Rejection	RR	f = 120Hz ΔV <sub>I</sub> = 10V	54	60		dB
Dropout Voltage	V <sub>D</sub>	T <sub>J</sub> = +25°C I <sub>O</sub> = 1A		2		V
Short Circuit Current	I <sub>SC</sub>	T <sub>J</sub> = +25°C, V <sub>I</sub> = -35V		300		mA
Peak Current	I <sub>PK</sub>	T <sub>J</sub> = +25°C		2.2		A

\* Load and line regulation are specified at constant junction temperature. Changes in V<sub>O</sub> due to heating effects must be taken into account separately. Pulse testing with low duty is used.

**LM7915 ELECTRICAL CHARACTERISTICS**(V<sub>I</sub> = 23V, I<sub>O</sub> = 500mA, 0°C ≤ T<sub>J</sub> ≤ +125°C, C<sub>I</sub> = 2.2μF, C<sub>O</sub> = 1μF, unless otherwise specified.)

Characteristic	Symbol	Test Conditions	Min	Typ	Max	Unit
Output Voltage	V <sub>O</sub>	T <sub>J</sub> = +25°C	-14.4	-15	-15.6	V
		I <sub>O</sub> = 5mA to 1A, P <sub>O</sub> = 15W V <sub>I</sub> = -18 to -30V	-14.25	-15	-15.75	
Line Regulation	ΔV <sub>O</sub>	T <sub>J</sub> = 25°C	V <sub>I</sub> = -17.5 to -30V	12	300	mV
			V <sub>I</sub> = -20 to -26V	6	150	
Load Regulation	ΔV <sub>O</sub>	T <sub>J</sub> = +25°C		12	300	mV
		I <sub>O</sub> = 5mA to 1.5A		4	150	
Quiescent Current	I <sub>Q</sub>	T <sub>J</sub> = +25°C		3	6	mA
Quiescent Current Change	ΔI <sub>Q</sub>	I <sub>O</sub> = 5mA to 1A		0.05	0.5	mA
		V <sub>I</sub> = -18.5 to -30V		0.1	1	
Temperature Coefficient of V <sub>O</sub>	ΔV <sub>O</sub> /ΔT	I <sub>O</sub> = 5mA		-0.9		mV/°C
Output Noise Voltage	V <sub>N</sub>	f = 10Hz to 100KHz T <sub>A</sub> = +25°C		250		μV
Ripple Rejection	RR	f = 120Hz ΔV <sub>I</sub> = 10V	54	60		dB
Dropout Voltage	V <sub>D</sub>	T <sub>J</sub> = +25°C I <sub>O</sub> = 1A		2		V
Short Circuit Current	I <sub>SC</sub>	T <sub>J</sub> = +25°C, V <sub>I</sub> = -35V		300		mA
Peak Current	I <sub>PK</sub>	T <sub>J</sub> = +25°C		2.2		A

\* Load and line regulation are specified at constant junction temperature. Changes in V<sub>O</sub> due to heating effects must be taken into account separately. Pulse testing with low duty is used.

**LM7918 ELECTRICAL CHARACTERISTICS**(V<sub>I</sub> = 27V, I<sub>O</sub> = 500mA, 0°C ≤ T<sub>J</sub> ≤ +125°C, C<sub>I</sub> = 2.2μF, C<sub>O</sub> = 1μF, unless otherwise specified.)

Characteristic	Symbol	Test Conditions	Min	Typ	Max	Unit
Output Voltage	V <sub>O</sub>	T <sub>J</sub> = +25°C	-17.3	-18	-18.7	V
		I <sub>O</sub> = 5mA to 1A, P <sub>O</sub> = 15W V <sub>I</sub> = -22.5 to -33V	-17.1	-18	-18.9	
Line Regulation	ΔV <sub>O</sub>	T <sub>J</sub> = 25°C	V <sub>I</sub> = -21 to -33V	15	360	mV
			V <sub>I</sub> = -24 to -30V	8	180	
Load Regulation	ΔV <sub>O</sub>	T <sub>J</sub> = +25°C I <sub>O</sub> = 5mA to 1.5A		15	360	mV
		T <sub>J</sub> = +25°C I <sub>O</sub> = 250 to 750mA		5	180	
Quiescent Current	I <sub>Q</sub>	T <sub>J</sub> = +25°C		3	6	mA
Quiescent Current Change	ΔI <sub>Q</sub>	I <sub>O</sub> = 5mA to 1A			0.5	mA
		V <sub>I</sub> = -22 to -33V			1	
Temperature Coefficient of V <sub>O</sub>	ΔV <sub>O</sub> /ΔT	I <sub>O</sub> = 5mA		-1		mV/°C
Output Noise Voltage	V <sub>N</sub>	f = 10Hz to 100KHz T <sub>A</sub> = +25°C		300		μV
Ripple Rejection	RR	f = 120Hz ΔV <sub>I</sub> = 10V	54	60		dB
Dropout Voltage	V <sub>D</sub>	T <sub>J</sub> = +25°C I <sub>O</sub> = 1A		2		V
Short Circuit Current	I <sub>SC</sub>	T <sub>J</sub> = +25°C, V <sub>I</sub> = -35V		300		mA
Peak Current	I <sub>PK</sub>	T <sub>J</sub> = +25°C		2.2		A

\* Load and line regulation are specified at constant junction temperature. Changes in V<sub>O</sub> due to heating effects must be taken into account separately. Pulse testing with low duty is used.



**LM7924 ELECTRICAL CHARACTERISTICS**(V<sub>I</sub> = 33V, I<sub>O</sub> = 500mA, 0°C ≤ T<sub>J</sub> ≤ +125°C, C<sub>I</sub> = 2.2μF, C<sub>O</sub> = 1μF, unless otherwise specified.)

Characteristic	Symbol	Test Conditions	Min	Typ	Max	Unit
Output Voltage	V <sub>O</sub>	T <sub>J</sub> = +25°C	- 23	- 24	- 25	V
		I <sub>O</sub> = 5mA to 1A, P <sub>O</sub> ≤ 15W V <sub>I</sub> = -27 to -38V	- 22.8	- 24	- 25.2	
Line Regulation	ΔV <sub>O</sub>	T <sub>J</sub> = 25°C	V <sub>I</sub> = - 27 to - 38V	15	480	mV
			V <sub>I</sub> = - 30 to - 36V	8	180	
Load Regulation	ΔV <sub>O</sub>	T <sub>J</sub> = +25°C I <sub>O</sub> = 5mA to 1.5A		15	480	mV
		T <sub>J</sub> = + 25°C I <sub>O</sub> = 250 to 750mA		5	240	
Quiescent Current	I <sub>Q</sub>	T <sub>J</sub> = + 25°C		3	6	mA
Quiescent Current Change	ΔI <sub>Q</sub>	I <sub>O</sub> = 5mA to 1A			0.5	mA
		V <sub>I</sub> = -27 to -38V			1	
Temperature Coefficient of V <sub>O</sub>	ΔV <sub>O</sub> /ΔT	I <sub>O</sub> = 5mA		-1		mV/°C
Output Noise Voltage	V <sub>N</sub>	f = 10Hz to 100KHz T <sub>A</sub> = + 25°C		400		μV
Ripple Rejection	RR	f = 120Hz ΔV <sub>I</sub> = 10V	54	60		dB
Dropout Voltage	V <sub>D</sub>	T <sub>J</sub> = +25°C I <sub>O</sub> = 1A		2		V
Short Circuit Current	I <sub>SC</sub>	T <sub>J</sub> = + 25°C, V <sub>I</sub> = -35V		300		mA
Peak Current	I <sub>PK</sub>	T <sub>J</sub> = +25°C		2.2		A

\* Load and line regulation are specified at constant junction temperature. Changes in V<sub>O</sub> due to heating effects must be taken into account separately. Pulse testing with low duty is used.

**LM7905A ELECTRICAL CHARACTERISTICS**(V<sub>I</sub> = 10V, I<sub>O</sub> = 500mA, 0°C ≤ T<sub>J</sub> ≤ +125°C, C<sub>I</sub> = 2.2μF, C<sub>O</sub> = 1μF, unless otherwise specified.)

Characteristic	Symbol	Test Conditions	Min	Typ	Max	Unit
Output Voltage	V <sub>O</sub>	T <sub>J</sub> = +25°C	-4.9	-5.0	-5.1	V
		I <sub>O</sub> = 5mA to 1A, P <sub>O</sub> = 15W V <sub>I</sub> = -7 to -20V	-4.8	-5.0	-5.2	
Line Regulation	ΔV <sub>O</sub>	T <sub>J</sub> = +25°C	V <sub>I</sub> = -7 to -20V I <sub>O</sub> = 1A	5	50	mV
			V <sub>I</sub> = -8 to -12V I <sub>O</sub> = 1A	2	25	
		V <sub>I</sub> = -7.5 to -25V	7	50		
		V <sub>I</sub> = -8 to -12V I <sub>O</sub> = 1A	7	50		
Load Regulation	ΔV <sub>O</sub>	I <sub>O</sub> = 5mA to 1.5A		10	100	mV
		T <sub>J</sub> = +25°C I <sub>O</sub> = 250 to 750mA		3	50	
Quiescent Current	I <sub>Q</sub>	T <sub>J</sub> = +25°C		3	6	mA
Quiescent Current Change	ΔI <sub>Q</sub>	I <sub>O</sub> = 5mA to 1A		0.05	0.5	mA
		V <sub>I</sub> = -8 to -25V		0.1	0.8	
Temperature Coefficient of V <sub>D</sub>	ΔV <sub>O</sub> /ΔT	I <sub>O</sub> = 5mA		-0.4		mV/°C
Output Noise Voltage	V <sub>N</sub>	f = 10Hz to 100KHz T <sub>A</sub> = +25°C		40		μV
Ripple Rejection	RR	f = 120Hz, I <sub>O</sub> = -35V ΔV <sub>I</sub> = 10V	54	60		dB
Dropout Voltage	V <sub>D</sub>	T <sub>J</sub> = +25°C I <sub>O</sub> = 1A		2		V
Short Circuit Current	I <sub>SC</sub>	T <sub>J</sub> = +25°C, V <sub>I</sub> = -35V		300		mA
Peak Current	I <sub>PK</sub>	T <sub>J</sub> = +25°C		2.2		A

\* Load and line regulation are specified at constant junction temperature. Changes in V<sub>O</sub> due to heating effects must be taken into account separately. Pulse testing with low duty is used.

**LM7912A ELECTRICAL CHARACTERISTICS**(V<sub>I</sub> = 18V, I<sub>O</sub> = 500mA, 0°C ≤ T<sub>J</sub> ≤ +125°C, C<sub>I</sub> = 2.2μF, C<sub>O</sub> = 1μF, unless otherwise specified.)

Characteristic	Symbol	Test Conditions	Min	Typ	Max	Unit	
Output Voltage	V <sub>O</sub>	T <sub>J</sub> = +25°C	-11.75	-12	-12.25	V	
		I <sub>O</sub> = 5mA to 1A, P <sub>O</sub> = 15W V <sub>I</sub> = -15.5 to -27V	-11.5	-12	-12.5		
Line Regulation	ΔV <sub>O</sub>	T <sub>J</sub> = +25°C	V <sub>I</sub> = -14.5 to -30V		12	240	mV
			V <sub>I</sub> = -16 to -22V		6	120	
Load Regulation	ΔV <sub>O</sub>	T <sub>J</sub> = +25°C		12	240	mV	
		I <sub>O</sub> = 5mA to 1.5A		4	120		
Quiescent Current	I <sub>Q</sub>	T <sub>J</sub> = +25°C		3	6	mA	
Quiescent Current Change	ΔI <sub>Q</sub>	I <sub>O</sub> = 5mA to 1A		0.05	0.5	mA	
		V <sub>I</sub> = -15 to -30V		0.1	1		
Temperature Coefficient of V <sub>O</sub>	ΔV <sub>O</sub> /ΔT	I <sub>O</sub> = 5mA		-0.8		mV/°C	
Output Noise Voltage	V <sub>N</sub>	f = 10Hz to 100KHz T <sub>A</sub> = +25°C		200		μV	
Ripple Rejection	RR	f = 120Hz ΔV <sub>I</sub> = 10V	54	60		dB	
Dropout Voltage	V <sub>D</sub>	T <sub>J</sub> = +25°C I <sub>O</sub> = 1A		2		V	
Short Circuit Current	I <sub>SC</sub>	T <sub>J</sub> = +25°C, V <sub>I</sub> = -35V		300		mA	
Peak Current	I <sub>PK</sub>	T <sub>J</sub> = +25°C		2.2		A	

\* Load and line regulation are specified at constant junction temperature. Changes in V<sub>O</sub> due to heating effects must be taken into account separately. Pulse testing with low duty is used.

**LM7915A ELECTRICAL CHARACTERISTICS**(V<sub>I</sub> = 23V, I<sub>O</sub> = 500mA, 0°C ≤ T<sub>J</sub> ≤ +125°C, C<sub>I</sub> = 2.2μF, C<sub>O</sub> = 1μF, unless otherwise specified.)

Characteristic	Symbol	Test Conditions	Min	Typ	Max	Unit
Output Voltage	V <sub>O</sub>	T <sub>J</sub> = +25°C	-14.7	-15	-15.3	V
		I <sub>O</sub> = 5mA to 1A, P <sub>O</sub> 15W V <sub>I</sub> = -18 to -30V	-14.4	-15	-15.6	
Line Regulation	ΔV <sub>O</sub>	T <sub>J</sub> = +25°C	V <sub>I</sub> = -17.5 to -30V	12	300	mV
			V <sub>I</sub> = -20 to -26V	6	150	
Load Regulation	ΔV <sub>O</sub>	T <sub>J</sub> = +25°C I <sub>O</sub> = 5mA to 1.5A		12	300	mV
			T <sub>J</sub> = +25°C I <sub>O</sub> = 250 to 750mA		4	
Quiescent Current	I <sub>Q</sub>	T <sub>J</sub> = +25°C		3	6	mA
Quiescent Current Change	ΔI <sub>Q</sub>	I <sub>O</sub> = 5mA to 1A V <sub>I</sub> = -18.5 to -30V		0.05	0.5	mA
				0.1	1	
Temperature Coefficient of V <sub>O</sub>	ΔV <sub>O</sub> /ΔT	I <sub>O</sub> = 5mA		-0.9		mV/°C
Output Noise Voltage	V <sub>N</sub>	f = 10Hz to 100KHz T <sub>A</sub> = +25°C		250		μV
Ripple Rejection	RR	f = 120Hz ΔV <sub>I</sub> = 10V	54	60		dB
Dropout Voltage	V <sub>D</sub>	T <sub>J</sub> = +25°C I <sub>O</sub> = 1A		2		V
Short Circuit Current	I <sub>SC</sub>	T <sub>J</sub> = +25°C, V <sub>I</sub> = -35V		300		mA
Peak Current	I <sub>PK</sub>	T <sub>J</sub> = +25°C		2.2		A

\* Load and line regulation are specified at constant junction temperature. Changes in V<sub>O</sub> due to heating effects must be taken into account separately. Pulse testing with low duty is used.

TYPICAL PERFORMANCE CHARACTERISTICS

Fig.1 Output Voltage




Fig. 2 Load Regulation




Fig.3 Quiescent Current




Fig. 4 Dropout Voltage






Fig.5 Short Circuit Current




## TYPICAL APPLICATIONS

Fig. 6 Negative Fixed output regulator

**Notes:**

- (1) To specify an output voltage, substitute voltage value for "XX"
- (2) Required for stability. For value given, capacitor must be solid tantalum. If aluminum electrolytics are used, at least ten times value shown should be selected.  $C_i$  is required if regulator is located an appreciable distance from power supply filter.
- (3) To improve transient response. If large capacitors are used, a high current diode from input to output (1N4001 or similar) should be introduced to protect the device from momentary input short circuit.

Fig. 7 Split power supply ( $\pm 12V/1A$ )

\*: Against potential latch-up problems.

## TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACE <sup>x</sup> ™	ISOPLANAR™	TinyLogic™
CoolFET™	MICROWIRE™	UHC™
CROSSVOLT™	POP™	VCX™
E <sup>2</sup> CMOS™	PowerTrench®	
FACT™	QFET™	
FACT Quiet Series™	QS™	
FAST®	Quiet Series™	
FAST <sub>r</sub> ™	SuperSOT™-3	
GTO™	SuperSOT™-6	
HiSeC™	SuperSOT™-8	

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.  
As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.