



MC80N10B

主要参数 MAIN CHARACTERISTICS

I_D	60.0A
V_{DSS}	100V
$R_{dson-max}$ (@ $V_{gs}=10V$)	9.2m Ω
Q_g-typ	39.7nC

用途

- LED 应用
- 负载开关
- 同步整流领域 DC/DC 与 AC/DC 转换

产品特性

- 沟槽功率 MOSFET 技术
- 低 $R_{DS(ON)}$
- 低栅极电荷
- 开关速度快



APPLICATIONS

- LED applications
- Load Switch
- Synchronous Rectification in DC/DC and AC/DC Converters

FEATURES

- Trench Power MOSFET Technology
- Low $R_{DS(ON)}$
- Low gate charge
- Fast-switching

封装 Package



订货信息 ORDER MESSAGE

订货型号 Order codes				印 记 Marking	封 装 Package
有卤-条管 Halogen-Tube	无卤-条管 Halogen-Free-Tube	有卤-编带 Halogen-Reel	无卤-编带 Halogen-Free-Reel		
N/A	N/A	N/A	MC80N10B-AA-AR	MC80N10B	PDFN5*6





绝对最大额定值 ABSOLUTE RATINGS (Tc=25°C)

项 目 Parameter	符 号 Symbol	数 值 Value	单 位 Unit
		MC80N10B	
最高漏极-源极直流电压 Drain-Source Voltage	V_{DSS}	100	V
连续漏极电流 Drain Current -continuous	I_D T=25°C	60*	A
	I_D T=100°C	48*	A
最大脉冲漏极电流 (注1) Drain Current - pulse (note 1)	I_{DM}	240*	A
最高栅源电压 Gate-Source Voltage	V_{GSS}	+20/-12	V
单脉冲雪崩能量 (注2) Single Pulsed Avalanche Energy (note 2)	E_{AS}	211	mJ
雪崩电流 (注1) Avalanche Current (note 1)	I_{AS}	65	A
耗散功率 Power Dissipation	P_D Tc=25°C -Derate above 25°C	62.5	W
		0.5	W/°C
最高结温及存储温度 Operating and Storage Temperature Range	T_J, T_{STG}	-55~+150	°C

*漏极电流由最高结温限制

*Drain current limited by maximum junction temperature





电特性 ELECTRICAL CHARACTERISTICS

项 目 Parameter	符 号 Symbol	测试条件 Tests conditions	最小 Min	典型 Typ	最大 Max	单 位 Units
关态特性 Off –Characteristics						
漏—源击穿电压 Drain-Source Voltage	BV_{DSS}	$I_D=250\mu A, V_{GS}=0V$	100	-	-	V
零栅压下漏极漏电流 Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=100V, V_{GS}=0V,$ $T_C=25^\circ C$	-	-	1	μA
		$V_{DS}=80V, V_{GS}=0V,$ $T_C=125^\circ C$	-	-	10	μA
正向栅极体漏电流 Gate-body leakage current, forward	I_{GSSF}	$V_{DS}=0V, V_{GS}=20V$	-	-	100	nA
反向栅极体漏电流 Gate-body leakage current, reverse	I_{GSSR}	$V_{DS}=0V, V_{GS}=-20V$	-	-	-100	nA
通态特性 On-Characteristics						
阈值电压 Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D=250\mu A$	1.0	1.6	2.5	V
静态导通电阻 Static Drain-Source On-Resistance	$R_{DS(ON)}$	$V_{GS}=10V, I_D=15A$	-	7.6	9.2	m Ω
		$V_{GS}=4.5V, I_D=8A$	-	10.8	15	m Ω
正向跨导 Forward Transconductance	g_{fs}	$V_{DS} = 10V, I_D=3A$ (note 4)	-	11	-	S
动态特性 Dynamic Characteristics						
输入电容 Input capacitance	C_{iss}	$V_{DS}=25V,$ $V_{GS}=0V,$ $f=1.0MHz$	-	2500	4000	pF
输出电容 Output capacitance	C_{oss}		-	690	1000	pF
反向传输电容 Reverse transfer capacitance	C_{rss}		-	120	180	pF
栅电阻 Gate resistance	R_g	V_{DS} open, $V_{GS}=0V, f=1.0MHz$		1.60		Ω





电特性 ELECTRICAL CHARACTERISTICS

开关特性 Switching Characteristics						
延迟时间 Turn-On delay time	$t_d(\text{on})$	$V_{DD}=50V, I_D=1A, R_G=6\Omega$ (note 3, 4)	-	14.6	30	ns
上升时间 Turn-On rise time	t_r		-	21.5	44	ns
延迟时间 Turn-Off delay time	$t_d(\text{off})$		-	54	108	ns
下降时间 Turn-Off Fall time	t_f		-	84.3	168	ns
栅极电荷总量 Total Gate Charge	Q_g	$V_{DS}=80V,$ $I_D=8.5A$ $V_{GS}=10V$ (note 3, 4)	-	39.7	80	nC
栅-源电荷 Gate-Source charge	Q_{gs}		-	5.4	10	nC
栅-漏电荷 Gate-Drain charge	Q_{gd}		-	11.2	22	nC
漏-源二极管特性及最大额定值 Drain-Source Diode Characteristics and Maximum Ratings						
正向最大连续电流 Maximum Continuous Drain -Source Diode Forward Current	I_S	$T_C=25^\circ\text{C}$	-	-	60	A
正向最大脉冲电流 Maximum Pulsed Drain-Source Diode Forward Current	I_{SM}	$T_C=25^\circ\text{C}$	-	-	240	A
正向压降 Drain-Source Diode Forward Voltage	V_{SD}	$T_J=25^\circ\text{C}, V_{GS}=0V, I_S=25A$	-	-	1.0	V

热特性 THERMAL CHARACTERISTIC

项 目 Parameter	符 号 Symbol	最大 Max	单 位 Unit
		MC80N10B	
结到环境的热阻 Thermal Resistance, Junction to Ambient	$R_{th(j-A)}$	2	$^\circ\text{C}/\text{W}$
结到管壳的热阻 Thermal Resistance, Junction to Case	$R_{th(j-C)}$	75	$^\circ\text{C}/\text{W}$

注释:

- 1: 脉冲宽度由最高结温限制
- 2: $I_{AS}=65A, V_{DD}=50V, V_{GS}=10V, L=0.1mH,$
 $R_G=25\Omega, \text{起始结温 } T_J=25^\circ\text{C}$
- 3: 脉冲测试: 脉冲宽度 $\leq 300\mu\text{s}$, 占空比 $\leq 2\%$
- 4: 基本与工作温度无关

Notes:


- 1: Pulse width limited by maximum junction temperature
- 2: $I_{AS}=65A, V_{DD}=50V, V_{GS}=10V, L=0.1mH,$
 $R_G=25\Omega, \text{Starting } T_J=25^\circ\text{C}$
- 3: Pulse Test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$
- 4: Essentially independent of operating temperature






特征曲线 ELECTRICAL CHARACTERISTICS (curves)


Continuous Drain Current vs. Temperature




On-Resistance Variation vs. Temperature




Gate threshold Variation vs. Temperature




Gate Charge Characteristics



Transient Thermal Curve Response Curve




Maximum Safe Operation Area





PDFN5*6

单位 Unit: mm



SYMBOL	mm	
	MIN	MAX
A	0.95	1.25
C	0.1	0.4
b	0.25	0.55
D1	4.9	5.5
D2	3.75	4.3
e	1.27 BSC	
E1	5.9	6.4
E2	5.6	6.1
E3	3.47	3.97
E4	0.31	0.61
L	0.25	0.75
H	0.35	0.65
K	1.13	1.53



**注意事项**

- 1.吉林华微电子股份有限公司的产品销售分为直销和销售代理，无论哪种方式，订货时请与公司核实。
- 2.购买时请认清公司商标，如有疑问请与公司本部联系。
- 3.在电路设计时请不要超过器件的绝对最大额定值，否则会影响整机的可靠性。
- 4.本说明书如有版本变更不另外告知

NOTE

1. Jilin Sino-microelectronics co., Ltd sales its product either through direct sales or sales agent , thus, for customers, when ordering , please check with our company.
2. We strongly recommend customers check carefully on the trademark when buying our product, if there is any question, please don't be hesitate to contact us.
3. Please do not exceed the absolute maximum ratings of the device when circuit designing.
4. Jilin Sino-microelectronics co., Ltd reserves the right to make changes in this specification sheet and is subject to change without prior notice.

联系方式**吉林华微电子股份有限公司**

公司地址：吉林省吉林市深圳街 99 号

邮编：132013

总机：86-432-64678411

传真：86-432-64665812

网址：www.hwdz.com.cn

市场营销部

地址：吉林省吉林市深圳街 99 号

邮编：132013

电话：86-432-64675588

64675688

64678411

传真：86-432-64671533

CONTACT**JILIN SINO-MICROELECTRONICS CO., LTD.**

ADD: No.99 Shenzhen Street, Jilin City, Jilin Province, China.

Post Code: 132013

Tel: 86-432-64678411

Fax: 86-432-64665812

Web Site: www.hwdz.com.cn

MARKET DEPARTMENT

ADD: No.99 Shenzhen Street, Jilin City, Jilin Province, China.

Post Code: 132013

Tel: 86-432-64675588

64675688

64678411

Fax: 86-432-64671533

