


P- Channel 30-V (D-S) MOSFET

GENERAL DESCRIPTION

The ME95P03 is the P-Channel logic enhancement mode power field effect transistors are produced using high cell density, DMOS trench technology. This high density process is especially tailored to minimize on-state resistance. These devices are particularly suited for low voltage application such as cellular phone and notebook computer power management and other battery powered circuits , and low in-line power loss are needed in a very small outline surface mount package.

PIN CONFIGURATION




FEATURES

- $R_{DS(ON)} \leq 5.6m\Omega @ V_{GS} = -20V$
- $R_{DS(ON)} \leq 6m\Omega @ V_{GS} = -10V$
- $R_{DS(ON)} \leq 8m\Omega @ V_{GS} = -4.5V$
- Super high density cell design for extremely low $R_{DS(ON)}$
- Exceptional on-resistance and maximum DC current capability

APPLICATIONS

- Power Management in Note book
- DC/DC Converter
- Load Switch
- LCD Display inverter



P-Channel MOSFET

Ordering Information: ME95P03 (Pb-free)

ME95P03-G (Green product-Halogen free)

Absolute Maximum Ratings (TA=25°C Unless Otherwise Noted)

Parameter	Symbol	Maximum Ratings	Unit
Drain-Source Voltage	V_{DS}	-30	V
Gate-Source Voltage	V_{GS}	± 25	V
Continuous Drain Current	I_D	$T_C = 25^\circ C$	-68.2
		$T_C = 70^\circ C$	-54.6
Pulsed Drain Current	I_{DM}	-273	A
Maximum Power Dissipation	P_D	$T_C = 25^\circ C$	41.7
		$T_C = 70^\circ C$	26.7
Operating Junction Temperature	T_J	150	°C
Storage Temperature Range	T_{stg}	-55 to 150	°C
Thermal Resistance-Junction to Case*	$R_{\theta JC}$	3	°C/W

*The device mounted on 1in² FR4 board with 2 oz copper.



P-Channel 30-V (D-S) MOSFET

Electrical Characteristics (T_A=25°C Unless Otherwise Specified)

Symbol	Parameter	Limit	Min	Typ	Max	Unit
STATIC						
V _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =-250 μA	-30			V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =-250 μA	-1		-3	V
I _{GSS}	Gate Leakage Current	V _{DS} =0V, V _{GS} =±25V			±100	nA
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =-24V, V _{GS} =0V			-1	μA
R _{DS(on)}	Drain-Source On-State Resistance ^a	V _{GS} =-20V, I _D = -20A		4.5	5.6	mΩ
		V _{GS} =-10V, I _D = -20A		5	6	
		V _{GS} =-4.5V, I _D = -16A		6	8	
V _{SD}	Diode Forward Voltage	I _S =-1A, V _{GS} =0V		-0.7	-1.2	V
DYNAMIC						
Q _g	Total Gate Charge	V _{DS} =-15V, V _{GS} =-10V, I _D =-20A		139		nC
Q _g	Total Gate Charge			69.7		
Q _{gs}	Gate-Source Charge	V _{DS} =-15V, V _{GS} =-4.5V, I _D =-20A		27		
Q _{gd}	Gate-Drain Charge			36.6		
C _{iss}	Input capacitance	V _{DS} =-15V, V _{GS} =0V, F=1MHz		6670		pF
C _{oss}	Output Capacitance			813		
C _{rss}	Reverse Transfer Capacitance			716		
t _{d(on)}	Turn-On Delay Time	V _{DS} =-15V, R _L =15Ω V _{GEN} =-10V, R _G =3Ω		66.5		ns
t _r	Turn-On Rise Time			26.3		
t _{d(off)}	Turn-Off Delay Time			224		
t _f	Turn-Off Fall Time			63.5		

Notes: a. Pulse test: pulse width ≤ 300us, duty cycle ≤ 2%, Guaranteed by design, not subject to production testing.


b. Matsuki Electric/ Force mos reserves the right to improve product design, functions and reliability without notice.

DCC
正式發行


P-Channel 30-V (D-S) MOSFET

Typical Characteristics (T_J = 25°C Noted)


On Resistance vs. Junction Temperature




On Resistance vs. Drain Current




Capacitance




On Resistance vs. Gate-to-Source Voltage



Threshold Voltage




On-Region Characteristics




P- Channel 30-V (D-S) MOSFET

Typical Characteristics (T_J =25°C Noted)


Gate Charge





Body-diode characteristics




Maximum Forward Biased Safe Operating Area



Normalized Thermal Transient Impedance, Junction-to-Case



TO252-3L Package Outline



SYMBOL	MIN	MAX
A	2.10	2.50
B	0.40	0.90
C	0.40	0.90
D	5.30	6.30
D1	2.20	2.90
E	6.30	6.75
E1	4.80	5.50
L1	0.90	1.80
L2	0.50	1.10
L3	0.00	0.20
H	8.90	10.40
P	2.30 BSC	

