


October 2004



www.DataSheet4U.com

### Ordering Information

MF228	TO-46 Package
MF228 ST	ST Housing
MF228 SC	SC Housing
MF228 SMA	SMA Housing
MF228 FC	FC Housing

**-40°C to +85°C**

Note: Rated Fiber coupled power apply only on the TO-46 package, for housing options fiber coupled power is typically 10% less

### Features



- 850 nm Surface-Emitting LED
- 70 MHz Bandwidth
- Uniform phase distribution
- Designed for 200/280 μm fiber

### Applications

- Electronic Distance Measurement (EDM)
- Sensors
- Avionics

### Description

This device is capable of providing high power into large-core fiber over a wide temperature range. Thanks to its very uniform phase distribution of the optical power, it is ideal for Electronic Distance Measurement equipment.


**Figure 1 - Pin Diagram**

**Figure 2 - Functional Schematic**

**Optical and Electrical Characteristics - Case Temperature 25°C**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition	
Fiber-Coupled Power (Figures 3, 4, and 5) (Table 1)	$P_{\text{fiber}}$	1000	1200		$\mu\text{W}$	$I_F = 100 \text{ mA}$ (Note 1)	Fiber: 200/280 $\mu\text{m}$ Step Index NA = 0.24
Rise and Fall Time (10-90%)	$t_r, t_f$		7	10	ns	$I_F = 100 \text{ mA}$ (no bias)	
Bandwidth (3dB <sub>ej</sub> )	$f_c$		50		MHz	$I_F = 100 \text{ mA}$	
Peak Wavelength	$\lambda_p$	830	850	870	nm	$I_F = 100 \text{ mA}$	
Spectral Width (FWHM)	$\Delta\lambda$		50		nm	$I_F = 100 \text{ mA}$	
Forward Voltage (Figure 7)	$V_F$		1.8	2.2	V	$I_F = 100 \text{ mA}$	
Reverse Current	$I_R$			20	$\mu\text{A}$	$V_R = 1 \text{ V}$	
Capacitance	C		250		pF	$V_R = 0 \text{ V}, f = 1 \text{ MHz}$	

Note 1: Measured at the exit of 100 meters of fiber.

**Absolute Maximum Ratings**

Parameter	Symbol	Limit
Storage Temperature	$T_{\text{stg}}$	-55 to +125°C
Operating Temperature (derating: Figure 6)	$T_{\text{op}}$	-40 to +85°C
Electrical Power Dissipation (derating: Figure 6)	$P_{\text{tot}}$	250 mW
Continuous Forward Current (f<10 kHz)	$I_F$	110 mA
Peak Forward Current (duty cycle<50%, f>1 MHz)	$I_{\text{FRM}}$	180 mA
Reverse Voltage	$V_R$	1.5 V
Soldering Temperature (2mm from the case for 10 sec.)	$T_{\text{slid}}$	260°C

**Thermal Characteristics**

Parameter	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance - Infinite Heat Sink	$R_{\text{thjc}}$			100	°C/W
Thermal Resistance - No Heat Sink	$R_{\text{thja}}$			400	°C/W
Temperature Coefficient - Optical Power	$dP/dT_j$		-0.4		%/°C
Temperature Coefficient - Wavelength	$d\lambda/dT_j$		0.3		nm/°C

**Typical Fiber-Coupled Power**

Core Diameter/Cladding Diameter Numerical Aperture				
50/125 $\mu\text{m}$ 0.20	62.5/125 $\mu\text{m}$ 0.275	100/140 $\mu\text{m}$ 0.29	200/230 $\mu\text{m}$ 0.37	200/280 $\mu\text{m}$ 0.24
60 $\mu\text{W}$	150 $\mu\text{W}$	450 $\mu\text{W}$	1300 $\mu\text{W}$	1200 $\mu\text{W}$




Figure 3 - Relative Fiber-coupled Power vs. z - Axial Displacement of Fiber



Figure 4 - Relative Fiber-coupled Power vs. r - Radial Displacement of Fiber




Figure 5 - Relative Fiber-coupled Power vs. Forward Current




Figure 6 - Max. Electrical Power Disapation vs. Operating Temperature




Figure 7 - Forward Current vs. Forward Voltage




Figure 8 - Peak Forward Current vs. Operating Temperature



**For more information about all Zarlink products  
visit our Web Site at**

[www.DataSheet4U.com](http://www.DataSheet4U.com)

**[www.zarlink.com](http://www.zarlink.com)**

Information relating to products and services furnished herein by Zarlink Semiconductor Inc. or its subsidiaries (collectively "Zarlink") is believed to be reliable. However, Zarlink assumes no liability for errors that may appear in this publication, or for liability otherwise arising from the application or use of any such information, product or service or for any infringement of patents or other intellectual property rights owned by third parties which may result from such application or use. Neither the supply of such information or purchase of product or service conveys any license, either express or implied, under patents or other intellectual property rights owned by Zarlink or licensed from third parties by Zarlink, whatsoever. Purchasers of products are also hereby notified that the use of product in certain ways or in combination with Zarlink, or non-Zarlink furnished goods or services may infringe patents or other intellectual property rights owned by Zarlink.

This publication is issued to provide information only and (unless agreed by Zarlink in writing) may not be used, applied or reproduced for any purpose nor form part of any order or contract nor to be regarded as a representation relating to the products or services concerned. The products, their specifications, services and other information appearing in this publication are subject to change by Zarlink without notice. No warranty or guarantee express or implied is made regarding the capability, performance or suitability of any product or service. Information concerning possible methods of use is provided as a guide only and does not constitute any guarantee that such methods of use will be satisfactory in a specific piece of equipment. It is the user's responsibility to fully determine the performance and suitability of any equipment using such information and to ensure that any publication or data used is up to date and has not been superseded. Manufacturing does not necessarily include testing of all functions or parameters. These products are not suitable for use in any medical products whose failure to perform may result in significant injury or death to the user. All products and materials are sold and services provided subject to Zarlink's conditions of sale which are available on request.

Purchase of Zarlink's I<sup>2</sup>C components conveys a licence under the Philips I<sup>2</sup>C Patent rights to use these components in and I<sup>2</sup>C System, provided that the system conforms to the I<sup>2</sup>C Standard Specification as defined by Philips.

Zarlink, ZL and the Zarlink Semiconductor logo are trademarks of Zarlink Semiconductor Inc.

Copyright Zarlink Semiconductor Inc. All Rights Reserved.

**TECHNICAL DOCUMENTATION - NOT FOR RESALE**