



MGBR30L50C

DIODE

DUAL MOS GATED BARRIER RECTIFIER



DESCRIPTION

The UTC **MGBR30L50C** is a dual mos gated barrier rectifiers, it uses UTC's advanced technology to provide customers with low forward voltage drop and high switching speed, etc.

FEATURES

- * Low forward voltage drop
- * High switching speed

SYMBOL



TO-220


ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
MGBR30L50CL-TA3-T	MGBR30L50CG-TA3-T	TO-220	A	K	A	Tube

Note: Pin Assignment: A: Anode, K: Cathode

<p>MGBR30L50CL-TA3-T</p> <p>(1) Packing Type</p> <p>(2) Package Type</p> <p>(3) Lead Free</p>	<p>(1) T: Tube</p> <p>(2) TA3: TO-220</p> <p>(3) L: Lead Free, G: Halogen Free</p>
---	--

MARKING INFORMATION



■ ABSOLUTE MAXIMUM RATINGS (PER LEG) ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitance load, derate current by 20%.

PARAMETER SYMBOL		RATINGS	UNIT
DC Blocking Voltage		V_{RM} 50	V
Working Peak Reverse Voltage		V_{RWM} 50	V
Peak Repetitive Reverse Voltage		V_{RRM} 50	V
Average Rectified Output Current Per Device	Per Leg	15 A	
	Total 3	0	A
Non-Repetitive Peak Forward Surge Current 8.3ms Single Half Sine-Wave Superimposed on Rated Load		I_{FSM} 200	A
Operating Junction Temperature		T_J -65~	+150 $^{\circ}\text{C}$
Storage Temperature		T_{STG} -65~	+150 $^{\circ}\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL CHARACTERISTICS (PER LEG)

PARAMETER SYMBOL	RATINGS	UNIT
Junction to Case	θ_{JC} 2	$^{\circ}\text{C}/\text{W}$

■ ELECTRICAL CHARACTERISTICS (PER LEG) ($T_A=25^{\circ}\text{C}$ unless otherwise specified.)


PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Reverse Breakdown Voltage (Note 1)	$V_{(BR)R}$	$I_R=0.50\text{mA}$ 50				V
Forward Voltage Drop	V_{FM}	$I_F=15\text{A}$, $T_J=25^{\circ}\text{C}$			0.60	V
		$I_F=15\text{A}$, $T_J=125^{\circ}\text{C}$			0.55	V
Leakage Current (Note 1)	I_{RM}	$V_R=50\text{V}$, $T_J=25^{\circ}\text{C}$			300	μA
		$V_R=50\text{V}$, $T_J=125^{\circ}\text{C}$			100	mA

Notes: 1. Short duration pulse test used to minimize self-heating effect.


2. Thermal resistance junction to case mounted on heatsink.

■ TYPICAL CHARACTERISTICS


Forward Derating Curve



Typical Forward Characteristics



Typical Reverse Characteristics



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.