

Six-Pack



SPT⁺ IGBT

V_{CES} = 1200 V
 I_{C25} = 170 A
 $V_{CE(sat)\text{ typ.}}$ = 1.9 V

Preliminary data

Part name (Marking on product)

MIEB100W1200DPFTEH



E 72873

Features:

- SPT⁺ IGBT technology
- low saturation voltage
- low switching losses
- switching frequency up to 30 kHz
- square RBSOA, no latch up
- high short circuit capability
- positive temperature coefficient for easy parallelling
- MOS input, voltage controlled
- ultra fast free wheeling diodes
- solderable pins for PCB mounting
- space savings
- HiPerFRED™ diode

Application:

- AC motor control
- AC servo and robot drives
- power supplies

Package:

- designed for wave soldering
- with copper base plate

Output Inverter T1 - T6

Ratings

Symbol	Definitions	Conditions	min.	typ.	max.	Unit
V_{CES}	collector emitter voltage	$T_{VJ} = 25^\circ C$		1200		V
V_{GES}	max. DC gate voltage	continuous		± 20		V
V_{GEM}	max. transient collector gate voltage	transient		± 30		V
I_{C25}	collector current	$T_C = 25^\circ C$	171			A
I_{C80}		$T_C = 80^\circ C$	119			A
P_{tot}	total power dissipation	$T_C = 25^\circ C$	600			W
$V_{CE(sat)}$	collector emitter saturation voltage (on chip level) ①	$I_C = 100 A; V_{GE} = 15 V$ $T_{VJ} = 25^\circ C$ $T_{VJ} = 125^\circ C$	1.9 2.1	2.3 2.5		V
$V_{GE(th)}$	gate emitter threshold voltage	$I_C = 4 mA; V_{GE} = V_{CE}$	$T_{VJ} = 25^\circ C$	5	6	V
I_{CES}	collector emitter leakage current	$V_{CE} = V_{CES}; V_{GE} = 0 V$	$T_{VJ} = 25^\circ C$ $T_{VJ} = 125^\circ C$		1.4 6	mA mA
I_{GES}	gate emitter leakage current	$V_{GE} = \pm 20 V$			1	μA
C_{ies}	input capacitance	$V_{CE} = 25 V; V_{GE} = 0 V; f = 1 MHz$	7430			pF
$Q_{G(on)}$	total gate charge	$V_{CE} = 600 V; V_{GE} = 15 V; I_C = 100 A$	750			nC
$t_{d(on)}$	turn-on delay time	$T_{VJ} = 125^\circ C$ inductive load $V_{CE} = 600 V; I_C = 100 A$ $V_{GE} = \pm 15 V; R_G = 10 \Omega$ $L_S = 70 nH$	120			ns
t_r	current rise time		60			ns
$t_{d(off)}$	turn-off delay time		480			ns
t_f	current fall time		240			ns
E_{on}	turn-on energy per pulse		12			mJ
E_{off}	turn-off energy per pulse		10			mJ
$E_{rec(off)}$	reverse recovery losses at turn-off		6			mJ
RBSOA	reverse bias safe operating area	$V_{GE} = \pm 15 V; R_G = 10 \Omega;$ $V_{CEK} = 1200 V$			200	A
SCSOA	short circuit safe operating area					
t_{sc}	short circuit duration	$V_{CE} = 900 V; V_{GE} = \pm 10 V;$			10	μs
	short circuit current	$R_G = 3.9 \Omega$; non-repetitive				
R_{thJC}	thermal resistance junction to case	(per IGBT)			0.21	K/W
R_{thJH}	thermal resistance junction to heatsink	(IXYS test setup)			0.27	K/W

Output Inverter D1 - D6

Ratings

Symbol	Definitions	Conditions	min.	typ.	max.	Unit
V_{RRM}	max. repetitive reverse voltage	$T_{VJ} = 25^\circ C$		1200		V
I_{F25}	forward current	$T_C = 25^\circ C$	199			A
I_{F80}		$T_C = 80^\circ C$	127			A
V_F	forward voltage (on chip level) ①	$I_F = 100 A; V_{GE} = 0 V$ $T_{VJ} = 25^\circ C$ $T_{VJ} = 125^\circ C$	2.5 1.8			V
I_{rr}	max. reverse recovery current	$T_{VJ} = 125^\circ C$ inductive load $V_{CE} = 600 V; I_C = 100 A$ $V_{GE} = \pm 15 V; R_G = 10 \Omega$ $L_S = 70 nH; -di/dt = 2300 A/\mu s$	165			A
t_{rr}	reverse recovery time		290			ns
Q_{rr}			18.6			μC
E_{rec}			6			mJ
R_{thJC}	thermal resistance junction to case	(per diode)			0.3	K/W
R_{thJH}	thermal resistance junction to heatsink	(IXYS test setup)			0.39	K/W

 $T_C = 25^\circ C$ unless otherwise stated

Temperature Sensor NTC

Ratings						
Symbol	Definitions	Conditions	min.	typ.	max.	Unit
R_{25}	<i>resistance</i>		$T_c = 25^\circ\text{C}$	4.75	5.0	5.25
$B_{25/50}$				3375		K

Module


Ratings						
Symbol	Definitions	Conditions	min.	typ.	max.	Unit
T_{VJ}	<i>operating temperature</i>		-40		125	°C
T_{VJM}	<i>max. virtual junction temperature</i>				150	°C
T_{stg}	<i>storage temperature</i>		-40		125	°C
V_{ISOL}	<i>isolation voltage</i>	$I_{ISOL} \leq 1 \text{ mA}; 50/60 \text{ Hz}$	$t = 1 \text{ min}$ $t = 1 \text{ s}$		3000 3600	V~ V~
CTI	<i>comparative tracking index</i>				200	
M_d	<i>mounting torque (M5)</i>		3		6	Nm
$R_{\text{pin to chip}}$	<i>see ①</i>			2.5		mΩ
d_s	<i>creep distance on surface</i>		12.7			mm
d_A	<i>strike distance through air</i>		9.6			mm
Weight				300		g

$$\textcircled{1} \quad V_{CE} = V_{CE(\text{sat})} + 2x R_{\text{pin to chip}} \cdot I_c$$

$T_c = 25^\circ\text{C}$ unless otherwise stated



Curves are measured on modul level except Fig. 14 to Fig. 17

Equivalent Circuits for Simulation



Ratings						
Symbol	Definitions	Conditions	min.	typ.	max.	Unit
V_0	<i>IGBT</i>	$T1 - T6$	$T_{VJ} = 150^\circ\text{C}$		1.25 13	V mΩ
R_0						
V_0	<i>free wheeling diode</i>	$D1 - D6$	$T_{VJ} = 150^\circ\text{C}$		1.40 3.5	V mΩ
R_0						

Circuit Diagram




Part number

M = Module
I = IGBT
X = XPT
A = standard
150 = Current Rating [A]
W = Six-Pack
1200 = Reverse Voltage [V]
T = NTC
EH = E3-Pack

Outline Drawing

Dimensions in mm (1 mm = 0.0394")



Product Marking

Ordering	Part Name	Marking on Product	Delivering Mode	Base Qty	Ordering Code
Standard	MIEB100W1200DPFTEH	MIEB100W1200DPFTEH	Box	5	511348


Output Inverter IGBT


Fig. 1 Typ. output characteristics




Fig. 2 Typ. output characteristics




Fig. 3 Typ. transfer characteristics




Fig. 4 Typ. turn-on gate charge




Fig. 5 Typ. turn-on energy & switching times versus collector current




Fig. 6 Typ. turn-off energy & switching times versus collector current

Output Inverter IGBT




Fig. 7 Typ. turn-on energy and switching times versus gate resistor




Fig. 8 Typ. turn-off energy and switching times versus gate resistor




Fig. 9 Typ. transient thermal impedance


Output Inverter Diode

Fig. 10 Typ. forward characteristics




Fig. 11 Typ. reverse recovery characteristics




Fig. 12 Typ. reverse recovery characteristics




Fig. 13 Typ. transient thermal impedance