



SPECIFICATIONS

Current Rating: 5A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Pin Material: Brass/Tin-plated
 Solder Tabs: Brass/Tin-plated
 Material: Nylon 6T,UL94V-0

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
MIF-PVE-2X01	---	6.65
MIF-PVE-2X02	3.00	9.65
MIF-PVE-2X03	6.00	12.65
MIF-PVE-2X04	9.00	15.65
MIF-PVE-2X05	12.00	18.65
MIF-PVE-2X06	15.00	21.65
MIF-PVE-2X07	18.00	24.65
MIF-PVE-2X08	21.00	27.65
MIF-PVE-2X09	24.00	30.65
MIF-PVE-2X10	27.00	33.65
MIF-PVE-2X11	30.00	36.65
MIF-PVE-2X12	33.00	39.65

MORETHANALL
 CONNECTORS
 ASSEMBLIES

焯倫有限公司

PART NO. MIF-PVE-2Xxx

DWG NO. MIF-PVE-2Xxx

FILE NO.

UNIT / mm

SCALE 1:1

APPROVED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X
.XX
.XXX
AWG

DESCRIPTION: **3.00mm PITCH
180° WAFER, SMT TYPE, MICRO-FIT**

AREA	REVISIONS	HK	DATE
------	-----------	----	------