

MIP160, MIP162, MIP163, MIP164, MIP165, MIP166

Silicon MOS IC

■ Features


- Single chip IC with high breakdown voltage power MOS FET and CMOS control circuit
- Worldwide input (85 to 274VAC) possible
- Over-voltage protection at secondary section, pulse by pulse over-current protection, and intermittent operation timer at overload

■ Applications


- Switching mode regulator (5 to 40W)
- AC adapter
- Battery charger

■ Absolute Maximum Ratings (Ta= 25°C)

Parameter	Symbol	Rating	Unit
Drain voltage	V_D	700	V
Control voltage	V_C	8	V
Output current	I_D	I_{LIMIT}	A
Control current	I_C	0.1	A
Allowable power dissipation	P_D	1.7/12.5 * 1	W
Operating ambient temperature	T_{opr}	- 20 to + 85	°C
Channel temperature	T_{ch}	150	°C
Storage temperature	T_{stg}	- 55 to +150	°C

* 1 : T_C= 25°C

■ Block Diagram



■ Electrical Characteristics (Tc= 25± 2°C)

	Parameter		Symbol	Condition	Min	Typ	Max	Unit
Control function	Output frequency		f _{osc}	I _C = 4mA	90	100	110	kHz
	Maximum duty cycle		MAXDC	I _C = 2mA	64	67	70	%
	Minimum duty cycle		MINDC	I _C =10mA	1	2	3	%
Start up	Control pin charge current		I _C	V _C = 0V	- 2.4	-1.9	-1.2	mA
				V _C = 5V	- 2.0	-1.5	- 0.8	
	Control pin voltage at startup		V _{C (ON)}		5.0	5.7	6.3	V
	Control pin voltage at stop		V _{C (OFF)}		4.0	4.7	5.3	V
	Start/stop hysteresis voltage		ΔV _C		0.5	1.0	1.5	V
	Intermittent operation time-ratio		T _{SW} /T _{TIM}			5	8	%
	Intermittent operation frequency		f _{TIM}		0.5	1.2	2.0	Hz
Protection function	Over current protection/detection	MIP160	I _{LIMIT}		0.415	0.5	0.585	A
		MIP162			0.75	0.9	1.05	
		MIP163			1.12	1.35	1.57	
		MIP164			1.35	1.62	1.89	
		MIP165			1.88	2.25	2.63	
		MIP166			2.4	2.8	3.2	
	Blanking width at ON		t _{on(BLK)}	I _C = 4mA		0.25		μs
	Over current protection delay time		t _{d(OCL)}	I _C = 4mA		0.1		μs
	Over current protection temperature		T _{OTP}	I _C = 4mA	130	140	150	°C
	Over voltage protection/detection current		I _{ovp}		25	45	75	mA
	Latch reset voltage		V _{C reset}		2.3	3.3	4.2	V
Output	ON resistance	MIP160	R _{DS(ON)}	0.1A		15	18	Ω
		MIP162		0.3A		8.5	10	
		MIP163		0.3A		5.8	6.7	
		MIP164		0.5A		4.5	5.5	
		MIP165		0.8A		3.0	3.8	
		MIP166		1.0A		2.6	3.3	
	Drain pin leak current at OFF		I _{DSS}	V _{DS} = 650V, I _C = 4mA latch mode		0.5	0.9	mA
	Drain breakdown voltage		V _{DSS}	I _C = 4mA, I _p = 0.25mA latch mode	700			V
	Rise time		t _r			0.1	0.2	μs
	Fall time		t _f			0.1	0.2	μs
	Minimum drain voltage		V _{D(MIN)}		36			V
Supply voltage	Shunt regulator voltage		V _C	I _C = 4mA	5.5	5.8	6.1	V
	Control pin discharge current		I _{CD1}	at output MOS operation	0.7	1.4	1.8	mA
			I _{CD2}	at output MOS stop	0.5	0.8	1.1	mA