

isc Silicon NPN Power Transistors
MJ13070/13071
DESCRIPTION

- Collector-Emitter Sustaining Voltage-
: $V_{CEO(SUS)} = 400V(\text{Min})$ —MJ13070
= $450V(\text{Min})$ —MJ13071
- High Switching Speed
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS



- Designed for high-voltage ,high-speed, power switching in inductive circuits where fall time is critical. They are particularly suited for line operated switch-mode applications.
Typical applications:
- Switching regulators
- Inverters
- Solenoid and relay drivers
- Motor controls
- Deflection circuits

ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector- Base Voltage	MJ13070	650
		MJ13071	750
$V_{CEO(SUS)}$	Collector-Emitter Voltage	MJ13070	400
		MJ13071	450
V_{EBO}	Emitter-Base Voltage	6	V
I_C	Collector Current-Continuous	5	A
I_{CM}	Collector Current-Peak	8	A
I_B	Base Current-Continuous	2	A
I_{BM}	Base Current-Peak	4	A
P_C	Collector Power Dissipation@ $T_c=25^\circ\text{C}$	125	W
T_J	Junction Temperature	200	$^\circ\text{C}$
T_{stg}	Storage Temperature	-65~200	$^\circ\text{C}$

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance,Junction to Case	1.4	$^\circ\text{C/W}$



isc Silicon NPN Power Transistors

MJ13070/13071

ELECTRICAL CHARACTERISTICS

T_C=25°C unless otherwise specified

SYMBOL	PARAMETER		CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CEO(SUS)}	Collector-Emitter Sustaining Voltage	MJ13070	I _C =50mA ; I _B =0	400			V
		MJ13071					
V _{CE(sat)-1}	Collector-Emitter Saturation Voltage		I _C = 3A; I _B = 0.6A I _C = 3A; I _B = 0.6A; T _C =100°C			1.0 2.0	V
V _{CE(sat)-2}	Collector-Emitter Saturation Voltage		I _C = 5A; I _B = 1A			3.0	V
V _{BE(sat)}	Base-Emitter Saturation Voltage		I _C = 3A; I _B = 0.6A I _C = 3A; I _B = 0.6A; T _C =100°C			1.5 1.5	V
I _{CBO}	Collector Cutoff Current	MJ13070	V _{CB0} =650V; I _E =0 V _{CB0} =650V; I _E =0; T _C =100°C			0.5 2.5	mA
		MJ13071	V _{CB0} =750V; I _E =0 V _{CB0} =750V; I _E =0; T _C =100°C			0.5 2.5	
I _{EBO}	Emitter Cutoff Current		V _{EB} = 6V; I _C =0			1.0	mA
h _{FE}	DC Current Gain		I _C = 3A ; V _{CE} = 5V	8			
C _{OB}	Output Capacitance		I _E = 0; V _{CB} = 10V; f _{test} =1.0kHz		250		pF

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.