



Micro Commercial Components

Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

MJE13003A

Features

- Capable of 1.25Watts of Power Dissipation.
- Collector-current 1.5A
- Collector-base Voltage 700V
- Operating and storage junction temperature range: -55°C to +150°C
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0

NPN Silicon Plastic-Encapsulate Transistor

Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Max	Units
OFF CHARACTERISTICS				
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage ($I_C=10mA$, $I_B=0$)	400		Vdc
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage ($I_C=1000\mu A$, $I_E=0$)	700		Vdc
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage ($I_E=1000\mu A$, $I_C=0$)	9.0		Vdc
I_{CBO}	Collector Cutoff Current ($V_{CB}=700Vdc$, $I_E=0$)		1000	μA
I_{CEO}	Collector Cutoff Current ($V_{CE}=400Vdc$, $I_B=0$)		500	μA
I_{EBO}	Emitter Cutoff Current ($V_{EB}=9.0Vdc$, $I_C=0$)		1000	μA


ON CHARACTERISTICS

$h_{FE(1)}$	DC Current Gain ($I_C=0.5A$, $V_{CE}=5.0Vdc$)	8.0	40	
$h_{FE(2)}$	DC Current Gain ($I_C=1.5A$, $V_{CE}=5.0Vdc$)	5.0		
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage ($I_C=1000mA$, $I_B=250mA$)		1.0	Vdc
$V_{BE(sat)}$	Base-Emitter Saturation Voltage ($I_C=1000mA$, $I_B=250mA$)		1.2	Vdc
V_{BE}	Base-Emitter Voltage ($I_E=2000mA$)		3.0	Vdc

SMALL-SIGNAL CHARACTERISTICS

f_T	Transistor Frequency ($I_C=100mA$, $V_{CE}=10Vdc$, $f=1.0MHz$)	5.0		MHz
t_f	Fall Time	$V_{CC}=100V$, $I_C=1.0A$, $I_{B1}=I_{B2}=0.2A$	0.5	μS
t_s	Storage Time		2.5	μS


TO-126




DIMENSIONS

DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.291	0.307	7.40	7.80	
B	0.154	0.161	3.90	4.10	
C	0.083	0.091	2.10	2.30	
D	0.118	0.126	3.00	3.20	
E	0.046	0.056	1.17	1.37	
F	0.026	0.034	0.66	0.86	
G	0.09(Typ)		2.29(Typ)		
H	0.176	0.184	4.48	4.68	
J	0.417	0.433	10.60	11.00	
K	0.098	0.114	2.50	2.90	
L	0.602	0.618	15.30	15.70	
M	0.043	0.059	1.10	1.50	
N	0.018	0.024	0.45	0.60	


MJE13003A




DC Current Gain




Collector Saturation Region




Base-Emitter Voltage



Collector-Emitter Saturation Region



Collector Cutoff Region



Capacitance



Micro Commercial Components

Ordering Information

Device	Packing
(Part Number)-BP	Bulk;1Kpcs/Box

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp.* does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages.

*****APPLICATIONS DISCLAIMER*****

Products offer by *Micro Commercial Components Corp.* are not intended for use in Medical, Aerospace or Military Applications.