

isc Silicon NPN Power Transistor


MJE18004

DESCRIPTION

- Collector-Base Breakdown Voltage-
: $V_{(BR)CBO} = 1000V(\text{Min})$
- High Switching Speed
- Minimum Lot-to-Lot variations for robust device performance and reliable operation


APPLICATIONS

- Designed for use in 220V line-operated switchmode power supplies and electronic light ballasts



ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	1000	V
V_{CEO}	Collector-Emitter Voltage	450	V
V_{EBO}	Emitter-Base Voltage	9	V
I_C	Collector Current-Continuous	5	A
I_{CM}	Collector Current-Peak	10	A
I_B	Base Current	2	A
I_{BM}	Base Current-Peak	4	A
P_D	Total Power Dissipation@ $T_c=25^\circ\text{C}$	100	W
T_j	Junction Temperature	150	$^\circ\text{C}$
T_{stg}	Storage Temperature	-65~150	$^\circ\text{C}$



THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	1.25	$^\circ\text{C/W}$
$R_{th\ j-a}$	Thermal Resistance, Junction to Ambient	62.5	$^\circ\text{C/W}$

isc Silicon NPN Power Transistor
MJE18004
ELECTRICAL CHARACTERISTICS
T_j=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
V _{CE0(SUS)}	Collector-Emitter Sustaining Voltage	I _C = 30mA; I _B =0	450			V
V _{CE(sat)-1}	Collector-Emitter Saturation Voltage	I _C = 1 A ; I _B = 0.1A T _C =125°C			0.5 0.6	V
V _{CE(sat)-2}	Collector-Emitter Saturation Voltage	I _C = 2A ; I _B = 0.4 A T _C =125°C			0.45 0.8	V
V _{CE(sat)-3}	Collector-Emitter Saturation Voltage	I _C = 2.5A ; I _B = 0.5 A			0.75	V
V _{BE(sat)-1}	Base-Emitter Saturation Voltage	I _C = 1A; I _B = 0.1A			1.1	V
V _{BE(sat)-2}	Base-Emitter Saturation Voltage	I _C = 2A; I _B = 0.4A			1.25	V
V _{BE(sat)-3}	Base-Emitter Saturation Voltage	I _C = 2.5A; I _B = 0.5 A			1.3	V
I _{CES}	Collector Cutoff Current	V _{CE} = Rated V _{CE} ; V _{EB} = 0 T _C =125°C			0.05 0.5	mA
		V _{CE} = 800V T _C =125°C			0.01 0.1	
I _{CEO}	Collector Cutoff Current	V _{CE} = Rated V _{CE0} ; I _B = 0			0.1	mA
I _{EBO}	Emitter Cutoff Current	V _{EB} = 9V; I _C = 0			0.1	mA
h _{FE-1}	DC Current Gain	I _C = 1A ; V _{CE} = 5V	14		36	
h _{FE-2}	DC Current Gain	I _C = 2A ; V _{CE} = 1V	6			
h _{FE-3}	DC Current Gain	I _C = 10mA; V _{CE} = 5V	10			
f _T	Current-Gain—Bandwidth Product	I _C = 0.5A; V _{CE} = 10V; f _{test} =1.0MHz		13		MHz
C _{OB}	Output Capacitance	I _E = 0; V _{CB} = 10V; f _{test} =1.0MHz		450		pF

Switching Times Resistive Load, Duty Cycle ≤ 10%, Pulse Width = 20 μs

t _{on}	Turn-on Time	V _{CC} =250V , I _C =2.5A I _{B1} =I _{B2} =0.5 A		450	600	ns
t _S	Storage Time			2	3	μs
t _f	Turn-off Time			0.275	0.4	μs

isc Silicon NPN Power Transistor**MJE18004****NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.

