

isc Silicon NPN Darlington Power Transistor

MJE5742H

DESCRIPTION

- Collector-Emitter Breakdown Voltage
: $V_{CEO} = 400V(\text{Min})$
- Low Collector-Emitter Saturation Voltage
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS



- Switching Regulators
- Inverters
- Solenoid and relay drivers
- Motor control

ABSOLUTE MAXIMUM RATINGS($T_a = 25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CEV}	Collector-Base Voltage	650	V
$V_{CEO(SUS)}$	Collector-Emitter Voltage	400	V
V_{EBO}	Emitter-Base Voltage	8	V
I_C	Collector Current-Continuous	8	A
I_{CM}	Collector Current-Peak	16	A
I_B I_{BM}	Base Current- Continuous ---Peak	2.5 5	A
P_C	Collector Power Dissipation @ $T_C = 25^\circ\text{C}$	80	W
T_j	Junction Temperature	-65~150	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	-65~150	$^\circ\text{C}$

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	1.56	$^\circ\text{C/W}$



isc Silicon NPN Darlington Power Transistor


MJE5742H

ELECTRICAL CHARACTERISTICS

 $T_c = 25^\circ\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{CEO(SUS)}$	Collector-Emitter Breakdown Voltage	$I_C = 50\text{mA}$, $I_B = 0$	400			V
I_{CEV}	Collector Cutoff Current	$V_{CEV} = 650\text{V}$, $T_c = 25^\circ\text{C}$ $T_c = 100^\circ\text{C}$			1 5	mA
I_{EBO}	Emitter Cutoff Current	$V_{EB} = 8\text{V}$; $I_C = 0$			10	mA
h_{FE}	DC Current Gain	$I_C = 0.5\text{A}$; $V_{CE} = 5\text{V}$ $I_C = 4\text{A}$; $V_{CE} = 5\text{V}$	700 2000			
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C = 4\text{A}$; $I_B = 0.2\text{A}$ $I_C = 8\text{A}$; $I_B = 0.4\text{A}$ $I_C = 4\text{A}$; $I_B = 0.2\text{A}$, $T_c = 100^\circ\text{C}$			2.0 3.0 2.2	V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage	$I_C = 4\text{A}$; $I_B = 0.2\text{A}$ $I_C = 8\text{A}$; $I_B = 0.4\text{A}$ $I_C = 4\text{A}$; $I_B = 0.2\text{A}$, $T_c = 100^\circ\text{C}$			2.5 3.5 2.4	V

TYPICAL CHARACTERISTICS DC Current Gain



NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.