


MK5103



Cylinder sensor with GMR cell

MKT2028BARKG/G/ZH



- 1 fastening clamp
2 Sensing face



Electrical data

Operating voltage	[V]	10...30 DC; ("supply class 2" to cULus.)
Protection class		III
Reverse polarity protection		yes
Max. power-on delay time	[ms]	30

Outputs

Output function		normally open
Max. voltage drop switching output DC	[V]	4.5
Minimum load current	[mA]	5
Max. leakage current	[mA]	0,8
Permanent current rating of switching output DC	[mA]	100
Switching frequency DC	[Hz]	4000
Electrical design		PNP/NPN
Short-circuit protection		yes
Overload protection		yes

Range

Magnetic sensitivity	[mT]	2.8
Travel speed	[m/s]	> 10

Accuracy / deviations

Hysteresis	[mm]	1.5
Repeatability	[mm]	< 0.2

MK5103



Cylinder sensor with GMR cell

MKT2028BARKG/G/ZH

Operating conditions

Ambient temperature	[°C]	-25...85
Protection		IP 65; IP 67

Tests / approvals

EMC	EN 61000-4-2 ESD	- CD / 8 kV AD
	EN 61000-4-3 HF radiated	10 V/m
	EN 61000-4-4 Burst	2 kV
	EN 61000-4-6 HF conducted	10 V
	EN 55011	class B
MTTF	[years]	3145
UL Approval no.		C003

Mechanical data

Weight	[g]	26.4
Mounting		flush mountable
Cylinder type		T-slot cylinders
Dimensions	[mm]	25 x 5 x 6.5
Materials		PA; fastening clamp: stainless steel

Displays / operating elements

Display	switching status	1 x LED, yellow
---------	------------------	-----------------

Accessories

Accessories (supplied)	rubber placeholder: 1
	Cable clip: 1


Remarks

Remarks	fastening clamp with combined slot / hexagon socket, width across flats 1.5
Pack quantity	1 pcs.

Electrical connection

Cable: 2 m, PUR; 2 x 0.14 mm²

Connection



Core colours :

BN = brown
BU = blue